

### COUNTY OF SANTA CRUZ

#### PLANNING DEPARTMENT

701 OCEAN STREET, 4<sup>TH</sup> FLOOR, SANTA CRUZ, CA 95060 (831) 454-2580 FAX: (831) 454-2131 TDD: (831) 454-2123 **KATHY MOLLOY PREVISICH, PLANNING DIRECTOR** 

# ENVIRONMENTAL COORDINATOR NOTICE OF INTENT TO ADOPT A NEGATIVE DECLARATION AGENDA DATE: January 24, 2011 DETERMINATION DATE: February 3, 2011

Pursuant to the California Environmental Quality Act, the following projects have been reviewed by the County Environmental Coordinator to determine if they have a potential to create significant impacts to the environment and, if so, how such impacts could be solved. A negative declaration has been prepared in cases where the project is determined not to have any significant environmental impacts. An environmental impact report (EIR) will be prepared for projects, which could have a significant impact.

Public review periods are provided for these Environmental Determinations according to the requirements of the County Environmental Review Guidelines, depending upon whether State agency review is required or whether an EIR is required. The environmental documents are available for review at the County Planning Department at 701 Ocean Street, Santa Cruz. You may also view environmental documents on the web at <a href="https://www.sccoplanning.com">www.sccoplanning.com</a> under the Planning Department menu, Agendas link. If you have questions or comments about these determinations please contact Matt Johnston of the Environmental Review staff at (831) 454-3201

The County of Santa Cruz does not discriminate on the basis of disability, and no person shall, by reason of a disability, be denied the benefits of its services, programs or activities. If you require special assistance in order to review this information, please contact Bernice Romero at (831) 454-3137 (TDD number (831) 454-2123 or (831) 763-8123) to make arrangements.

#### 09-0407 CUNNISON LN. AND SOQUEL DR., SOQUEL APN(S): 037-101-58,-59

The proposal to develop a neighborhood park and a community center to include an approximately 4,584 square foot one-story community center, 225 square foot restroom building, pedestrian pathways, replacement pedestrian bridge over an unnamed arroyo (including associated required mitigation restoration and elective stream/habitat restoration), sports play area with a half basketball court, skate area, children's play areas, gardens (community, heritage and native), bocce court, picnic tables, benches, kiosk, on-site parking, and approximately 6,800 cubic yards of grading. The project includes a 5 Year Master Plan with potential construction phasing. The project requires a Park Master Site Plan Development Permit, Riparian Exception, Parking Plan, Preliminary Grading Approval, and a Variance to increase the impervious surface area from approximately 20 percent to 29 percent.

**ZONE DISTRICT: PR (Parks, Recreation, and Open Space)** 

APPLICANT: County of Santa Cruz Redevelopment Agency and Parks Department

OWNER: Santa Cruz County Redevelopment Agency PROJECT PLANNER: Sheila McDaniel, 454-3439

EMAIL: pln056@co.santa-cruz.ca.us

**ACTION: Negative Declaration with mitigations** 

REVIEW PERIOD: FEBUARY 3, 2011 TO MARCH 5, 2011

This project will be considered at a public hearing by the Planning Commission. The time, date and location have not been set. When scheduling does occur, these items will be included in all public hearing notices for the project.

NAME:

The Farm Neighborhood Park

APPLICATION: 09-0407

A.P.N:

037-101-58, 59

#### **NEGATIVE DECLARATION MITIGATIONS**

- In order to ensure that the mitigation measures and conditions set forth in the proposed project Α. description are communicated to the various parties responsible for constructing the project, prior to any disturbance on the property the applicant shall convene a pre-construction meeting on the site. The following parties shall attend: The project engineer, project contractor supervisor, Santa Cruz County Environmental Planning staff, and project biologists. Results of pre-construction biotic surveys will be collected at that time and all protection measures, including tree protection fencing and limits of disturbance, shall be inspected.
- In order to avoid impacts to special status bats, tree removal activities shall be limited to the B. months between November 1 and March 1, if feasible.
  - If trees must be removed outside of the timeframe above, a qualified biologist shall conduct surveys for special status bats 3-4 weeks prior to site disturbance. If active roosts are present in trees to be retained, roosting bats shall be excluded from trees to be removed prior to any disturbance. In trees to be retained, no disturbance zones, set by the biologist based on the particular species present, shall be fenced off around the subject tree to ensure other construction activities do not harm sensitive species.
  - 2. The maternity roosting season for bats is March1 July 3. Tree removal should be scheduled outside of the maternal roosting period if special status bats are present. Before any trees are removed during the maternal roosting season, a qualified biologist shall perform surveys. If maternal roosts are present, disturbance shall be avoided until roosts are unoccupied. The biologist shall be responsible for ensuring bat roosts are vacated.
- C. In order to avoid impacts to raptors and migratory songbirds, tree removal activities shall be limited to the months between September 1 and February 1, if feasible.
  - 1. If trees must be removed outside of the timeframe above, a qualified biologist shall conduct surveys for raptor or migratory songbird nests 3-4 weeks prior to site disturbance.
    - a. If active raptor or migratory bird nests are found in trees to be retained, the biologist shall be required to be on site during any initial vegetation or ground disturbance activities (e.g. vegetation clearing, grading, excavation, tree pruning/removal) that could potentially impact listed species. The biologist shall be responsible for setting and maintaining the disturbance buffers from active nests during construction activities, and buffers and exclusionary measures shall be implemented only after consultation with CDFG.
    - b. If no active nests are present on the subject parcel, tree removal can proceed provided the mitigations in B. above have been implemented.
- In order to mitigate impacts of nighttime lighting on the riparian habitat, prior to issuance of a D. building permit, the applicant shall submit a lighting plan to the Planning Department for review and approval. The plan shall reflect that permanent outdoor lighting shall be shielded by fixture design or other means to minimize illumination of riparian habitat. Light sources that do not attract insects (e.g. yellow or sodium vapor bulbs) shall be used if outdoor lighting is necessary (e.g. security or handicap access structures).
- E. In order to ensure that no significant impacts occur as a result of construction noise related to the project, the following mitigations shall be incorporated into the conditions of approval:
  - 1. Construction shall be restricted between 8 a.m. to 6 p.m.
  - 2. No construction shall occur on weekends.

- 3. All internal combustion engines with intake and exhaust mufflers shall be maintained in good condition.
- 4. Project construction shall utilize "quiet" air compressors and other stationary noise sources where technology exists.
- 5. The project shall designate a "noise coordinator" who is responsible for responding to any local complaints about construction noise. The disturbance coordinator shall determine the cause of the noise complaint (e.g., starting early, bad muffler, etc.) and will require that reasonable measures warranted to correct the problem be implemented. The applicant shall post a telephone number for the disturbance coordinator at the construction site and include it in the notice sent to neighbors regarding the construction schedule.
- F. In order to reduce the impacts to trees to be retained to a less than significant level, prior to issuance of building permits, the applicant shall provide a tree protection plan to the Planning Department for review and approval.



## County of Santa Cruz

#### PLANNING DEPARTMENT

701 OCEAN STREET,  $4^{TH}$  FLOOR, SANTA CRUZ, CA 95060 (831) 454-2580 FAX: (831) 454-2131 TDD: (831) 454-2123

KATHLEEN MOLLOY PREVISICH, PLANNING DIRECTOR

www.sccoplanning.com

## CALIFORNIA ENVIRONMENTAL QUALITY ACT (CEQA) ENVIRONMENTAL REVIEW INITIAL STUDY

**Date:** 11/22/10 **Application Number: 09-0407** 

**Staff Planner**: Sheila McDaniel

#### I. OVERVIEW AND ENVIRONMENTAL DETERMINATION

**APPLICANT**: Santa Cruz County

Redevelopment Agency and Parks

Department

**OWNER**: Santa Cruz County

Redevelopment Agency

**APN(s)**: 037-101-58, -59

**SUPERVISORAL DISTRICT**: 1<sup>st</sup> District

**PROJECT LOCATION**: The property is located on the northwest corner of Cunnison Lane and Soquel Drive about ¾ mile East of Porter Street and Soquel Drive, within the Soquel Planning area.

**SUMMARY PROJECT DESCRIPTION**: Proposal to develop a neighborhood park and a community center to include an approximately 4,584 square foot one-story community center, 225 square foot restroom building, pedestrian pathways, replacement pedestrian bridge over an unnamed arroyo (including associated required mitigation restoration and elective stream/habitat restoration), sports play area with a half basketball court, skate area, children's play areas, gardens (community, heritage and native), bocce court, picnic tables, benches, kiosk, on-site parking, and approximately 6,800 cubic yards of grading. The project includes a 5 Year Master Plan with potential construction phasing. The project requires a Park Master Site Plan Development Permit, Riparian Exception, Parking Plan, Preliminary Grading Approval, and a Variance to increase the impervious surface area from approximately 20 percent to 29 percent.

<b>ENVIRONMENTAL FACTORS POTENTIALLY AFFECTED:</b> All of the following potential environmental impacts are evaluated in this Initial Study. Categories that are marked have been analyzed in greater detail based on project specific information.						
$\boxtimes$	Geology/Soils	$\boxtimes$	Noise			
$\boxtimes$	Hydrology/Water Supply/Water Quality		Air Quality			
$\boxtimes$	Biological Resources		Greenhouse Gas Emissions			
	Agriculture and Forestry Resources		Public Services			
	Mineral Resources	$\boxtimes$	Recreation			
	Visual Resources & Aesthetics	$\boxtimes$	Utilities & Service Systems			
	Cultural Resources		Land Use and Planning			
	Hazards & Hazardous Materials		Population and Housing			
$\boxtimes$	Transportation/Traffic		Mandatory Findings of Significance			
DISC	CRETIONARY APPROVAL(S) BEING CO	NSIE	DERED:			
	General Plan Amendment		Coastal Development Permit			
	Land Division	$\boxtimes$	Grading Permit			
	Rezoning	$\boxtimes$	Riparian Exception			
	Development Permit	$\boxtimes$	Other: Park Site Master Plan			
NON	-LOCAL APPROVALS					
Othe	r agencies that must issue permits or auth	noriza	itions:			
United State Fish and Wildlife Service Incidental Take Permit California Water Resources Control Board, Section 401 Water Quality Certification United States Army Corps of Engineers Permit California Department of Fish and Game Streambed Alteration Agreement Regional Water Quality Control Board Approval						
DET	ERMINATION: (To be completed by the le	ead a	gency)			
On t	ne basis of this initial evaluation:					
	I find that the proposed project COULD Nenvironment, and a NEGATIVE DECLAR		_			
	I find that although the proposed project of environment, there will not be a significant the project have been made or agreed to NEGATIVE DECLARATION will be prepared	nt effe by th	ect in this case because revisions in			

CEQ. Page	QA Environmental Review Initial Study ge 3	
	I find that the proposed project MAY had and an ENVIRONMENTAL IMPACT RE	ve a significant effect on the environment, PORT is required.
	I find that the proposed project MAY has "potentially significant unless mitigated" one effect 1) has been adequately analyapplicable legal standards, and 2) has beased on the earlier analysis as describe ENVIRONMENTAL IMPACT REPORT effects that remain to be addressed.	impact on the environment, but at least yzed in an earlier document pursuant to been addressed by mitigation measures ed on attached sheets. An
	standards, and (b) have been avoided of	nificant effects (a) have been analyzed VE DECLARATION pursuant to applicable or mitigated pursuant to that earlier EIR or revisions or mitigation measures that are
	atthew Johnston vironmental Coordinator	Date

#### II. BACKGROUND INFORMATION

EXISTING SITE CONDITIONS	
Parcel Size: 037-101-58 = 3.7 acres, 037-	101-59 = 1.7 acres, Total = 5.5 acres
Existing Land Use: Vacant County Land	
<b>Vegetation:</b> The site contains coast live oa oak forest, California annual grassland, dev aquatic	
Slope in area affected by project:0 -	30% 31 – 100%
Nearby Watercourse: Un-named epheme direction	
<b>Distance To:</b> The stream follows the east swithin the approximate center of APN 037-1	
ENVIRONMENTAL RESOURCES AND CO	DNSTRAINTS
Groundwater Supply: No	Liquefaction: No
Water Supply Watershed: No	Fault Zone: No
Groundwater Recharge: No	Scenic Corridor: No
Timber or Mineral: No	Historic: No
Agricultural Resource: No	Archaeology: No
Biologically Sensitive Habitat: Yes	Noise Constraint: No
Fire Hazard: No	Electric Power Lines: No
Floodplain: No	Solar Access: N/A
Erosion: No	Solar Orientation: Southern
Landslide: No	Hazardous Materials: No
SERVICES	
Fire Protection: Central Fire Protection	<b>Drainage District</b> : Zone 5 Flood Control District
School District: Soquel	Project Access: Soquel Drive
Sewage Disposal: Santa Cruz County Sanitation District	Water Supply: Soquel Creek Water District
PLANNING POLICIES	
Zone District: PR (Parks, Recreation, and Open Space) General Plan: O-R (Existing Parks and Parks)	Special Designation: No
Recreation), PK-N (Neighborhood Park) Urban Services Line:	Outside
	U Outside
Coastal Zone: Inside	

#### PROJECT BACKGROUND:

Up until the early 1990s, this property contained The Farm Greenhouse Restaurant ("The Farm") which was the name of a restaurant, bakery and gift shop, with a fruit orchard, and flower and vegetable gardens. The Farm also catered outdoor weddings and receptions, sited amidst landscaped grounds. The Farm site buildings were occupied from 1993 through 2001, after which time the buildings were unoccupied.

In 1991 the County Board of Supervisors authorized the Redevelopment Agency to purchase the project site for future use as a neighborhood park and community facility. At the time, the park was part of a larger group of properties that were proposed to be developed as apartments and residences. The Board of Supervisors subsequently approved a plan that reconfigured the properties to create 39 affordable apartments and six single-family dwelling lots, retaining the 5.5 acre project site for future park development. The Farm buildings were removed over a period of years after purchase by the Redevelopment Agency until removal of the last remaining buildings occurred in 2007.

Development of the park project is a collaborative effort of the County of Santa Cruz Redevelopment Agency and the County of Santa Cruz Parks, Open Space and Cultural Services Department, who will operate and maintain the park after its completion. The programs for the park and the design of the site are the product of a series of neighborhood meetings and workshops and two Parks Commission hearings where a significant number of residents in the vicinity became actively involved in identifying the park features that would meet their recreational and open space needs. Following these meetings, the Board of Supervisors approved the Park Site Master Plan at a public hearing on November 21, 2006. The park master plan calls for the development of a LEED-certified community center building, community gardens, restrooms, parking lots, outdoor benches, pathways with interpretive signage, play structures, a skate board feature, a basketball half-court, heritage and native plants gardens, an outdoor sculpture and interpretive program elements.

This initial study is the next step in the entitlement process before permit review and approval by the Planning Commission and construction of the facility.

#### **ENVIRONMENTAL SETTING AND SURROUNDING LAND USES:**

The property is a County-owned five and one half acre site divided by a riparian corridor traveling north south through the property. The property is comprised of two separate assessor's parcels. The larger of the two sites is located at the corner of Soquel Drive and Cunnison Lane (to be referred to as the Cunnison Lane/Soquel Drive parcel), approximately ¾ of a mile east of Soquel Drive and Porter Street. The smaller site is located on the eastern end of Tee Street (to be referred to as the Tee Street parcel), extending east from Hardin Way, and north of Soquel Drive.

The property is bordered by Soquel Drive to the south, Cunnison Lane to the east, and Tee Street to the west. The property is otherwise surrounded by single family residentially developed property on all sides. The Farm multi-residential housing development is located to the east of the site on Cunnison lane.

Both properties contain an ephemeral stream that travels in a north/south direction through the property. The stream follows the eastern edge of the Tee Street parcel and provides a substantial riparian corridor that occupies approximately half of this site. The ephemeral creek also travels through the Cunnison Lane/Soquel Drive Lane parcel from the northeast to southwest of the site toward Soquel Drive. As a result of this stream, and associated riparian corridor, the property is physically divided into two separate development areas, one located and accessed from Tee Street and one located and accessed by Soquel Drive and Cunnison lane. These areas were previously connected via an existing pedestrian bridge that was removed.

Topographically speaking, the property generally slopes to the southwest with an elevation range of 160 to 120 feet. The site contains an approximately fifteen to twenty-five foot depression where the ephemeral stream channel is located.

Site vegetation is comprised of approximately 2 acres of coast live oak riparian forest/eucalyptus trees along the unnamed ephemeral creek, 1/3 of an acre of coast live oak forest on the west side of property located on the Tee Street portion of the site, 1.7 acres of California annual grassland located on both sides of the creek, 1.2 acres of developed/ornamental vegetation comprised of agricultural fields including fruit orchards and field crops, and .07 acres of ephemeral aquatic habitat located in the ephemeral creek.

The property currently contains remnants of historic development including asphalt paving, portions of remaining fencing, and remnant soil mounds.

#### **DETAILED PROJECT DESCRIPTION:**

For purposes of clarity, the project description has been broken into three distinct areas of site development: The area located adjacent to Cunnison Lane/Soquel Drive, the area adjacent to Tee Street, and the Riparian Corridor area/creek area. These areas are as follows:

#### **Cunnison Lane/Soquel Drive**

This portion of the project site includes a proposed 4,584 square foot one-story community building with an assembly room with a small "warming" kitchen, two classrooms/art studios, kiln room, an office, foyer gallery, restrooms, outdoor building terrace and patios. Fifty four parking spaces are provided on site along Cunnison Lane and adjacent to Soquel Drive. The site also provides a half basketball court and skate facility located adjacent to Soquel Drive. Also proposed are community gardens,

heritage gardens, and native gardens located on the northeast portion of the site, as well as pedestrian pathways throughout the site, and nature trails alongside the riparian corridor area. Vehicular access to this site is proposed along two locations on Cunnison Lane. Pedestrian access is proposed from both Soquel Drive and Cunnison Lane. A gated entry is proposed at both vehicle site entry locations.

#### **Tee Street Improvements**

This portion of the park is proposed to contain a 225 square foot restroom building, four parking spaces on site, three children's play areas, picnic areas, benches, multipurpose turf areas, nature trails, and a bocce ball court, as well as nature trails alongside the riparian corridor. Access to the four proposed parking spaces is via Tee Street. A gated entry is proposed at this vehicle site entry.

#### Riparian Corridor/Creek Area

The project proposes creek stabilization work within the creek channel that includes habitat restoration throughout the channel. In stream habitat restoration and riparian plantings within the corridor associated with creek restoration. The project plans include detailed restoration plans referencing the recommended restoration measures of the biotic report (Attachment 5) as well as erosion control plans.

Four principal areas of restoration are proposed for this project: Oak riparian mitigation to promote high quality habitat; Oak tree replacement mitigation within the riparian area for replacement of trees removed elsewhere on the site; Riparian corridor buffer plantings, which include removal of invasive species; and, park restoration plantings throughout the site and planting of native species to improve habitat value.

Other project work within the corridor includes pedestrian bridge construction to connect the two development areas of the park on Tee Street and Cunnison Lane. This involves bridge abutments and some oak tree trimming and requires a Riparian Exception.

#### **Parks Program Statement**

The Parks, Open Space and Cultural Services Department has provided a program statement (Attachment 15) that details the program specific uses proposed for the park and community center. Hours of operation for the proposed park are generally proposed between sunrise and sunset for outdoor recreation, picnic, play areas, nature trails, etc. The hours of operation for the community building, with associated classrooms, is generally proposed between 8 am and 10 p.m., with early morning classes starting as early as 7 a.m. During the weekdays, of the total 58 on site parking spaces, 45 parking spaces are to be dedicated to the community center uses and 13 spaces dedicated to outdoor uses. During the weekends, 37 space of the total 58 parking spaces are proposed to be dedicated for community center use and 21 spaces are available for outdoor uses at the park.

The three rooms of the community center are proposed to be occupied at various times of the day, based on the park program statement. The occupancy of the community center classrooms are proposed to be limited by the total number of parking spaces on site minus the required parking demand for the outdoor recreational uses on the weekdays and weekend. At no time will the parking required for general park usage, as determined by the traffic study, be used for the community center uses. The Program Statement includes a Parking Matrix (Attachment 15) that provides greater detail regarding the classroom occupancy of the various rooms on the weekdays and weekend. Upon completion of construction, the Parks Department will manage the park site, and program uses, including the classroom schedule.

#### Grading

The project requires approximately 6,800 cubic yards of cut and 1,900 cubic yards of fill for site preparation, mostly in the area of Cunnison lane, to address the challenges of sloping site topography for development of parking and circulation, site accessibility requirements, and to create a natural appearing slope.

Less than
Significant
with
Mitigation
Incorporated

Less than Significant Impact

No Impact

#### III. ENVIRONMENTAL REVIEW CHECKLIST

#### A. GEOLOGY AND SOILS

Would the project:

1.	pot incl	oose people or structures to ential substantial adverse effects, luding the risk of loss, injury, or ath involving:			
	A.	Rupture of a known earthquake fault, as delineated on the most recent Alquist-Priolo Earthquake Fault Zoning Map issued by the State Geologist for the area or based on other substantial evidence of a known fault? Refer to Division of Mines and Geology Special Publication 42.			
	B.	Strong seismic ground shaking?			
	C.	Seismic-related ground failure, including liquefaction?		$\boxtimes$	
	D.	Landslides?		$\boxtimes$	

**Discussion (A through D):** The project site is located outside of the limits of the State Alquist-Priolo Special Studies Zone (County of Santa Cruz GIS Mapping, California Division of Mines and Geology, 2001). However, the project site is located approximately 7 miles to the southwest of the San Andreas fault zone, and 4 miles to the southwest of the Zayante Fault. While the San Andreas fault is larger and considered more active, each fault is capable of generating moderate to severe ground shaking from a major earthquake. Consequently, large earthquakes can be expected in the future. The October 17, 1989 Loma Prieta earthquake (magnitude 7.1) was the second largest earthquake in central California history.

All of Santa Cruz County is subject to some hazard from earthquakes. However, the project site is not located within or adjacent to a County or State mapped fault zone. A geotechnical investigation for the proposed project was performed by Haro, Kasunich and Associates, Inc. and dated November 23, 2009 (Attachment 3). The report states that "Potential seismic hazards include structural damage from seismic shaking, surface ground rupture, liquefaction, and land sliding." "The potential for seismic induced liquefaction at the site is relatively low." "The potential for seismic

CEQA Environmental Review Initial Study Page 10

Potentially Significant Impact Less than
Significant
with
Mitigation
Incorporated

Less than Significant Impact

No Impact

induced land sliding on gently sloping areas of the property is also relatively low." The geotechnical report recommendations are included in the design of the project. The report is required to be updated prior to issuance of the building permit to address evaluation of scour, and how it will affect proposed foundation design, as well as updated seismic design parameters for the most current building code (as of January 1, the 2010 CBC will be in effect). This will ensure that structural damage as a result of an event will be low, which will result in a less than significant impact.

of an	of an event will be low, which will result in a less than significant impact.						
2.	Be located on a geologic unit or soil that is unstable, or that would become unstable as a result of the project, and potentially result in on- or off-site landslide, lateral spreading, subsidence, liquefaction, or collapse?						
instable building setbal proportion of the loop prior of the loop	<b>Discussion:</b> The geotechnical report concluded that the "potential for deep seated instability of the creek bank slopes which would affect the proposed community center building or pedestrian bridge abutments is low." The proposed community building is setback approximately 35 feet, which provides for an adequate setback for the proposed building. The community center site is underlain by clay soil, which is known for expansion. The report recommends re-densification of the soil at the proposed spread footing building pads. The upper parking lot area is comprised of silty sand and the lower parking lot is comprised of clayey sand. Additional testing is recommended prior to determination of sub grade elevations of these areas and will be implemented during the project construction.						
	ecommendations contained in the geotechemented to reduce this potential hazard to	•			e		
3.	Develop land with a slope exceeding 30%?			$\boxtimes$			
to slo	ussion: There are slopes that exceed 30% nunity building is set back 35 feet from the pes in excess of 30%. However, creek reposed to occur on slopes that exceed 30 per the quality of the habitat and is not expected.	slope and estoration w rcent slope	is not with ork along . This wor	in close pro the creek l k is intend	oximity banks is ed to		
4.	Result in substantial soil erosion or the loss of topsoil?						

**Discussion:** Some potential for erosion exists during the construction phase of the project; however, this potential is minimal because the plans provide an erosion control plan that includes standard erosion control measures as a required condition of the project. As typically noted in the conditions of approval, prior to approval of a grading or building permit the project must have an approved Erosion Control Plan that

CEQA E Page 11	nvironmental Review Initial Study	Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impact			
specifies detailed erosion and sedimentation control measures. The plan includes provisions for disturbed areas to be planted with ground cover and to be maintained to minimize surface erosion. The potential for erosion is less than significant.								
5.	Be located on expansive soil, as defined in Section 1802.3.2 of the California Building Code (2007), creating substantial risks to life or property?				<u> </u>			
<b>Discussion:</b> According to the geotechnical report for the project, noted above, there are indications of expansive soils in the project area. The recommendations contained in the geological report, including re-densification of the soil pads for the proposed community center and restroom building shall be implemented during construction to adequately mitigate this potential hazard to a less than significant impact.								
6.	Place sewage disposal systems in areas dependent upon soils incapable of adequately supporting the use of septic tanks, leach fields, or alternative waste water disposal systems where sewers are not available?							
<b>Discussion</b> : No septic systems are proposed. The project will connect to the Santa Cruz County Sanitation District (Attachment 11), and the applicant will be required to pay standard sewer connection and service fees that fund sanitation improvements within the district as a Condition of Approval for the project.								
7.	Result in coastal cliff erosion?				$\boxtimes$			
<b>Discu</b> and th	ession: The proposed project is not located erefore, would not contribute to coastal cl	d in the vi iff erosion	cinity of a (	coastal cli	ff or bluff;			
	TOROLOGY, WATER SUPPLY, AND WA	TER QUA	ALITY		•			
1.	Place development within a 100-year flood hazard area as mapped on a federal Flood Hazard Boundary or Flood Insurance Rate Map or other flood hazard delineation map?							
Nation	rssion: According to the Federal Emerger nal Flood Insurance Rate Map, dated Marc ithin a 100-year flood hazard area.	ncy Manag ch 2, 2006	gement Ag 3, no portio	ency (FEN n of the p	MA) roject site			

CEQA I Page 12	Environmental Review Initial Study 2	Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impact	
2.	Place within a 100-year flood hazard area structures which would impede or redirect flood flows?					
<b>Discussion:</b> According to the Federal Emergency Management Agency (FEMA) National Flood Insurance Rate Map, dated March 2, 2006, no portion of the project si lies within a 100-year flood hazard area.						
3.	Be inundated inundated by a seiche, tsunami, or mudflow?		. 🗆			
4.	Substantially deplete groundwater supplies or interfere substantially with groundwater recharge such that there would be a net deficit in aquifer volume or a lowering of the local groundwater table level (e.g., the production rate of pre-existing nearby wells would drop to a level which would not support existing land uses or planned uses for which permits have been granted)?					
<b>Discussion:</b> The project would obtain water from Soquel Creek Water District and would not rely on private well water. Although the project would incrementally increase water demand, Soquel Creek Water District has indicated that adequate supplies are available to serve the project (Attachment 10). The Soquel Creek Water District has conditioned the project to provide offsets for new water service.						
5.	roject is not located in a mapped groundw  Substantially degrade a public or private water supply? (Including the contribution of urban contaminants, nutrient enrichments, or other agricultural chemicals or seawater intrusion).					
Discu	ussion: The project will not affect a public	or private	water supp	oly.		
6.	Degrade septic system functioning?				$\boxtimes$	
	ussion: There is no indication that existing ed by the project.	septic sy	stems in th	e vicinity v	would be	

CEQA E	Environmental Review Initial Study 3	Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impact
7.	Substantially alter the existing drainage pattern of the site or area, including through the alteration of the course of a stream or river, or substantially increase the rate or amount of surface runoff in a manner which would result in flooding, on- or off-site?				· 🔲
within Hydra dated would The p the vid	and alongside an ephemeral stream characters. The proposed project includes stream allics Final Report (Attachment 13) prepared July 29, 2009 determined the recommend not be an alteration to the stream channel project is conditioned to require the soils recinity of bridge abutments for foundation on and grading permits.	nnel. A Stred by Meaded bridgeles as a reseport to pro	ream Hydresiti-Miller Ele height to ult of the be ovide an ar	ology and ngineering ensure the ridge considers of second the ridg	g, Inc., at there struction. scour in
report	project is designed to comply with the reco t to ensure that there are no alterations to ruction of the bridge.	mmendati the strear	ions of the s	stream hy as a result	drology of
14) progression areas required developments are rainward productions.	proposed project includes an On-Site Storm repared by Mesiti-Miller Engineering, Inc., are proposed to increase by 60,501 squares a detention system to mitigate hydrologopment run-off at the pre-development run psed detention system on the Cunnison Large flows into the street. The tee street drain rater garden system designed to allow per provide a usable surface. Off site improve the ess project proposed improvements to ensistream drainage system.	dated Augare feet as gic changen-off rate. ane portion age plans colation of ements ide sure that fl	gust 4 <sup>th</sup> , 20 a result of es and to m The project of the pro s provide a f run-off into entified in It ooding doe	09. Imperthe project design in ject design detention, or the grouper 8 belows not occur.	ervious  ct. This  cst  ncludes a  ned to  /retention  ndwater  w,  ur in the
The p	plan improvements will ensure that the pro	ject does	not result i	n flooding	on or off
8.	Create or contribute runoff water which would exceed the capacity of existing or planned storm water drainage systems, or provide substantial additional sources of polluted runoff?				
<b>Disc</b> Repo	<b>ussion:</b> Drainage calculations included in ort (Attachment 14) prepared by Mesiti-Mil	the Off- S ler Engine	Site Storm [ ering, Inc.,	Orainage F dated Ju	Final ly 11 <sup>th</sup> ,

CEQA Environmental Review Initial Study Page 14

Potentially Significant Impact Less than
Significant
with
Mitigation
Incorporated

Less than Significant Impact

No Impact

2009 have been accepted by the Department of Public Works (DPW) Drainage Section staff. Some of the downstream drainage facilities are not adequately sized to accommodate existing or proposed runoff. The calculations show that as a result of the proposed drainage runoff, project upgrades are required to be completed to a number of downstream drainage facilities impacted by the proposed project. The report recommends drainage upgrades to Soquel Drive East and Soquel Junction drainage areas, as noted in the report, and includes pipe diameter enlargement, replacement of three existing inlets, replacement of one existing junction structure, adjustment/replacement of another junction structure, and replacement of a manhole cover for adjustments of new pipe elevations. The project plans address these requirements. The project is conditioned to provide final drainage details and analysis prior to issuance of the building permit.

adjus cove requi	cement of three existing inlets, replacement stment/replacement of another junction struing replacements of new pipe elevations. The project is conditioned to prote to issuance of the building permit.	cture, and he project	replacement plans add	ent of a ma ress these	nhole
9.	Expose people or structures to a significant risk of loss, injury or death involving flooding, including flooding as a result of the failure of a levee or dam?				
Disc	ussion:				
10.	Otherwise substantially degrade water quality?			$\boxtimes$	
to en	ussion: The project includes a detention saure that contaminants do not enter into the formaintenance will be required to minimise a standard condition of approval and is required to minimise a standard condition of approval and is required.	e drainage nize the eff	e system w fects of url	rithout treat oan pollutar	ment. nts.
	IOLOGICAL RESOURCES Id the project:				
1.	Have a substantial adverse effect, either directly or through habitat modifications, on any species identified as a candidate, sensitive, or special status species in local or regional plans, policies, or regulations, or by the California Department of Fish and Game, or U.S. Fish and Wildlife Service?				

**Discussion:** A Biotic Report was prepared for this project by H.T. Harvey and Associates Ecological Consultants, dated December 4, 2009 (Attachment 4 and 5, Excerpts, full report on file). It identified 30 special-status plants that occur in habitat types similar to those found on the project site, assessed potential impacts to these species as a result of the proposed project, and recommended measures to reduce

Less than
Significant
with
Mitigation
Incorporated

Less than Significant Impact

No Impact

impacts to less than significant. These measures have been incorporated into the project design.

#### Less than Significant Impacts:

The report concluded that there are three impacts that are less than significant. Impacts to annual grassland that occur in less than optimal habitat area due to previous development disturbance. Impacts to the Maple-leaved checkerbloom can be assumed to be absent, based on the disturbed condition of the site. This species was not observed on the site, and although it may still be present the report concluded that the likelihood is low considering that the habitat is poor. Removal of non-natives will benefit the Maple-leaved checkerbloom.

Lastly, several special status wildlife species may occur on the site, but are not expected to breed there. This includes the bank swallow, western red bat, yellow warbler, and tri-colored blackbird. The project will have no effect on the breeding success of these species. Project activities may temporarily reduce habitat, but the report concluded habitat suitable to these species is readily available elsewhere locally. Thus, the project impacts to these species are not considered significant.

#### Potentially significant impacts to habitat:

The biotic report identified potentially significant impacts resulting from the project such as the loss of Coast Live Oak Riparian Forest, loss of Coast Live Oak Habitat, impacts to aquatic habitat by in stream stabilization. The recommended measures are identified in the biotic report excerpts, attached, and are included in the project restoration plans. The project includes a recommended implementation plan, planting plan, and a maintenance and monitoring plan. This includes impacts to Coast Live Oak Riparian Forest, loss of Coast Live oak, impacts to aquatic habitat, and in-stream stabilization.

#### Potentially significant impacts to terrestrial species:

Potential significant impacts to roosting bats and nesting birds have been identified as a result of restoration plan work. In order to reduce potential impacts to roosting bats, raptors, and migratory songbirds, the following mitigation measures shall be included in the project conditions of approval.

- A. Tree removal activities shall be limited to the months between November 1 and March 1, if feasible.
  - 1. If trees must be removed outside of the timeframe above, a qualified biologist shall conduct surveys for special status bats 3-4 weeks prior to site disturbance. If active roosts are present in trees to be retained, roosting bats shall be excluded from trees to be removed prior to any disturbance. In trees to be retained, no disturbance zones, set by the biologist based on the particular species present, shall be fenced off around the subject tree to ensure other construction activities do not harm sensitive species.
  - 2. The maternity roosting season for bats is March1 July 3. Tree removal

Less than
Significant
with
Mitigation
Incorporated

Less than Significant Impact

No Impact

should be scheduled outside of the maternal roosting period if special status bats are present. Before any trees are removed during the maternal roosting season, a qualified biologist shall perform surveys. If maternal roosts are present, disturbance shall be avoided until roosts are unoccupied. The biologist shall be responsible for ensuring bat roosts are vacated.

- B. In order to avoid impacts to raptors and migratory songbirds, tree removal activities shall be limited to the months between September 1 and February 1, if feasible.
  - If trees must be removed outside of the timeframe above, a qualified biologist shall conduct surveys for raptor or migratory songbird nests 3-4 weeks prior to site disturbance.
    - a. If active raptor or migratory bird nests are found in trees to be retained, the biologist shall be required to be on site during any initial vegetation or ground disturbance activities (e.g. vegetation clearing, grading, excavation, tree pruning/removal) that could potentially impact listed species. The biologist shall be responsible for setting and maintaining the disturbance buffers from active nests during construction activities, and buffers and exclusionary measures shall be implemented only after consultation with CDFG.
- C. If no active nests are present on the subject parcel, tree removal can proceed provided the mitigations in 1. above have been implemented.
  2. Have a substantial adverse effect on any riparian habitat or sensitive natural community identified in local or regional plans, policies, regulations (e.g., wetland, native grassland, special forests, intertidal zone, etc.) or by the California Department of Fish and Game or U.S. Fish and Wildlife Service?

**Discussion:** A Biotic Report was prepared for this project by H.T. Harvey and Associates Ecological Consultants and dated December 4, 2009 (Attachment 4 and 5). The project restoration work includes creek stabilization work within the creek channel and restoration of habitat within the riparian buffer. The project also includes pedestrian bridge construction across the channel and within the riparian buffer.

Four principal areas of restoration work are proposed by this project: Oak riparian restoration to promote high quality habitat; Oak woodland enhancement, including relocating, replanting, and replacement of trees removed elsewhere on the site; Riparian Exception buffer plantings within the buffer, which includes removal of

Less than
Significant
with
Mitigation
Incorporated

Less than Significant Impact

No Impact

invasive species; and, park restoration plantings throughout the site with native species to improve habitat value.

The project requires a Riparian Exception from the Planning Department, a United States Army Corps of Engineers (USACE) permit for work within the creek and up to the high water mark, California Fish and Game Streambed Alteration Agreement for work along the streambed and stream bank, and a Regional Water Quality Control Board water quality certification pursuant to USACE jurisdiction requirements.

Recommended biotic protection measures are included in the project plans with exception of a few identified impacts.

Coast Live Oak Riparian Habitat: The plans include a restoration area of approximately .04 acre and is comprised of tree removal and replacement within the riparian corridor at a ratio of 3:1, tree pruning/shrub removal associated with in-stream restoration at a ratio of 1:1, in-stream repair work aquatic restoration at a ratio of 1:1, and, non-native eucalyptus removal at a ratio of 2:1. The replacement ratios are per the Habitat Restoration Summary and Table 5 of the Biotic Report and are included in the project proposal.

<u>Oak Woodland</u>: The project also includes removal of 15 oak trees outside the sensitive habitat areas that are recommended to be replaced with 43 trees. The plans include restoration plans identifying the replacement species and location as well as relocation of salvaged trees.

<u>County of Santa Cruz Riparian Buffer Restoration</u>: Construction disturbance within the buffer area is recommended to require seeding of native species on all temporarily disturbed areas within the buffer following construction. Erosion control plans are included in the project plans. A detailed erosion and drainage control plan is a required component of the County Grading permit

Non biotic report plantings include:

Park Restoration Plantings: Additional habitat enhancement is provided via landscape planting of native species throughout the site, in approximately .6 acres of the site.

<u>Tree Protection Fencing Measures</u>: The biotic report recommends tree protection measures as recommended by the arborist report (Exhibit 9). The tree protection fencing is not shown on the plans. In order to ensure no significant impacts to existing trees to be retained will occur, prior to issuance of building permits, the applicant shall submit to the Planning Department a tree protection plan for review and approval.

<u>Tree Transplant</u>: The report recommends trees suitable for replanting (less than 6 inches in diameter) are replanted. This includes approximately 8-12 native oak trees. Replanting is included in the project restoration plan and project plans, consistent with this recommendation.

Non-Native Species Removal: The report recommends removal of a non-native eucalyptus grove as well as non-native woody invasive trees within the project area. This is included in the restoration plan.

CEQA Environmental Review Initial Study Page 18

Potentially Significant Impact Less than
Significant
with
Mitigation
Incorporated

Less than Significant Impact

No Impact

<u>Drainage Pipe Construction:</u> Installation of a drainage pipe on the Tee Street side requires placement of an outfall into the riparian corridor and is included in the proposed creek stabilization work. Construction work requires trimming of trees and/or roots. This work shall be conducted under the supervision of the project biologist. Tree and/or root trimming shall be supervised by the project arborist to minimize or avoid impacts, as noted in the biotic report.

#### **Restoration Monitoring**

The project includes a recommended monitoring plan that includes project construction supervised by an ecologist, a biologist prepared as-built plan following construction completion, and final performance and success criteria pursuant to the recommendations of the report.

3.	Interfere substantially with the movement of any native resident or migratory fish or wildlife species, or with established native resident or migratory wildlife corridors, or impede the use of native or migratory wildlife		
	nursery sites?		

#### Discussion:

A Biotic Report was prepared for this project by H.T. Harvey and Associates Ecological Consultants and dated December 4, 2009 (Attachment 4 and 5). The report identifies potentially significant impacts from proposed in-stream channel stabilization work on .08 acres of the aquatic habitat and creek bank area, including temporary impacts to aquatic habitat and creek bank area. The following measures are included in the plans to reduce the impacts to less than significant levels.

Channel Repair and Stabilization Work: Three areas of the creek channel are proposed to be stabilized to reduce the likelihood of additional creek instability and habitat degradation, which will improve the long term quality of the habitat and reduce the likelihood of creek bank failure. The recommendations of the habitat restoration plan are incorporated into the plans as proposed.

Aquatic Habitat: To minimize impacts to water quality and protect habitat value, best management practices are recommended to be implemented during construction, project monitoring by a biologist during construction, dry season work only, and implementation of erosion control measures during construction.

Revegetation of Channel Slopes: Once the bridge has been constructed and inchannel stabilization is complete, all disturbed areas will be revegetated at a 1:1 ratio, trees removed will be replaced at a 2:1 or 3:1 ratio per the biotic report.

Roosting Bats, migratory songbirds and raptors: See C.1. above.

CEQA Environmental Review Initial Study Page 19		Potentially Significant Impact	Less than Significant Impact	No Impact	
4.	Produce nighttime lighting that would substantially illuminate wildlife habitats?		$\boxtimes$		

**Discussion:** The project plans provide lighting consistent with the County Code lighting requirements enumerated in County Code 13.11, as noted on the plans. These requirements minimize impacts to surrounding properties. The plans propose the following lighting adjacent to the riparian corridor, which is consistent with the general standards:

<u>Cunnison/Soquel Drive</u>: Lighting is proposed at the community building exits, located to the rear of the building adjacent to the riparian corridor. These lights are wall mounted, 34 watt, fluorescent lights, with battery backup. The proposed trellis structure adjacent to the building and riparian corridor proposes a series of 50 watt down light bulbs with integral transformer. Parking lot lights adjacent to the riparian corridor are 15 foot maximum height, pole mounted, metal halide lights, without house shield fixtures. Two wall mounted lights are proposed on either end of the proposed pedestrian bridge, similar to those described for the building, above.

<u>Tee Street</u>: A 15 foot pole, 210 watt light, without shield, is proposed along the restroom building, within 30 feet of the riparian buffer. A wall mounted, 34 watt, fluorescent light, with battery backup fixture is proposed behind the restroom building also.

The Biotic Study (Attachment 4 and 5) did not identify any significant impacts that would occur as a result of potential project lighting. Nonetheless, the riparian corridor could be adversely affected by a new or additional source of light that is not adequately deflected or minimized. Based on the light diagram included in the project plans, two proposed light sources are recommended to be revised to mitigate lighting impacts to the riparian corridor.

#### Proposed Mitigation Measures:

- A) The proposed 10 foot tall parking light pole adjacent to the riparian corridor is recommended to be revised to provide a shield that will prevent light from casting into the edge of the riparian buffer.
- B) The four proposed lights on the bridge are recommended to be shielded so that lighting will not cast into the creek channel and riparian corridor.

These mitigation measures would reduce the project impacts to less than significant. Prior to issuance of a building permit, the applicant shall submit a lighting plan reflecting the mitigations, above, to the Planning Department for review and approval.

CEQA E Page 20	Environmental Review Initial Study	Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impact		
5.	Have a substantial adverse effect on federally protected wetlands as defined by Section 404 of the Clean Water Act (including, but not limited to marsh, vernal pool, coastal, etc.) through direct removal, filling, hydrological interruption, or other means?						
Discu	ussion: No wetlands have been identified on the subject parcels.  Conflict with any local policies or						
6.	ordinances protecting biological						
<b>Discussion:</b> The proposed project includes riparian restoration plans that have been prepared to meet the recommendations of the biotic report to improve the habitat quality of the riparian corridor. This includes removal of non-natives and replacement with native vegetation. The work is exempt from the riparian protection ordinance and does not require a riparian exception.							
	roject proposes bridge construction across parian ordinance. A riparian exception can				t from		
No gra	ading is permitted between October 15 <sup>th</sup> a	nd April 15	o <sup>th</sup> .				
7.	Conflict with the provisions of an adopted Habitat Conservation Plan, Natural Community Conservation Plan, or other approved local, regional, or state habitat conservation plan?						
<b>Discussion:</b> The proposed project would not conflict with the provisions of any adopted Habitat Conservation Plan Natural Community Conservation Plan, or other approved local, regional, or state habitat conservation plan. Therefore, no impact would occur.							
	GRICULTURE AND FOREST RESOURCE ermining whether impacts to agricultural re		ıre significa	ınt environ	mental		

In determining whether impacts to agricultural resources are significant environmental effects, lead agencies may refer to the California Agricultural Land Evaluation and Site Assessment Model (1997) prepared by the California Department of Conservation as an optional model to use in assessing impacts on agriculture and farmland. In determining whether impacts to forest resources, including timberland, are significant environmental effects, lead agencies may refer to information compiled by the California Department of

CEQA Environmenta	l Review	Initial	Study
Page 21			•

Less than
Significant
with
Mitigation
Incorporated

Less than Significant Impact

No Impact

Forestry and Fire Protection regarding the state's inventory of forest land, including the Forest and Range Assessment Project and the Forest Legacy Assessment Project; and forest carbon measurement methodology provided in Forest Protocols adopted by the California Air Resources Board. Would the project:

	t carbon measurement methodology prov ornia Air Resources Board.  Would the pr		st Protocols	adopted l	by the
1.	Convert Prime Farmland, Unique Farmland, or Farmland of Statewide Importance (Farmland), as shown on the maps prepared pursuant to the Farmland Mapping and Monitoring Program of the California Resources Agency, to non-agricultural use?				
Farm maps Califo Local State	ussion: The project site does not contain land, Unique Farmland, or Farmland of Some prepared pursuant to the Farmland Mapornia Resources Agency. In addition, the Importance. Therefore, no Prime Farmlawide or Farmland of Local Importance who impact would occur from project implements.	Statewide Impoping and Mol project does and, Unique Fould be conve	ortance as nitoring Pro not contain farmland, F	shown on ogram of the Farmland farmland o	ne Lof of
2.	Conflict with existing zoning for agricultural use, or a Williamson Act contract?				$\boxtimes$
not counde	ussion: The project site is zoned Parks, onsidered to be an agricultural zone. Add r a Williamson Act Contract. Therefore, the for agricultural use, or a Williamson Act	litionally, the ne project doe	project site es not conf	's land is r lict with ex	not isting
3.	Conflict with existing zoning for, or cause rezoning of, forest land (as defined in Public Resources Code Section 12220(g)), timberland (as defined by Public Resources Code Section 4526), or timberland zoned Timberland Production (as defined by Government Code Section 51104(g))?				
Disc	ussion: The project is not adjacent to lar	nd designated	as Timber	Resource	<del>)</del> .

**Discussion:** The project is not adjacent to land designated as Timber Resource. Thus, the project will not affect the resource or access to harvest the resource in the future.

4. Result in the loss of forest land or conversion of forest land to non-forest use?

CEQA Environmental Review Initial Study Page 22

Potentially Significant Impact Less than
Significant
with
Mitigation
Incorporated

Less than Significant Impact

No Impact

	<b>cussion:</b> No forest land occurs on the project is anticipated.	ect site or i	n the imme	ediate vicini	ty. No
5.	Involve other changes in the existing environment which, due to their location or nature, could result in conversion of Farmland, to nonagricultural use or conversion of forest land to non-forest use?				
does Farm maps Calife Farm agric occu antic	ussion: The project site and surrounding a not contain any lands designated as Primal and of Statewide Importance or Farmland sprepared pursuant to the Farmland Mappornia Resources Agency. Therefore, no Proland of Statewide, or Farmland of Local Insultural use. In addition, the project site corrs within one mile of the proposed project sipated.  INERAL RESOURCES  Id the project:	e Farmland I of Local I Ding and M Ime Farmla Inportance I Intains no fo	d, Unique mportance onitoring Fand, Unique would be correst land,	Farmland, a as shown of the program of the converted to and no fore	on the he I, o a non-
1.	Result in the loss of availability of a known mineral resource that would be of value to the region and the residents of the state?			Ģ	
value	ussion: The site does not contain any know to the region and the residents of the state project implementation.				
2.	Result in the loss of availability of a locally-important mineral resource recovery site delineated on a local general plan, specific plan or other land use plan?				
	ussion: The project site is zoned Parks, R		-	•	

not considered to be an Extractive Use Zone (M-3) nor does it have a Land Use Designation with a Quarry Designation Overlay (Q) (County of Santa Cruz 1994). Therefore, no potentially significant loss of availability of a known mineral resource of locally important mineral resource recovery (extraction) site delineated on a local general plan, specific plan or other land use plan would occur as a result of this project.

CEQA E Page 23	Environmental Review Initial Study 3	Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impact		
	SUAL RESOURCES AND AESTHETICS I the project:						
1.	Have an adverse effect on a scenic vista?						
desigr	resion: The project will not directly impact nated in the County's General Plan (1994), resources.	•					
2.	Substantially damage scenic resources, within a designated scenic corridor or public view shed area including, but not limited to, trees, rock outcroppings, and historic buildings within a state scenic highway?						
public	ssion: The project site is not located along viewshed area, scenic corridor, within a dea state scenic highway. Therefore, no imp	esignated	scenic res				
3.	Substantially degrade the existing visual character or quality of the site and its surroundings, including substantial change in topography or ground surface relief features, and/or development on a ridgeline?						
proper with an landso propos propos along appea	rties. The property is a vacant, infill site rties. Topographically speaking, the proper nelevation range of 120 feet to 160 feet. Caped to fit into this setting. Approximately sed to develop the combined property to a sed grading gently realigns the natural con Cunnison Lane to address the project desuring slope. The final project will not significater of the site.	rties gene The project 6800 cub ccomplish tours of th ign require	erally slope of has been pic yards of handicap ne site fron ements and	to the sound designed for the design of thed	ithwest and ty The rive up a natural		
4.	Create a new source of substantial light or glare which would adversely affect day or nighttime views in the area?						
	<b>Discussion:</b> The project will create an incremental increase in night lighting. However, this increase will be small, and will be similar in character to the lighting						

Application Number: 09-0407

associated with the surrounding existing uses.

CEQA Page 2	Environmental Review Initial Study 24	Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impact
	ULTURAL RESOURCES d the project:				
1.	Cause a substantial adverse change in the significance of a historical resource as defined in CEQA Guidelines Section 15064.5?				
	ussion: The existing structure(s) on the pro arce on any federal, State or local inventory		ot designa	ted as a h	istoric
2.	Cause a substantial adverse change in the significance of an archaeological resource pursuant to CEQA Guidelines Section 15064.5?				
Pursu proce age, o reaso perso	ussion: No archeological resources have be uant to County Code Section 16.40.040, if a less of excavating or otherwise disturbing the or any artifact or other evidence of a Native enably appears to exceed 100 years of age ons shall immediately cease and desist from the notification procedures given in County	at any timo e ground, e America are disco n all furthe	e in the pre any humar n cultural si vered, the er site exca	paration for remains ite which responsibusion and	or or of any le
3.	Disturb any human remains, including those interred outside of formal cemeteries?				
time of this per cease Plann full are Califo signifi	during site preparation, excavation, or other roject, human remains are discovered, the e and desist from all further site excavation ing Director. If the coroner determines that cheological report shall be prepared and retrained indian group shall be contacted. District cance of the archeological resource is determined the resource on the site are established.	r ground of responsible and notify t the remain epresental urbance significant ermined a	disturbance ble persons the sheriff ains are not tives of the hall not res	associate shall imm f-coroner a t of recent local Nati ume until	ed with nediately and the origin, a ve
4.	Directly or indirectly destroy a unique paleontological resource or site or unique geologic feature?				
Discu	ussion: No paleontological resources are n	nanned in	the project	area	

CEQA L Page 25	Environmental Review Initial Study 5	Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impact
	AZARDS AND HAZARDOUS MATERIALS If the project:	S			
1.	Create a significant hazard to the public or the environment as a result of the routine transport, use or disposal of hazardous materials?				
	ession: The project does not involve the use transport, use, or disposal as a result of				require
2.	Create a significant hazard to the public or the environment through reasonably foreseeable upset and accident conditions involving the release of hazardous materials into the environment?				
Discu	ssion: The project does not involve the us	se of haza	ardous mat	erials.	
3.	Emit hazardous emissions or handle hazardous or acutely hazardous materials, substances, or waste within one-quarter mile of an existing or proposed school?				
Discu	ssion: The project does not involve the us	se of haza	ardous mat	erials.	
4.	Be located on a site which is included on a list of hazardous materials sites compiled pursuant to Government Code Section 65962.5 and, as a result, would it create a significant hazard to the public or the environment?				
	ssion: The project site is not included on Cruz County, compiled pursuant to the sp			hazardous	s sites in
5.	For a project located within an airport land use plan or, where such a plan has not been adopted, within two miles of a public airport or public use airport, would the project result in a safety hazard for people residing or working in the project area?				

CEG Page	A Environmental Review Initial Study e 26	Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impa
Dis	cussion: The project is not located within a	n airport a	pproach zo	ne.	
6.	For a project within the vicinity of a private airstrip, would the project result in a safety hazard for people residing or working in the project area?				
Dis	cussion: The project is not located within th	e vicinity	of a private	airstrip.	
7.	Impair implementation of or physically interfere with an adopted emergency response plan or emergency evacuation plan?				
Disc	cussion: The project will not interfere with a	n adopted	l emergend	y respons	e plan.
8.	Expose people to electro-magnetic fields associated with electrical transmission lines?				$\boxtimes$
Disc	cussion: The project does not involve electr	o-magnet	ic lines.		
9.	Expose people or structures to a significant risk of loss, injury or death involving wildland fires, including where wildlands are adjacent to urbanized areas or where residences are intermixed with wildlands?				
<b>Disc</b> requ ager	cussion: The project design incorporates all irements and will include fire protection devincy.	applicablices as re	e fire safety quired by th	/ code ne local fir	e
	RANSPORTATION/TRAFFIC				
1.	Conflict with an applicable plan, ordinance or policy establishing measures of effectiveness for the performance of the circulation system, taking into account all modes of transportation including mass transit and non-motorized travel and relevant components of the circulation system, including but not limited to intersections, streets, highways and				

Significant with Mitigation Incorporated

Less than

Less than Significant Impact

No Impact

freeways, pedestrian and bicycle paths, and mass transit?

#### Discussion:

A traffic study was prepared for the proposed project by Fehr & Peers Transportation Consultants (Attachment 8), dated September 30, 2009 and accepted by the Public Works Department Road Engineering. Based on the traffic report, the proposed project is expected to create a small incremental increase in traffic on nearby roads and intersections. However, given the small number of new trips created by the project (94 PM peak-hour trips when the community center is occupied and the outdoor area is in use, based on use primarily in the PM peak-hour of use, as detailed in the program statement attached as Appendix D - Community Center Program and Schedule Assumptions), this increase is a less than significant project level and cumulative-level impact at the three study intersections at the PM peak hour (Soquel Drive/Porter Street, Soquel Drive/Cunnison Lane, and Soquel Drive/Park Avenue). AM peak-hour trips were not evaluated because the main use of the facility occurs in the PM peak-hour and thus the increment of traffic for the AM is also less than significant. Further, the increase in PM traffic will not cause the Level of Service at any nearby signalized intersection at either the Soquel Drive/Porter Street or Soquel Drive/Park Avenue intersection to drop below Level of Service D. The proposed level of service under project conditions at the un-signalized Soquel Drive/Cunnison Lane intersection is expected to be LOS A overall, which will not reduce the level of service or result in significant impacts as a result of the project. Notwithstanding the overall LOS, the southbound left turn lane on the Cunnison Lane approach at this intersection is expected to be LOS E which initiated a review of traffic signal warrants. The traffic signal warrant analysis indicates that this intersection does not meet the minimum peak-hour volume signal warrants. In addition, the Public Works Department, in conjunction with the Redevelopment Agency, coordinated a community meeting process to consider a signal at this intersection. The Community supported the traffic analysis that a traffic signal was not necessary at this intersection. Furthermore, the project includes Transportation Improvement Area fees, which will offset any cumulative traffic impacts at this intersection.

The report noted that the proposed project is expected to attract pedestrian users from surrounding neighborhoods including Hardin Way, Monterey Avenue, and Orchard Street. The report concluded that the proposed park and community center will have a less than significant impact on the existing pedestrian, bicycle, and transit network; and the report did not recommend any required pedestrian improvements. However, the report suggested pedestrian crosswalk improvements at Cunnison lane to allow pedestrians to cross the street to the park. These improvements would also serve the metro bus stop along Soquel Drive. A pedestrian crosswalk will be included as a condition of

CEQA Page 2	Environmental Review Initial Study 8	Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impact
	approval, but is not required as a mitigat	ion measu	re.		
2.	Result in a change in air traffic patterns, including either an increase in traffic levels or a change in location that results in substantial safety risks?				
3.	Substantially increase hazards due to a design feature (e.g., sharp curves or dangerous intersections) or incompatible uses (e.g., farm equipment)?				
4.	Result in inadequate emergency access?				$\boxtimes$
	ussion: The project's road access meets oved by the local fire agency or California I				
	g construction, one lane will remain open ther emergency vehicles will not be blocke				
5.	Cause an increase in parking demand which cannot be accommodated by existing parking facilities?				$\boxtimes$
study, for the be acc	ussion: The project includes a parking pla contained in a traffic report (Attachment proposed facility and proposed uses, an commodated on site. This parking plan is iption pursuant to the Parking Ordinance,	12). It eva d conclude included i	luates the les that park n the prope	required p sing demai osed proje	arking nd will ct
6.	Conflict with adopted policies, plans, or programs regarding public transit, bicycle, or pedestrian facilities, or otherwise decrease the performance or safety of such facilities?				
neces arrivin existin projec	ession: The proposed project would composer to prevent potential hazards to motor to the site. The project proposes handing bus stop on Soquel Drive to the proposet provides bicycle parking on site for bicycle public safety of public transit, bicycle, contents to the proposer to the proposer to the provides bicycle parking on site for bicycle, contents to the proposer to the provides bicycle public transit, bicycle, contents to the proposer t	rists, bicyc cap acces ed park ar cle access	lists, and/o sible pathw nd commun as well. T	r pedestria ays from the contention of the content	ans the The will

Page		Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impact
the s	site.				
7.	Exceed, either individually (the project alone) or cumulatively (the project combined with other development), a level of service standard established by the County General Plan for designated intersections, roads or highways?				
Disc	ussion: See Item 1, above.				
	IOISE ld the project result in:				
1.	A substantial permanent increase in ambient noise levels in the project vicinity above levels existing without the project?	-			
dated study noise parki foot f fence proje prope park	ussion: A noise study was prepared for to October 31, 2008 and revised on July 27 determined that operational noise from the level in the vicinity of the project would reing areas and picnic areas. The noise studence along the west property line of the particle along the west property line north of Tee ct plans. A portion of fence may be three to erty owner's property line, as stipulated in a noise would not disturb them. It is not anter the fence height along a single property will state.	, 2009 (Att e project the sult from p dy recommerk south o Street. The to four feet an agreementicipated the	achment 7) hat may income a lay/sports and second for Tee Street in the laght and at the agreet and the agreet may be at the agreet may be accepted as the acc	). The no crease the area as we truction of and an elincluded along a single county the dupon re	ise ambient all as a six eight foot in the gle nat the eduction
2.	Exposure of persons to or generation of excessive groundborne vibration or groundborne noise levels?				$\boxtimes$
<i>Disc</i> i borne	ussion: The project site is not located ade vibration or ground-borne noise levels.	jacent to k	nown sourc	ces of grou	und-
3.	Exposure of persons to or generation of noise levels in excess of standards established in the General Plan or noise ordinance, or applicable standards of other agencies?				

**Discussion:** Per County policy, average hourly noise levels shall not exceed the General Plan threshold of 50 Leq during the day and 45 Leq during the nighttime.

CEQA Environmental	Review	Initial	Study
Page 30			-

Less than Significant with Mitigation Incorporated

Less than Significant Impact

No Impact

 $\boxtimes$ 

Impulsive noise levels shall not exceed 65 db during the day or 60 db at night. The noise study (Attachment 7) prepared for this project has shown that traffic noise along Soquel Drive and Cunnison Lane will result in less than .5 dBA Ldn increase in noise levels. This is considered less than a significant impact.

4.	A substantial temporary or periodic increase in ambient noise levels in the project vicinity above levels existing		
,	without the project?		

**Discussion:** Noise generated during construction will increase the ambient noise levels for adjoining areas. Construction will be temporary, however, and given the limited duration of this impact it is considered to be less than significant with standard construction noise controls. These include hours of operation, intake/ and exhaust mufflers on internal combustion engine noise sources, separation between noise sources and sensitive receptors, use of quiet stationary noise sources, construction plan identifying schedule for noise generating activities coordinated with noise sensitive facilities, and identification of a disturbance coordinator. In order to ensure that no significant impacts occur as a result of the project, Noise Study mitigation recommendations contained in the attached Noise Study (recommended mitigations only) prepared by Richard B. Rodkin, dated October 31, 2008 and Revised July 27, 2009 (Attachment 7) shall be incorporated into the conditions of approval:

- A. Construction shall be restricted between 8 a.m. to 6 p.m.
- B. No construction shall occur on weekends.
- C. All internal combustion engines with intake and exhaust mufflers shall be maintained in good condition.
- D. Project construction shall utilize "quiet" air compressors and other stationary noise sources where technology exists.
- E. The project shall designate a "noise coordinator" who is responsible for responding to any local complaints about construction noise. The disturbance coordinator shall determine the cause of the noise complaint (e.g., starting early, bad muffler, etc.) and will require that reasonable measures warranted to correct the problem be implemented. The applicant shall post a telephone number for the disturbance coordinator at the construction site and include it in the notice sent to neighbors regarding the construction schedule.
- 5. For a project located within an airport land use plan or, where such a plan has not been adopted, within two miles of a public airport or public use airport, would the project expose people residing or working in the project area to excessive noise levels?

to excessive noise levels?

CEQA Page 3	Environmental Review Initial Study 1	Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impact
<i>Discu</i> airstri	<b>ussion</b> : The project site is not located in the p.	ne vicinity	of a public	airport or	private
6.	For a project within the vicinity of a private airstrip, would the project expose people residing or working in the project area to excessive noise levels?				
<b>Discu</b> airstri	<b>ussion</b> : The project site is not located in the p.	e vicinity o	of a public a	airport or p	orivate
K. AI	R QUALITY				
estab Air Po	e available, the significance criteria lished by the Monterey Bay Unified ollution Control District (MBUAPCD) may be to make the following determinations. Wo		oject:		
1.	Violate any air quality standard or contribute substantially to an existing or projected air quality violation?				
ozone would	ession: The North Central Coast Air Basine and particulate matter (PM <sub>10</sub> ). Therefore, be emitted by the project are ozone precus] and nitrogen oxides [NO <sub>x</sub> ]), and dust.	the region	nal pollutar	nts of cond	ern that
indica these	the modest amount of new traffic that will tion that new emissions of VOCs or $NO_x$ w pollutants and therefore there will not be a ality violation.	ill exceed	<b>MBUAPCI</b>	O threshol	ds for
general as per	ct construction may result in a short-term, leation of dust. However, standard dust con riodic watering, will be implemented during han significant level.	trol best m	nanagemei	nt practice	s, such
2.	Conflict with or obstruct implementation of the applicable air quality plan?				
<b>Discu</b> region	ssion: The project will not conflict with or all air quality plan. See K-1 above.	obstruct in	mplementa	tion of the	<b>)</b>
3.	Result in a cumulatively considerable net increase of any criteria pollutant for which the project region is non-			$\boxtimes$	

CEQA Environmental Review Initial Study Page 32		Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impact
	attainment under an applicable federal or state ambient air quality standard (including releasing emissions which exceed quantitative thresholds for ozone precursors)?				
Disc	ussion: See K-1 above.				
4.	Expose sensitive receptors to substantial pollutant concentrations?				
5.	Create objectionable odors affecting a substantial number of people?			$\boxtimes$	
	REENHOUSE GAS EMISSIONS d the project:				
1.	Generate greenhouse gas emissions, either directly or indirectly, that may have a significant impact on the environment?				. 🗆

**Discussion:** The proposed park project, like all development, is responsible for an incremental increase in green house gas emissions by usage of fossil fuels during the project construction and during on-going operation of the project in the form of facility heating.

At this time, Santa Cruz County is in the process of developing a Climate Action Plan (CAP) intended to establish specific emission reduction goals and necessary actions to reduce greenhouse gas levels to pre-1990 levels as required under SB 375 legislation. Until the CAP is completed, there are no specific standards or criteria to apply to this project. However, the following factors, when considered as a whole, are expected to reduce nay impacts of increased green house gas emissions to a less than significant level:

- A. The project proposes to obtain LEED certification for the community center building, which will reduce ongoing heating for the building and thereby greenhouse gas emissions. (LEED is a third-party certification program and the nationally accepted benchmark for the design, construction and operation of high-performance green buildings.)
- B. The facility is proposed along a major transit corridor and bus route, which will encourage visitors to access the facility via the public transit system.
- C. The proposed park is located in a residential neighborhood and will reduce

CEQA Environmental	Review Initial Stud	Ιv
Page 33		•

Less than
Significant
with
Mitigation
Incorporated

Less than Significant Impact

No Impact

vehicle trips of nearby residents that would otherwise travel to visit a park.

- D. The location of this facility will reduce vehicle trips from this neighborhood traveling to community classes offered by the parks department at other facilities in the County that will now be available at this facility.
- E. The project construction will be required to comply with the Regional Air Quality Control Board emissions requirements for construction equipment involved in the project.
- 2. Conflict with an applicable plan, policy or regulation adopted for the purpose of reducing the emissions of greenhouse gases?

Discussion: See Item 1, above.

#### M. PUBLIC SERVICES

Would the project:

- 1. Result in substantial adverse physical impacts associated with the provision of new or physically altered governmental facilities, need for new or physically altered governmental facilities, the construction of which could cause significant environmental impacts, in order to maintain acceptable service ratios, response times, or other performance objectives for any of the public services:

  - d. Parks or other recreational activities?

CEQA Environmental Review Initial Study Page 34

Potentially Significant Impact Less than
Significant
with
Mitigation
Incorporated

Less than Significant Impact

No Impact

**Discussion (a through e):** The project will result in an incremental contribution to the need for services; however, the increase would be minimal. Moreover, the project meets all of the standards and requirements identified by the local fire agency and transportation fees to be paid by the applicant will be used to offset the incremental increase in demand for public roads.

	ECREATION d the project:				
<b>1.</b>	Would the project increase the use of existing neighborhood and regional parks or other recreational facilities such that substantial physical deterioration of the facility would occur or be accelerated?				
<b>Disc</b> use o	ussion: The project is a proposed park an fother existing parks.	d will not re	esult in an	increase ir	n the
2.	Does the project include recreational facilities or require the construction or expansion of recreational facilities which might have an adverse physical effect on the environment?				
<i>Discu</i> here.	ussion: The project is a recreational facility The proposed project should not result in	y project u a significa	nder envird Int impact.	onmental r	eview
	TILITIES AND SERVICE SYSTEMS If the project:				
1.	Require or result in the construction of new storm water drainage facilities or expansion of existing facilities, the construction of which could cause significant environmental effects?				
Discu	recion:				

#### Discussion:

On-Site Drainage:

Drainage Calculations included in the On-Site Storm Drainage Final Report (Attachment 14) prepared by Mesiti-Miller Engineering, Inc., dated August 4<sup>th</sup>, 2009 noted in Table 4 of the report identify proposed impervious areas will increase from existing conditions by approximately 60,501 square feet. The drainage design recommended for the project includes two different approaches to slow down, infiltrate, and filter storm water. Some of the drainage from the parking areas is proposed to be diverted to vegetated areas, bioswales, rain gardens, and lawn areas. Two different

CEQA Environmental Review Initial Study Page 35

Potentially Significant Impact Significant with Mitigation Incorporated

Less than

Less than Significant Impact

No Impact

drainage approaches were provided for the site. The Cunnison Lane project requires a traditional drainage approach involving sub-surface detention/retention pipe via a series of bioswales and separator meant to meet the LEED certification design criteria. This detention system is designed to treat and meter flows into the public drainage system along Soquel Drive. Secondly, the Tee Street development area involves a detention/retention system that allows treatment through natural grassy areas and ultimately percolation into the groundwater system.

#### Off-Site Drainage:

The proposed project will add additional impervious surface within the drainage basin, which will increase the amount of runoff from the project as noted above. Drainage calculations included in the Off-Site Storm Drainage Final Report (Attachment 14) prepared by Mesiti-Miller Engineering, Inc., dated July 11, 2009 have been reviewed for potential off-site drainage impacts and are expected to be accepted by the Department of Public Works (DPW) Drainage Section staff. The calculations show that as a result of the proposed drainage runoff, off-site project upgrades are required to be completed to a number of downstream drainage facilities impacted by the proposed project. In particular, some of the downstream drainage improvements are not adequately sized to accommodate existing or proposed runoff. As a result, the report recommends drainage upgrades to Soquel Drive East and Soquel Junction (essentially Soquel Drive between Cunnison Lane and east of Hardin Way), and includes pipe diameter enlargement, replacement of three existing inlets, replacement of one existing junction structure, and adjustment/replacement of another junction structure, and replacement of a manhole cover for adjustments of new pipe elevations. Most of the off-site drainage improvements will be completed within the existing rightof-way.

These on-site and off-site drainage improvements are expected to result in the potential for temporary erosion during construction. The plans include an erosion control plan with measures that will limit site erosion and will not result in significant impacts.

2.	Require or result in the construction of		$\boxtimes$	
	new water or wastewater treatment	 		
	facilities or expansion of existing			
	facilities, the construction of which			
	could cause significant environmental			
	effects?			

**Discussion:** The project will connect to an existing municipal water supply. Soquel Creek Water District has granted a conditional will serve letter, dated September 28, 2010 that is valid for two years, determining that adequate supplies are available to serve the project (Attachment 10) provided the project complies with the Water Demand Offset Program and additional conservation requirements of the water district prior to the actual connection.

CEQA Page	Environmental Review Initial Study 36	Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impact
letter	cipal sewer service is available to serve the from the County Sanitation District Memor chment 11).	e project, a andum, d	as reflected ated Augus	in the att t 16, 2010	ached )
3.	Exceed wastewater treatment requirements of the applicable Regional Water Quality Control Board?				$\boxtimes$
<i>Disc</i>	<b>ussion</b> : The project's wastewater flows will lards.	ll not viola	ite any was	tewater tr	eatment
4.	Have sufficient water supplies available to serve the project from existing entitlements and resources, or are new or expanded entitlements needed?				
<b>Disc</b> i Wate Distri	<b>ussion</b> : The project is located within the ear District. The project has received a will sect.	xisting boo	undaries of from the So	the Soqu oquel Cre	el Creek ek Water
5.	Result in determination by the wastewater treatment provider which serves or may serve the project that it has adequate capacity to serve the project's projected demand in addition to the provider's existing commitments?				
Disc	ussion: See item O.1, above.				
6.	Be served by a landfill with sufficient permitted capacity to accommodate the project's solid waste disposal needs?				
yards accor gradir	ussion: The project is projected to require of soil to the county landfill. This landfill hamodate this disposal need. The projecting contractor to submit off-haul receipts to mitted landfill location.	nas sufficion shall be c	ent permitte onditioned	ed capacit to require	y to the
7.	Comply with federal, state, and local statutes and regulations related to				

CEQA Page	Environmental Review Initial Study 37	Potentially Significant Impact	Less than Significant with Mitigation Incorporated	Less than Significant Impact	No Impaci
	solid waste?				
	AND USE AND PLANNING Id the project:				
1.	Conflict with any applicable land use plan, policy, or regulation of an agency with jurisdiction over the project (including, but not limited to the general plan, specific plan, local coastal program, or zoning ordinance) adopted for the purpose of avoiding or mitigating an environmental effect?				
<b>Disc</b> adop	ussion: The proposed project does not conted for the purpose of avoiding or mitigating	nflict with a g an envir	any regulat onmental e	ions or po ffect.	licies
2.	Conflict with any applicable habitat conservation plan or natural community conservation plan?				
biotic	ussion: The project provides a habitat rest report and will be conditioned to comply w I in the report.	oration pla	an that has commended	been sub d measure	ject to a s, as
3.	Physically divide an established community?				$\boxtimes$
<i>Disc</i> iestab	ussion: The project will not include any election of the community.	ement tha	t would phy	sically div	ide an
	OPULATION AND HOUSING d the project:				
1.	Induce substantial population growth in an area, either directly (for example, by proposing new homes and businesses) or indirectly (for example, through extension of roads or other infrastructure)?				
Discu	ussion: The proposed project would not in	iduce sub	stantial pop	oulation gr	owth in

**Discussion:** The proposed project would not induce substantial population growth in an area because the project does not propose any physical or regulatory change that would remove a restriction to or encourage population growth in an area including, but not limited to the following: new or extended infrastructure or public facilities; new commercial or industrial facilities; large-scale residential development; accelerated conversion of homes to commercial or multi-family use; or regulatory changes

CEQA Environmental Review Initial Study Page 38

Potentially Significant Impact Significant with Mitigation Incorporated

Less than

Less than Significant Impact

No Impact

including General Plan amendments, specific plan amendments, zone reclassifications, sewer or water annexations; or LAFCO annexation actions.

The proposed project is designed at the density and intensity of development allowed by the General Plan and zoning designations for the parcel. Additionally, the project does not involve extensions of utilities (e.g., water, sewer, or new road systems) into areas previously not served. Consequently, it is not expected to have a significant growth-inducing effect.

2.	Displace substantial numbers of existing housing, necessitating the construction of replacement housing elsewhere?				
	cussion: The proposed project would not do	isplace ar	y existing	housing sir	nce the
3.	Displace substantial numbers of people, necessitating the construction of replacement housing elsewhere?				$\boxtimes$

**Discussion:** The proposed project would not displace a substantial number of people since the site is currently vacant.

## IV. TECHNICAL REVIEW CHECKLIST

	REQUIRED	DATE COMPLETED	N/A
Agricultural Policy Advisory Commission (APAC) Review	Yes No		$\boxtimes$
Archaeological Review	Yes No 🛛		
Biotic Report/Assessment	Yes 🛛 No 🗌	12/4/2009	
Geologic Hazards Assessment (GHA)	Yes 🗌 No 🔀		
Geologic Report	Yes 🗌 No 🔀		
Geotechnical (Soils) Report	Yes 🛛 No 🗌	11/23/2009	
Riparian Pre-Site	Yes 🛛 No 🗌	1/23/2009	
Septic Lot Check	Yes No		$\boxtimes$
Other:	Yes 🛛 No 🗌		
Off-Site Storm Drainage Final Report		7/11/2009	
Off-Site Storm Drainage Final Report		8/4/2009	
Stream Hydrology and Hydraulics Final Report		7/29/2009	
Sanitary Sewer Final Report		8/4/2009	
Domestic and Fire Protection Water Supply Final Report		8/4/2009	
Draft Transportation Impact Analysis	•	9/30/2009	
Arborist Report		12/4/2009	
Biotic Mitigations Report		12/4/2009	


## V. REFERENCES USED IN THE COMPLETION OF THIS ENVIRONMENTAL REVIEW INITIAL STUDY

County of Santa Cruz 1994.1994 General Plan and Local Coastal Program for the County of Santa Cruz, California. Adopted by the Board of Supervisors on May 24, 1994, and certified by the California Coastal Commission on December 15, 1994.

### VI. ATTACHMENTS


- Assessor's Map, Vicinity Map, Map of Zoning Districts, Map of General Plan Designations, Assessors Parcel Map
- 2. Project Cover Sheet prepared by MIG, Inc., dated 10/31/2009; Landscape Architectural Plan sheets L-1.0, L-1.1, L-1.3, L-2.0, L-2.1, L-2.2, L-2.3, L-3.0, L-3.1, L-3.2, L-4.0, L-4.1, L-7.0 prepared by MIG Architects, Inc. (including sheet L-1.2 by Mesiti-Miller Engineering, sheet L-5.0 by H.T.Harvey and Associates, and sheet L-6.1 by Balance Hydrologies, Inc.), dated 10/31/2009; Architectural Plan sheets A-1.0, A-2.0, A-3.0 prepared by Thatcher and Thompson Architects, dated 10/31/2009; Civil Engineering Plan sheets C-1.0, C-1.1,C-2.0,C-3.0 prepared by Mesiti-Miller Engineering, Inc., dated 10/31/2009; Survey Plan sheets 2 of 2, dated 4/30/2008, and Survey Plan sheets TS-1-TS3, dated 5/20/2008, prepared Ifland Survey; Structural Plan sheet S-1.0 prepared by Mesiti-Miller Engineering, Inc., dated 10/31/2009; Electrical Plan sheets E1.0, E2.0, E2.1, E3.0 prepared by Prime Design Group, dated 10/31/2009
- 3. Geotechnical Investigation (recommendations excerpt, full report on file with the Planning Department) prepared by Haro, Kasunich and Associates, Inc., dated November 23, 2009
- 4. Biotic Study (conclusions excerpt, full report on file with the Planning Department) prepared by H.T.Harvey and Associates, dated December 4, 2009
- 5. Biotic Mitigation and Monitoring Plan (mitigations excerpt, full report on file with the Planning Department) prepared by H.T.Harvey and Associates, dated December 4, 2009
- 6. Arborist Report (recommendations excerpt only, full report on file with the Planning Department) prepared by H.T. Harvey and Associates, dated December 4, 2009
- 7. Noise Study (mitigations excerpt, full report on file with the Planning Department) prepared by Richard B. Rodkin, PE, dated October 31, 2008 and revised July 27, 2009
- 8. Traffic Study (conclusions and recommendations excerpt, parking demand, full report on file with the Planning Department) prepared by Fehr and Peers Transportation Consultants, dated September 30, 2009
- 9. Discretionary Application Comments
- 10 Letter from Soquel Creek Water District, dated October 23, 2008 (expired 2010)
- 11. Memo from Department of Public Works, Sanitation, dated August 16, 2010 (Expired)
- 12. Parks Program Statement, undated


- 13. Stream Hydrology and Hydraulics Final Report prepared by Mesiti-Miller Engineering, Inc., dated July 29, 2009 (Recommendations excerpt, full report on file with the Planning Department)
- 14. On-Site Storm Drainage Final Report (Recommendations excerpt, full report on file with the Planning Department) prepared by Mesiti-Miller Engineering, Inc., dated August 4<sup>th</sup>, 2009, and Off-Site Storm Drainage Final Report (Recommendations excerpt, full report on file with the Planning Department) prepared by Mesiti-Miller Engineering, Inc., dated July 11, 2009






# Location Map









ATTACHMENT





# Zoning Map












## General Plan Designation Map







#### M I G FARM NEIGHBORHOOD PARK & COMMUNITY CENTER squel Drive & Cunnison Lor Santa Cruz County, CA. 95073 045000 87 0417 34 16/31/2009 0417 64 1444 10/31/2009 00/48, 971, 2004 44 Development Permit Application PROJECT TRAME ACTION COLUMN COVER NT. How & American 7 MOTOR NAME OF THE PERSON OF CONSULTANT HET THE HARO / KASNICH I ASSOCIATES INC. II.6 E. LAKE AVENE WATSONVILE, CA 19016 11. BOINTO 3100 TER AND FERS 160 M SANTA CLARA ST. SUITE 613 SAN JOSE, CA TERS TEL. 4060 378-1100 FAX. 406/ 378-1111 David L Pokers Lassociates Inc. 1871 the Alameda Butt 200 May Lose Car Wilds Tel. 408/248-3500 x 134 Pax. 408/248-3641 PROJECT OUNER/APPLICANT HI. HARVET 1 ASSOCIATES 469 INIVERSITY AVENE, BLDS. D LOS 64709, CA 45032 TEL: 400/450-9234 PAX: 400/450-9230 STREAM HYDROLOGY AND HYDRALICS FINAL REPOR MEDEVELOTTENT AGENCY OF BANTA CRUZ COLATY FOR COLEMA PRINCES; ROOF BY SANT CRUZ CA MEDEVE PROJECT HANAGER, BARETLE BALLEY CONTRACT BUILDING AND RESTROOM BLEVATIONS HESTIC AND PIRE PROTECTION MATER SUPP CHANNITY BUILDING AND RESTROOM PLANS MASE ) ENVIRONMENTAL SITE ASSESSMENT ESTING PROGRAM LECTRIC AND GAS UTILITIES FINAL REPORT COMMENTY BUILDING AND ARTIST SKETCH SECTRICAL LISTS, SCHEDULES + DETAILS AFF-SITE STORM DRAINAGE FINAL REPORT RIGATION WATER SUPPLY FINAL REPORT ON-SITE STORM DRAINAGE PINAL REPORT FED GOALS AND PROGRAM REPORT IOTIC AND BOTANIC FINAL REPORT DIVIRONAMENTAL NOISE ASSESSMENT ANITARY SEVER PINAL REPORT THAL TRANSPORTATION REPORT RECRUST PINAL REPORT HANTING SITE PLAN KANTING SITE PLAN TSUAL ANALYSIS OTO-ETRICS NAME OF HTDRALLIC ENSINEER CONTACT: SHANN CHARTRAND. ENVIRONMENTAL CONSULTANT CONTACT: JLIE MER ECOLOGICAL CONSULTAR CONTACT: JOE HOWARD, LANDSCAPE ARCHITECT Farm Neighborhood Park SANTA CRUZ COUNTY BOARD OF SUPERVISORS A-90 6-10 6-20 6-31 LIST ENGINEERING 4644 BLIE LARKSFAR LANE 1209 MONTEREY CA 19440 TEL: 651/313-4940 THACHER ETHORISON ARCHITECTS 200 MASHINGTON 97. SUTE 201 201 SAVAST-SAMB TEL, 201/431-3450 FAX, 201/436-160\* MENITHALLER ENGINETRING. INC. 224 MALINT AVE., SWITE B 224 MALINT AVE., SWITE B 11. 081/426-5106 7 AX. 081/426-5007 TRIGATION PLAN - ESTIMATED WATER USE CAL IIÎ.LAND. ENGINEERS LINE OAK BUSHEES PARK, 9300 SOOREL ANE, SUTE IO SANTA CRUZ CA 1936 TEL: 851/426-5915 FAX: 891/426-1169 RUBATION FLAN - CUNISON LIN/BOCKEL DR and Community Center RADING FLAN - CLANISON LN/SOGUEL DR "LANTING PLAN - CUNNIBON LN/SOGUEL DR ARK SITE PLAN - CLANISON LN/SOQUEL MADINS - PROFILES AND SECTIONS RIGATION PLAN - TEE STREET RADING VOLLINE STUDY PLAN ARK SITE PLAN - TEE STREET LANTING PLAN - TEE STREET IABITAT RESTORATION PLAN LADING PLAN . TEE STREET -SITE DRAINAGE PLAN M-BITE DRAINAGE FLAN ROSION CONTROL PLAN OPOSRAPHIC SURVEY OPOGRAPHIC SURVEY SITE ACCESS PLAN TILITY PLAN NEIL COONERTY (CHAIR) - DISTRICT S TONY CANIDOS - DISTRICT 4 DRAWING INDEX CIVILATRICTURAL DIGNEER CONTACT: JAMES MINAN, PE CIVIL BYGNEER DALE HENDROBEE, PE STRICTURAL BYGNEER PROJECT TEAM ARCHITECT CONTACT: MATTHEW THOMPSON ARCHITECT JOHN LEGITOLD - DISTRICT ! MARK IL STONE - DISTRICT S CANDROAFE ARCHITECT CONTACT: BUBAN MCKAY, PROJECT MANAGER LANDBCAPE ARCHITECT CONTACT, RON BLIE, PE WECHANICAL ENGINEER URVETOR CONTACT: GRES JONES Select No. L-3.0 7-30 3 3 120.0 PROJECT DESCRIPTION Cunnison Ln./Soquel Dr. PUBLIC RECREATION HOURS OF OPERATION. SANISE - SANSET VICINITY MAP PROGRAM SE ACRES 1800 SF TREE DEMOLITION AND PROTECTION SEE ARBOR REPORT 091/454-2160 091/474-6642 091/494-2160 AREA 1 IT REFERENCE TABLE Tee St. 2 PARKING SPACES (P'XIB' STALLS UZ COUNTY SANITATION DISTRICT NG SPACES (4'XIB' STALLS) LOOD CONTROLMATER ARY TABLE REEK WATER DISTRICT STRUCTURES AREA MAP KEY MAP

46/163


IAS I ELECTRIC COMPANY


0


9 80


TRIVE DESIGN
BOO SPEEN HILLS ROAD SUITE 100
SCOTTS VALLEY, CA 45008
TEL. 801/820-5600


ELECTRICAL ENGINEER CONTACT: DAVE AUBLE,














































SCHEMATIC DESIGN - GRADING VOLUME STUDY


ATTACHMENT L2

















NEIGHBORHOOD PARK & COMMUNITY CENTER ESTIMATED WATER USE
CALCULATIONS
Development
Permit Application MODE MOSANO BOLTBANI, INC.  $\mathfrak{S}$ Soquel Drive & Cunnison Lan Sonta Cruz Courty, CA, 95073 245 DAVIN DATE 3004 DAG 1071/2009 DAVIE TO 1071/2009 DAVIE TO 1071/2009 DAVIN DATE 3004 DAVIN COLOR TONA
COLOR
COLOR TONA
COLOR TONA
COLOR
COLOR IRRIGATION PLAN \_ X DATE REVISIONS SHEET TITLE e N 100 20.00 18,30 AND METERS CALLOIS RESUME TOTAL GALLDRY HERRIPED PER VEAR BYTHATED BELLING UNITETEAN PARTIES AND SOUNDED IN THE COMMON THE THE COMMON THE THE COMMON THE THE COMMON THE COMMO DW WATER AND WATHE DREMANEHTAL HEGILM WATER ORNAMENTAL TIMP ARE AS COMMUNITY GARDEN MODED RESTINATION ANEAS highen wit to keered out a fring you pront Proposal you? I will repairment in state in the less from proposed you I got to war some to be supplemented by relevant to washing system. HOPOSED LANDSCAPE, GALLONS MENLINED FEB YEAR MEDIUM WATER ORNAMEDITAL SOQUEL DRIVE PARCEL CON WATER AND WATVE DIDIAMENTAL SOMO | Control | Cont Mamual Esterior Water Misconson Worksheet 1) Project Harmon Commune, Control Scool Date Front Scool Date Fro ANTON MELONING .... # 5 #F78 Calculate the Landergoe Wear Allogance for the project by multiplying the total equals footego sharm in Box A by the Amaid To in Box B and by ,00045 (commission fat by from inches of water to 100-cubit family per year). 10,000 x 46,17 x 0,8 x ,62 229,003 + 748 0.2 0.2 1. Total Virgand Landscaped Area (square hard) (Bass A) 123.2007

1. Armali Elle for Landscaped Area (botters par year) (Bass B) 66.17

2. Elle Adjustment France (solders) per options had consume a linch Sopiel) M. A.

4. Conversion Factor (to galloc) per options had consume a linch Sopiel) M. A. 600 195 TOTAL GALLONS STOUND PER YAAR ESTIMATED BILLING UNITAYERS TOTAL GALLONS ADDIVINED PER YEAR ENTIRATED GLUND LINETAVEAR Can loss sections L. Madmum Landmage Water Allowance (gallons per year) L'itotal impainet Lerchesspool deux (enquere fest)
 Anneuel Eile be Lerchesspool deux (ferches par your)
 E lo Adjustement Fuctor (urplessa)
 Communium Factor (urplessa) 5. Markmun I andecape When Alberance (gallons per 1 6. Olden by 748 to convert Into billing smits. 7. Total billing units per wee Divide by 748 to commert into billing units.
 Total billing units per year. The set of the second forms being married, was described in the second of the second o mpaten wil to impace due a from your ponts. Prepared you 2 and 3 main replaimment the departed to be base from program of year Example STALLSHIB LANGACAN, GALLONS NEGUED TRITTAN DW WATER AND WITH OPPLANEUTA, TURF ARBAS-EFTRIGHED RESTDANTON AREAS Bassal Edwine When Alexanes Worksheet
19 Project And and Sept. Sept. Sept. 1 Project And and an SAC Ten Street. Sala Dr.Cont.Cathon.

1 Annear - Perei Humber - 25/31/10159.

Lentiness State Alexander Service.

109: The Test of the Service Service.

109: The Test of the Service Service.

109: The Test of the Service of the Service Service.

109: The Service Service Service Service.

109: The Service Service Service Service Service.

109: The Service Service Service Service Service.

109: The Service Service Service Service Service Service.

109: The Service Ser Calculate the Landscape Water Alberrance for the project by multiplying the total square bookse shown in Soc. A by the Annual 150 in last 8 and by JODG!! loowwriten factor from inches of water to 100-cubic free per year! 479,396 + 748 641 Erhar his annual Reference Dispolitamphistlen Rata (ETD) for the landscaped a ETO Mister Emilion Adjustment Fester: An 80 parcant adjostment to the ETO to applied for vester sarrhess. Sustment Factor 1 1. Your United and company Area (recent two) (Sen A) 70,537

2. Arrun Ells for the Landscapend Area (testing pay year) (Sen B) (48.77


1. Ells delications of Senter (continue) in 0.8 1. Conversion Parties the gallane part separations - separate 1 from depth) 16. 52 10,000 x 46,17 x 0,8 x ,63 x ,63 + 748 306 ance (galters per year) Local Inspect Landscaped Area (equate lead)
 Amoust File for Landscaped Area (equate payme)
 Els Adjustment Factor (confieme)
 Convertion Factor (la guidena per equate filed) 5 Materium I soukaupa White Albowaro (gsh. E. Divido Na 748 in cesteral rato billing late. 7 Tool billing unto per year. L. Mazimum Lendecape White Alternates (g. 4. Olvide by 748 to somert into billing unio. 7. Yotal billing units per year. . .


68/:66/163


L-3


9008 AS NOTED

ş












REPAIR SECTIONS Soquel Drive & Cunnison Lane Senta Cruz County, CA, 95073 INSTREAM SHEET TITLE


Development
Permit Application
DATE REVISIONS

L-6.2

DATE
DATE
TOGGROUP
DRAWN GY
NT
LOG NG
20/187
SCALE
T = Z-G\*

STAMP






4


Note: Length of logs and anchoring to be determined


74/165


 $\mathbf{\omega}$ 





















VIEW FROM CUNNISON LANE









Project No. SC9704 23 November 2009

DAVID J. POWERS AND ASSOCIATES, INC. 1871 The Alameda, Suite 200 San Jose, California 95126

Attention:

Julie Mier

Subject:

Geotechnical Plan Review

Reference: Preliminary Drainage and Erosion Control Plans

Farm Neighborhood Park and Community Center

Soquel Drive and Cunnison Lane Santa Cruz County, California

Dear Ms. Mier:

As requested, we have reviewed the geotechnical aspects of Preliminary Drainage and Erosion Control Plans prepared by Mesiti-Miller Engineering Inc. for the referenced project. Our Geotechnical Investigation for the project is dated 23 December 2008. The reviewed plan sheets include:

- Sheet C-1.0, titled "On-Site Drainage Plan", dated 31 October 2009 1.
- Sheet C-1.1, titled "Off-Site Drainage Plan", dated 31 October 2009 2
- Sheet C-3.0, titled "Erosion Control Plan", dated 31 October 2009 3.

The plans indicate surface runoff and roof runoff from the garden areas, parking lots, driveways, play areas, grass pavers and sport courts will be directed via bioswales and stormdrain pipes to drain inlets and catch basins connected to subsurface detention systems with water quality treatment facilities. Roof runoff from the Community Building will be directed to a rainwater harvesting system with an overflow to the detention system

At the Tee Street side of the project, treated runoff water will be released to the stream channel via an outlet tee and energy dissipater per an instream repair plan designed by others. On the Soquel Drive side of the project, detained treated water from the project will be released to new storm drain inlets and pipes on Soquel Drive which connect to the existing storm drain system.

#### RECOMMENDATIONS

The following geotechnical criteria and recommendations should be followed during project design and preparation of project plans and specifications:

#### Site Grading

- 1. The geotechnical engineer should be notified at least four (4) working days prior to any site clearing or grading so that the work in the field can be coordinated with the grading contractor, and arrangements for testing and observation can be made. The recommendations of this report are based on the assumption that the geotechnical engineer will perform the required testing and observation during grading and construction. It is the owner's responsibility to make the necessary arrangements for these required services.
- Where referenced in this report, Percent Relative Compaction and Optimum Moisture Content shall be based on ASTM Test Designation D1557-07.
- 3. Areas to be graded should be cleared of all obstructions including loose fill, building foundations, old pavement, concrete flatwork, bricks, old septic tanks, trees not designated to remain, or other unsuitable material. All unsuitable material should be removed offsite. Existing depressions or voids created during site clearing should be backfilled with engineered fill.

Project No. SC9704 23 December 2008

- 4. Cleared areas should then be stripped of organic-laden topsoil. Stripping depth should be from 2 to 4 inches. Actual depth of stripping should be determined in the field by the geotechnical engineer. Strippings should be wasted off-site or stockpiled for use in landscaped areas if desired.
- 5. The building pads for the proposed Community Center and restroom building should be excavated to a depth of 24 inches below the bottom of proposed footings and redensified as engineered fill. Potentially expansive clay soil excavated during preparation of building pads should not be reused as engineered fill. The excavation should extend 5 feet beyond the building perimeters. The soil to be reused as structural fill and depth of the excavation should be approved in the field during construction by the geotechnical engineer or his representative.
- 6. In drive and parking areas, as a minimum, the top 8 inches of soil should be redensified as engineered fill. except where permeable pavements are planned (see Permeable Pavements,. No. 38,). Where soft or over moist soil conditions are observed, additional excavation may also be necessary. The geotechnical engineer should determine the depth of overexcavation where soft soil is encountered during construction. The bottom of excavations must be observed and approved by the geotechnical engineer or his representative prior to placement and compaction of engineered fill.

- 7. The bottom of the excavations and other areas to receive engineered fill should be scarified to a depth of 8 inches, moisture conditioned, and compacted to a minimum of 90 percent relative compaction. Portions of the site may need to be moisture conditioned to achieve suitable moisture content for compaction. These areas may then be brought to design grade with engineered fill.
- 8. Engineered fill should be placed in thin lifts not exceeding 8 inches in loose thickness, moisture conditioned, and compacted to a minimum of 90 percent relative compaction. The upper 8 inches of pavement subgrades should be compacted to a minimum of 95 percent relative compaction. The aggregate base below pavements should likewise be compacted to a minimum of 95 percent relative compaction.
- 9. If grading is performed during or shortly after the rainy season, the grading contractor may encounter compaction difficulty, such as pumping or bringing free water to the surface, in the upper surface sandy silt and sandy silt with clay. If compaction cannot be achieved after adjusting the soil moisture content, it may be necessary to over-excavate the subgrade soil and replace it with angular crushed rock to stabilize the subgrade. We estimate that the depth of over-excavation would be 12 to 24 inches under these adverse conditions.

- 10. Fills should be keyed and benched into firm soil or bedrock in areas where existing slope gradients exceed 7:1 (horizontal to vertical). Subdrains will be required in areas where keyways or benches expose potential seepage zones.
- The top 12 inches of soil encountered in our borings appears acceptable for use as engineered fill, provided it is properly moisture conditioned. On the east side of the Community Center site and the restroom building site excavated clay soil should not be reused as structural fill. Materials used for engineered fill should be free of organic material, and contain no rocks or clods greater than 6 inches in diameter, with no more than 15 percent larger than 4 inches. Engineered fill should have a plasticity index (P.I.)< 15 but have sufficient binder so that footing and utility trenches will not collapse.
- 12. We estimate shrinkage factors of 15 to 25 percent for the on-site materials when used in engineered fill.
- 13. After the earthwork operations have been completed and the geotechnical engineer has finished observation of the work, no further earthwork operations shall be performed except with the approval of and under the observation of the geotechnical engineer.

# Community Center- Conventional Spread Footings

- 14. Conventional spread footings may be used to support the Community Center building and restroom building provided the entire building pads are redensified as engineered fill to a depth of 24 inches below the bottom of footings. The redensified zone should extend 5 feet beyond the building perimeters. Actual footing depths should be determined in accordance with anticipated use and applicable design standards. The footings should be reinforced as required by the structural designer based on the actual loads transmitted to the foundation.
- 15. Footings should be founded a minimum of 18 inches below the lowest adjacent grade. Perimeter footings should be at least 15 inches wide. Actual footing depths and widths should be determined in accordance with anticipated use and applicable design standards. The footings should be reinforced as required by the structural designer based on the actual loads transmitted to the foundation. As a minimum, the footings should have four (4) number 4 reinforcement bars; 2 in the top and 2 in the bottom.
- 16. The foundation trenches should be kept moist and be thoroughly cleaned of all slough or loose materials prior to pouring concrete. In addition, all footings located adjacent to other footings or utility trenches should have their bearing surfaces founded below an imaginary 1½:1 plane projected upward from the bottom edge of the adjacent footings or utility trenches.

Project No. SC9704 23 December 2008

- 17. Foundations designed in accordance with the above may be designed for an allowable soil bearing pressure of 2500 psf for dead plus live loads. This value may be increased by one-third to include short-term seismic and wind loads.
- 18. Total and differential settlement under the proposed light building loads is anticipated to be less than 1 inch and ½ inch, respectively.
- 19. Lateral load resistance for structures supported on footings may be developed in friction between the foundation bottom and the supporting subgrade. A friction coefficient of 0.33 is considered applicable.

# Pedestrian Bridge - Pier and Grade Beam Foundation

- 20. The pedestrian bridge abutments should be founded on drilled cast-in-place reinforced concrete pier and grade beam foundations. Drilled piers should be designed for skin friction only. The piers should penetrate loose soil and be embedded a minimum of 8 feet into firm native soil. For pier design, the top 2 feet of soil in pier holes should be neglected.
- 21. The concrete piers should be a minimum of 18 inches in diameter and vertically reinforced the full length. The vertical reinforcement in the piers should be structurally tied to horizontal reinforced concrete grade beams. Reinforcing vertical steel for the concrete

piers should extend the full depth of the excavation to a point 3 inches above the bottom of the pier hole. The bottom of each hole should be cleaned of loose soil and debris prior to the installation of reinforcement.

- 22. The concrete piers should be designed for skin friction. The top 2 feet of soil should be neglected when calculating skin friction. An allowable skin friction of 600 psf per lineal foot may be used below a depth of 2 feet. This value may be increased by one-third to include the effects of short term wind and seismic loads. The bottom of all pier excavations should be a minimum of 15 feet horizontally from adjacent slope surfaces.
- The piers and grade beams should be designed to resist an active force equivalent to a fluid weight of 50 pcf acting against the top 2 feet of soil in the pier and against portions of the grade beam embedded in the ground. Along concrete piers, the active force should be considered to act on a plane 1½ times the diameter of the pier hole.
- Passive restraining earth pressures may be assumed to be equivalent to fluids weighing 425 pcf provided there is a minimum horizontal distance of 5 feet between the top of the zone of passive pressure and the adjacent slope surface. The passive resistance can be assumed to act on a plane 2 times the diameter of the piers.

89/163

We recommend that the geotechnical engineer or his representative be present for excavation of spread footings and pier foundations to confirm anticipated soil conditions and footing depths and sizes. If significant variations in soil conditions are encountered, additional recommendations will be presented.

## Seismic Design Criteria (CBC)

26. The 2007 California Building Code (CBC) provides site class definitions for seismic design of structures. Based on these definitions, the result of our investigation indicates the site is classified as <u>Site Class C</u>. The site is located at Longitude -121.9431° and Latitude 36.9886°. The following maximum considered earthquake and five percent damped design spectral response accelerations adjusted for site class effects should be used for seismic design based on Sections 1613.5.3 and 1613.5.4 of the 2007 CBC:

A. 
$$S_{MS} = 1.500$$

B. 
$$S_{M1} = 0.815$$

$$S_{DS} = 1.000$$

D. 
$$S_{D1} = 0.543$$

# **Soil Corrosivity**

27. The results of soil corrosivity testing on near surface soil at the Community Center site are presented in the following table:

# TABLE 5

Corrosivity Test Results

Sample	Resistivity (Ohm-cm)	Chloride (mg/kg)	Sulfate (mg/kg)	рН
15-1-1	1465	<2	<5	7.7

The test results indicate the soil has a low potential for corrosion. A test summary is also presented in the appendix (see Figure 57 in Appendix B).

#### Retaining Walls

- 28. For retaining walls designed at the site, conventional spread footings may be used for the walls. For fully drained walls up to 8 feet high, the following design criteria should be used:
- A. Active earth pressure for walls allowed to yield (up to ½ percent of wall height) is that exerted by an equivalent fluid weight of 40 pcf for a level backslope and 55 pcf for a 2:1 backslope.
- B. Where walls are <u>not</u> allowed to yield (restrained condition), the walls should be designed to resist a uniformly distributed load (rectangular distribution) of 28H psf per foot for a level backslope and 38H psf per foot for a 2:1 backslope, where H is the total height of the wall.

- C. A spread footing foundation system is recommended for retaining walls. The walls may be designed for an allowable bearing capacity of 2000 psf plus a one-third increase for wind and seismic loads.
- Use a coefficient of friction of 0.33 between the base of the foundation and soil.A passive resistance of 300 pcf may be used below a depth of 12 inches.
- E. For seismic design, a dynamic lateral force equal to 14H<sup>2</sup> lbs should be added to the active pressure and applied at a point 0.6H above the heel of the wall (where H is the height of the wall).
- F. In addition, the walls must be designed for any adjacent live or dead loads which will exert a force on the wall (compaction equipment, structures or traffic).
- G. Retaining walls which act as interior building walls should be waterproofed.
- H. The above lateral pressures are provided assuming the walls are fully drained to prevent development of hydrostatic pressure behind the walls. Drainage materials behind the wall should consist of Class 1, Type A permeable material (Caltrans Specification 68-1.025) or an approved equivalent. The drainage material should be at least 12 inches thick. The drains should extend from the base of the walls to

within 12 inches of the top of the backfill. The top 12 inches of backfill behind the wall should be relatively impermeable native soil compacted in place. A perforated pipe should be placed (holes down) about 4 inches above the bottom of the wall and be tied to a suitable drain outlet.

Wall backfill should be compacted to a minimum of 90 percent relative compaction.
 The backfill material should be approved by the geotechnical engineer.

#### Slabs-on-Grade

- 29. In areas where floor wetness would be undesirable, a blanket of 4 inches of free-draining gravel should be placed beneath the floor slab to act as a capillary break. In order to minimize vapor transmission, a vapor retardant (minimum 10 mil thickness) should be placed over the gravel. The membrane should be covered with 2 inches of sand or rounded gravel to protect it during construction. The sand or gravel should be lightly moistened just prior to placing the concrete to aid in curing the concrete.
- 30. Exterior concrete slab-on-grade subgrade soil should be proof rolled to provide a smooth, firm surface for slab support. Reinforcing should be provided in accordance with the anticipated use and loading of the slab. The reinforcement should not be tied to the building foundations. These exterior slabs can be expected to suffer some cracking and movement. However, thickened exterior edges, a well-prepared subgrade including pre-

moistening prior to pouring concrete, adequately spaced expansion joints, and good workmanship should minimize cracking and movement.

## **Utility Trenches**

- 31. Trenches must be properly shored and braced during construction or laid back at an appropriate angle to prevent sloughing and caving at sidewalls. The project plans and specifications should direct the attention of the contractor to all CAL OSHA and local safety requirements and codes dealing with excavations and trenches.
- 32. Utility trenches that are parallel to the sides of buildings should be placed so that they do not extend below an imaginary line sloping down and away at a 1½:1 (horizontal to vertical) slope from the bottom outside edge of all footings. The structural design professional should coordinate this requirement with the utility layout plans for the project.
- 33. Trenches should be backfilled with granular-type material and uniformly compacted by mechanical means to the relative compaction as required by County of Santa Cruz specifications, but not less than 95 percent under paved areas and 90 percent elsewhere. The relative compaction will be based on the maximum dry density obtained from a laboratory compaction test run in accordance with ASTM Procedure D1557-07.

- 34. We strongly recommend placing a three-foot (3') wide concrete plug in each trench which passes under the exterior foundations to reduce the potential for water intrusion in underfloor areas. Care should be taken not to damage utility lines.
- 35. Trenches should be capped with a minimum of 12 inches of compacted relatively impermeable soil.

#### **Pavement Sections**

- 36. For design of pavement sections, an R-Value=7 should be used for design of pavements in the lower parking lot and and an R-Value=30 should be used in the upper parking lot. California Bearing Ratio test results indicate the CBR= 25.6% at 95 percent relative compaction for soil in the upper parking lot. R-Value and CBR test results are included in Appendix B. For designed pavement sections to perform to their greatest efficiency, it is important that the following items be considered:
  - A. Properly moisture condition the subgrade and compact it to a minimum relative compaction of 93 to 95 percent at a moisture content of 1 to 3 percent over the optimum moisture content. If permeable pavements are designed, the subgrade should be prepared as recommended in No. 38, Permeable pavements. If additional storm water storage capacity is needed, subgrade soil may be replaced with permeable angular aggregate rock. (1" maximum diameter

- B. Provide sufficient gradient to prevent ponding of water.
- C. Use only quality materials of the type and thickness (minimum) specified. All base rock, unless otherwise noted, must meet State of California Standard Specifications for Class 2 Aggregate Base, and be angular in shape. If pervious concrete pavements are designed for the parking lots and driveways, permeable angular aggregate rock may be used in replacement of aggregate base.
- D. Compact the base rock uniformly to a minimum of 95 percent relative compaction.
- E. Place the asphaltic concrete only during periods of fair weather when the free air temperature is within a prescribed limit.
- F. Provide a routine maintenance program.

## Permeable Pavement

Percolation test results indicate the near surface soils at the site have low permeability. To provide additional storage volume and improve the infiltration of near surface soil, replacement of subgrade soil with permeable angular rock (1" maximum diameter) is acceptable. To prevent migration of rock into the subsoil and provide stability, we recommend a woven geotextile (US 200 or equivalent) be placed between the rock and soil. The subgrade soil should not be compacted prior to placement of the geotextile. The rock placed on the geotextile should be compacted in 4 inch lifts (maximum thickness) with a hand operated vibratory plate compactor.

38. When the subgrade soil is excavated to achieve design elevations, care should be taken to prevent compaction of the soil. The subgrade soil should remain as undisturbed as possible to allow optimal infiltration. The subgrade should have a minimum gradient of 1 percent toward subdrains along parking lots and driveways which intercept storm water which does not infiltrate into the ground. Water from subdrains should be conveyed to trench drains or pits on the slopes below the parking lots.

#### Site Drainage

- 39. Proper drainage is essential to the project. Surface drainage should include provisions for positive gradients so that surface runoff is rapidly removed and not allowed to pond adjacent to foundations or pavements. Surface drainage should be directed away from the building foundations to collection systems which convey runoff to the on site storm water retention system or off site storm drain system.
- 40. Subdrains along parking lots should extend a minimum of 12 inches below the subgrade elevation. The subdrains should be a minimum of 12 inches wide and should have a minimum slope of 2 percent. The subdrains should be backfilled with Class 1, Type A permeable material (State of California Standard Specification No. 68-1.025). A four (4) inch diameter rigid perforated pipe should be placed within 3 inches of the bottom of the trench. The down slope end of subdrains should be connected to a solid pipe which conveys water downslope to trench drains or pits.

- 41. Trench drains or pits should be a minimum of 18 inches wide and extend to a depth of 6 feet. The trenches or pits should be filled with ¾ inch diameter crushed rock (no fines) wrapped in filter fabric (Mirafi 140N or equivalent). The top 12 inches of the trench or pit should be compacted on site soil. Clean outs should be installed to allow monitoring of the trenches or pits and removal of sediments, if necessary.
- 42. Rain gutters and downspouts should be placed around roof eaves. Discharge from the rain gutters should be conveyed from downspouts via splash blocks or solid plastic pipe (minimum 3 inches diameter) and discharged away from foundations and improvements to collection facilities which convey runoff to the on site storm water retention system or off site storm drain system.
- 43. The migration of water or spread of extensive root systems below foundations, slabs, or pavements may cause undesirable differential movements and subsequent damage to these structures. Landscaping should be planned accordingly.

#### **Erosion Control**

- 44. Bare soil at the project site has potential for erosion. We recommend the following provisions be incorporated into the project plans.
  - A. All grading and soil disturbance shall be kept to a minimum.
  - B. No eroded soil will be allowed to leave the site.

198/163

C. All bare soil should be seeded and mulched immediately after grading with barley, rye, grass and crimson clover.

#### Plan Review, Construction Observation, and Testing

Haro, Kasunich and Associates should be provided an opportunity to review project plans prior to construction to evaluate if our recommendations have been properly interpreted and implemented. We should also provide earthwork observations and testing and foundation excavation observations during construction. This allows us to confirm anticipated soil conditions and evaluate conformance with our recommendations and project plans. If we do not review the plans and provide observation and testing services during the earthwork phase of the project, we assume no responsibility for misinterpretation of our recommendations.

199/163

#### LIMITATIONS AND UNIFORMITY OF CONDITIONS

- 1. The recommendations of this report are based upon the assumption that the soil conditions do not deviate from those disclosed in the borings. If any variations or undesirable conditions are encountered during construction, or if the proposed construction will differ from that planned at the time, our firm should be notified so that supplemental recommendations can be given.
- 2. This report is issued with the understanding that it is the responsibility of the owner, or his representative, to ensure that the information and recommendations contained herein are called to the attention of the Architects and Engineers for the project and incorporated into the plans, and that the necessary steps are taken to ensure that the Contractors and Subcontractors carry out such recommendations in the field. The conclusions and recommendations contained herein are professional opinions derived in accordance with current standards of professional practice. No other warranty expressed or implied is made.
- 3. The findings of this report are valid as of the present date. However, changes in the conditions of a property can occur with the passage of time, whether they are due to natural processes or to the works of man, on this or adjacent properties. In addition, changes in applicable or appropriate standards occur whether they result from legislation or the broadening of knowledge. Accordingly, the findings of this report may be invalidated, wholly or partially, by changes outside our control. Therefore, this report should not be relied upon after a period of three years without being reviewed by a geotechnical engineer.



# THE FARM NEIGHBORHOOD PARK AND COMMUNITY CENTER BIOTIC STUDY

Prepared by:

H. T. Harvey & Associates

Prepared for:

MIG 800 Hearst Avenue Berkeley, California 94710

4 December 2009

Project # 2853-01

ATTACHMENT

that would result in the regional decline of this species; (3) a relatively large number of individuals within a population that is considered rare or declining; (4) the species' metapopulation (e.g., if one of only a few known populations occurs in the impact zone, or if the species has extremely narrow habitat requirements); or (5) a habitat type or vegetation community in regional decline or that is endemic.

Impacts to species or habitats would be less than significant if they are expected to affect only a very small percentage of regional populations (for species) or the regional extent (of habitats) because the Project will affect only a small number/limited extent of the resource and/or because the resource is regionally abundant.

#### IMPACTS FOUND TO BE LESS THAN SIGNIFICANT

#### Loss of California Annual Grassland and Ornamental/Landscaped Habitats

Approximately 1.71 acres of low-quality, disturbed California annual grassland and 1.20 acres of ornamental/landscaped habitat will be permanently impacted by the Project by conversion of these areas to park development elements such as buildings, play areas, parking, and other park features described above. The areas that will be impacted have already been disturbed by previous fill activities resulting from construction, clearing, and ongoing mowing. As such, these habitats provide only marginally suitable habitat for native plants. Wildlife species associated with the annual grassland and ornamental/landscaped habitats consist of common, regionally widespread species, many of which are well adapted to suburban areas such as the Project site. As a result, regional populations of these wildlife species, as well as the regional abundance of these habitat types in general, are very high, and the Project site represents only a very small fraction of the regional populations. Therefore, impacts to plants and wildlife associated with California annual grassland and landscaped/ornamental habitats on the site do not meet the CEQA standard of having a substantial adverse effect on these species' populations, and thus, impacts to these habitats are considered to be less than significant.

#### Loss of Maple-leaved Checkerbloom

While this species often occurs in disturbed areas, there is a low probability of occurrence on-site due to the predominance of non-native species and the degree of disturbance at the site. Maple-leaved checkerbloom was not observed during reconnaissance-level surveys of the Project site in 2008. If maple-leaved checkerbloom should occur on site, it would occur in such low abundance that the impact to this species would be negligible relative to the regional populations and would not reach the threshold of a *substantial* reduction in the population of this special-status species.

Furthermore, Project effects include removal of non-native woody species, thus creating disturbance that enhances this species' habitat, and Project restoration activities will create new habitat for this species as well. Therefore, due to the unlikelihood of occurrence, the low probability that a substantial number of individuals of this species would be adversely affected, and the potential benefits of the Project to this species, we feel that impacts to any individual maple-leaved checkerbloom plants that may occur on-site would be fully offset by the proposed

ATTACHMENT

Project. Thus, no further surveys for this species are necessary, and Project impacts to this species are considered to be less-than-significant under CEQA.

# Impacts to Foraging Special-Status Wildlife Species

Several special-status wildlife species may occur on the Project site only as rare visitors, migrants, or transients. These species may occasionally forage on the site, but they are not expected to breed there. These species include the bank swallow, western red bat, yellow warbler, and tricolored blackbird. The Project will have no effect on the breeding success of any of these species. Project activities may result in a very small and temporary reduction of foraging habitat available to these species locally, although foraging habitat for all four species will not change appreciably in the long term as a result of the Project. Due to the abundance of similar habitats locally and regionally and the infrequency with which most of these species occur on the Project site, the Project's impacts do not meet the CEQA standard of having a substantial adverse effect on these species' populations, and the Project will have a less than significant impact on these species.

#### SIGNIFICANT IMPACTS THAT CAN BE MITIGATED TO A LESS-THAN-SIGNIFICANT LEVEL

#### Impacts to Water Quality

Construction work, including grading during construction and excavation of small areas of the creek channel during the instream channel stabilization work, could mobilize soil during construction, resulting in the potential for decreased water quality along the creek channel downstream of the Project site.

## Mitigation Measures for Impacts to Water Quality

The Project construction and instream channel stabilization construction will be designed and constructed to avoid impacts to water quality within the creek corridor. The incorporation of best management practices (BMPs) and construction methods to avoid impacts to water quality will reduce Project impacts to water quality to less than significant levels.

Mitigation Measure 1a. Best Management Practices. Erosion control and BMPs will be employed at the instream site and general construction throughout the Project site to avoid adverse water quality impacts from sediment transport during construction and to ensure that no debris, soil, silt, sand, bark, slash, sawdust, cement, concrete, washings, petroleum products or other organic or earthen material will be allowed to enter into or be placed where it may be washed by rainfall or runoff into the creek from the Project site during construction. Construction work in the creek channel will be limited to the dry season (15 April – 15 October) when no flow is expected and will include the installation of silt fencing to limit sediment from entering the creek channel during construction. These BMPs will also include measures to divert flow such as a temporary culvert or pipe in the event an unexpected flow event occurs.

Mitigation Measure 1b. All disturbed areas not developed or designed for other planting treatments will be seeded with an appropriate erosion control native seed mix and revegetated

with native plantings as described above in the *Overview and Assumptions* section of this impact assessment. The native plant palette and the erosion control seed mix will be developed in detail in the Project's Habitat Mitigation and Monitoring Plan.

## Loss of Coast Live Oak Riparian Forest/Eucalyptus Trees

The existing habitat along the unnamed creek is highly degraded, with a mixture of native coast live oak and non-native eucalyptus species dominating the creek channel, interspersed with additional non-native species such as cotoneaster, tree-of-heaven, English ivy, cape ivy, periwinkle, and Himalayan blackberry along the creek channel (Figure 5). Overall, this existing vegetation provides low habitat functions and values, especially when compared with riparian habitats fully vegetated with native species).

Trimming of Coast Live Oak Trees for Pedestrian Bridge. The pedestrian bridge is located where it will minimize impacts to native coast live oak trees. However, to facilitate the placement of the pedestrian bridge and the abutments on either end of the bridge, coast live oak riparian forest/eucalyptus tree habitat may be impacted by pruning of trees within the grading footprint and along the bridge corridor of the proposed pedestrian bridge. The impacts to native coast live oak trees resulting from the trimming of trees within the pedestrian bridge impact area are 0.04 acres.

Tree Branch or Root Trimming During Trenching of Drainage Pipe. The drainage and detention system for the Tee Street side of the Project is designed to accommodate a 25-year flood event which will convey flow through a 12 to 18 inch pipe. The pipe will outflow into a crib wall structure on the creek bank (which is part of the instream stabilization features) where the water will infiltrate into a vegetated well drained soil/gravel mixture. The pipe will be located above the ordinary high water mark. The installation of the pipe will require trenching from the proposed catch basin across an area of coast live oak riparian forest/eucalyptus tree habitat. The pipe will be located to avoid and minimize impacts to existing trees and along the construction access route planned for the instream stabilization work described below. However, the construction work to install this pipe may require some minor trimming of overhead branches or roots.

Removal of Eucalyptus Trees Plus Removal of One Pine. As part of the Project goals for the restoration component of this project, and also to address safety issues relating to trees identified in arborist reports as having structural concerns, a number of non-native individual eucalyptus trees will be removed from within and adjacent to the unnamed creek. This non-native tree removal will include removal of the grove of eucalyptus trees located at the southwest corner of the property (Figure 5) (Belton 2007, H. T. Harvey & Associates 2009). In addition to these eucalyptus trees, one large leaning pine will be removed within the coast live oak riparian forest/eucalyptus tree habitat area. The total removal of these trees will result in 0.18 acres of impacts to trees within the coast live oak riparian forest/eucalyptus tree habitat. Removal of other non-native trees including cotoneaster and tree-of-heaven will not result in impacts as these are undesirable invasive species.

Removal of Understory Vegetation. The Project will remove some understory vegetation during tree trimming, bridge placement, trenching and instream restoration construction, and

eucalyptus removal. This understory vegetation comprises predominantly invasive non-native plants with low habitat value, and much of the disturbed areas will rapidly recolonize with the same groundcover species.

#### Mitigation Measures for Impacts to Coast Live Oak Riparian/Eucalyptus Forest

The Project has been designed to avoid and minimize impacts to native riparian vegetation along the creek channel. Mitigation measures are described below for impacts to coast live oak riparian/eucalyptus forest, and implementation of these measures will reduce impacts to this resource to a less than significant level.

Mitigation Plantings For Trimming of Coast Live Oak Mitigation Measure 2a. Riparian/Eucalyptus Forest. The impacts to coast live oak trees from the trimming within the area of the pedestrian bridge will be mitigated on an acreage basis at a ratio of 1:1 (mitigation:impact) by planting new coast live oak riparian forest habitat. Mitigation for impacts to replace Coast Live Oak Riparian/Eucalyptus Forest will occur on-site, within the restoration areas (See Habitat Restoration Summary and Table 5 below).

Mitigation Measure 2b. Tree Protection Zones and Protective Fencing. An arborist report has been prepared (H. T. Harvey & Associates 2009) that defines tree protection zones for each of the trees on the Project site and also details construction techniques to protect trees during Trees slated for preservation will be prominently marked to avoid injury or accidental removal during construction and during tree removal/trimming activities. Any trees requiring trimming will be trimmed prior to construction to avoid additional damage to the tree or to adjacent trees. Vehicles and equipment will be kept away from the soil and sensitive rooting zones within the tree protection zones. Protective fencing will be installed under the supervision of the Project arborist prior to the onset of construction. Protective fencing will be a minimum of 4 ft in height and will remain in place until all construction is complete.

Mitigation Measure 2c. Tree Transplanting. Based on the current schematic design (MIG Design Team 2009) and the arborist report for the Project (H. T. Harvey and Associates 2009), approximately 8-12 healthy coast live oak trees (each with a diameter of 8 in or less) within the development area have been determined suitable for transplant into areas of the site slated for habitat mitigation. The placement of these trees into the mitigation areas will help to jump-start the development of the restoration areas. All transplanting activities will be supervised by the project arborist to ensure this work is done using sound ecological techniques and that no additional impacts to trees occurs to the coast live oak riparian forest/eucalyptus habitat. Oak trees that will be transplanted would therefore not require further mitigation.

Mitigation Measure 2d. Drainage Pipe/Construction Avoidance Measures. The layout of the drainage pipe shall be staked and verified in the field by the Project biologist as the most feasible alignment to avoid coast live oak root or branch pruning. The trenching and installation of the pipe will be supervised by the Project biologist (with assistance from a licensed arborist as needed) to ensure that this construction will avoid and/or minimize any impacts to the roots or canopy of adjacent trees. Any required root or branch pruning shall be done at the direction and using methods approved by the project biologist. The impacts to tree roots are not expected to adversely affect the survival of the trees, therefore no mitigation is proposed.

Mitigation Measure 2e. Non-native Woody Species Removal. In order to enhance the existing coast live oak riparian forest occurring on the site, non-native woody species including all tree-of-heaven and cotoneaster will be removed (no mitigation is proposed as they are undesirable invasive species). Individual non-native eucalyptus trees identified for removal for instream channel stabilization work and the grove of non-native eucalyptus trees at the southwest corner of the site will also be removed and these areas will be replanted with native plantings typical of a coast live oak riparian forest. The removal of non-native eucalyptus trees will be mitigated on an acreage basis at a ratio of 2:1(mitigation:impact) by planting new coast live oak riparian forest habitat. It should be noted that no mitigation is proposed for non-native groundcover plants, tree-of-heaven, and cotoneaster as these are invasive and undesirable species.

#### Loss of Coast Live Oak Habitat/Individual Coast Live Oak Trees

The coast live oak habitat is vegetated with a mixture of coast live oak interspersed with nonnative groundcover species. None of these trees are located within the riparian area. Grading and installation of park elements will result in the removal of a number of these trees as well as a number of individual coast live oak that are located outside the Coast Live Oak Habitat (Table 4). The removal of any of those trees is considered significant. Although no trimming of these oak trees is planned during construction at this time we have included mitigation measures (Mitigation Measure 3a) if trimming of these trees is required during construction. As described above under Mitigation Measure 2c, some oak trees will be transplanted and will not require mitigation as they are not considered impacted.

# Mitigation Measures for Impacts to Coast Live Oak Habitat/Individual Coast Live Oak Trees

Mitigation for loss of Coast Live Oak Habitat and Individual Coast Live Oak Trees includes planting replacement trees and habitat restoration and monitoring. Tables 3 and 4 provide a summary of the impacted trees, mitigation ratios and the associated mitigation for these trees. A summary of the habitat restoration mitigation is provided below in Table 5 and in the associated restoration description. The mitigation measures described below will reduce the impact to Coast Live Oak habitat to less than significant levels.

Mitigation Measure 3a. Planting of Coast Live Oak Trees. Any trees that will be impacted due to branch pruning will be mitigated at a ratio of 1:1 (area of impacts:mitigation area). Trees that will be removed will be replaced on a per stem basis (number of trees planted:number of trees removed). Table 3 provides a summary of tree size categories and the replacement ratios for trees which will be removed.

Table 3. Summary of Oak Tree Replacement Ratios

SIZE OF TREE REMOVED (DBH, IN INCHES) <sup>1</sup>	REPLACEMENT RATIO (NUMBER OF TREES PLANTED:NUMBER OF TREES REMOVED)				
Removed 6-11"	2:1				

Removed 12-17"	3:1
Removed 18-24"	4:1
Removed >24"	5:1

dbh is defined as the diameter of the tree at breast height, or the diameter of the tree at 4.5 feet above existing grade.

Based on the replacement ratios in Table 3, and the size and number of trees impacted (Table 4), 43 trees are required to mitigate for tree removal. Based on 16-foot on-center plant spacing for replacement trees, the area required for replacement tree planting is approximately 0.25 acres (Table 4). Most of these trees will be located within the restoration area, but some of the replacement trees will also be located within the developed park areas.

Table 4. Oak Tree Impacts and Mitigation

TREE (OR GROUP) TAG NUMBER¹	COMMON NAME	SPECIES	SIZE CLASS (DBH)	NUMBER OF TREES IMPACTED	NUMBER OF TREES REQUIRED FOR MITIGATION <sup>2</sup>
13	coast live oak	Quercus agrifolia	12-17"	1	3
57	coast live oak	Quercus agrifolia	6-11"	3	6
58	coast live oak	Quercus agrifolia	6-11"	2	6
58	coast live oak	Quercus agrifolia	12-17"	1	3
2113	coast live oak	Quercus agrifolia	12-17"	1	3
220 <sup>3</sup>	coast live oak	Quercus agrifolia	18-24"	1	4
221 <sup>3</sup>	coast live oak	Quercus agrifolia	12-17"	5	15
223 <sup>3</sup>	coast live oak	Quercus agrifolia	12-17	]	3
Total Number of Trees Impacted 15				15	
Total Number of Trees Required For Mitigation					43 (+/- 0.25 acres)

<sup>&</sup>lt;sup>1</sup>Tree tag numbers are derived from the arborist report (H. T. Harvey & Associates 2009) and may describe several trees in a close grouping.

# Impacts to Aquatic Habitat and Coast Live Oak Riparian Forest/ Eucalyptus Resulting from Instream Channel Stabilization Work

The existing aquatic habitat can be described as a degraded, ephemeral creek characterized by incision, with areas of unstable and slumping banks. The instream channel stabilization work has been designed to enhance and improve the structure of the aquatic habitat over the long-term and minimize the potential for bank instability and erosion along the creek channel.

The construction of the instream channel stabilization will impact 0.08 acres of the aquatic habitat and creekbank. Several non-native trees that are located within the channel stabilization work area, including a eucalyptus tree and a pine tree will be removed during construction of the weir structures. Construction in this area will also include site grading and removal of primarily non-native understory.

<sup>&</sup>lt;sup>2</sup>Refer to Table 3 for ratios

<sup>&</sup>lt;sup>3</sup>This tree is located outside the Coast Live Oak Habitat area.

Mitigation Measures for Impacts to Aquatic Habitat and Coast Live Oak Riparian Forest/ Eucalyptus Resulting from Instream Channel Stabilization Work

The mitigation measures described here will reduce the temporary impacts to aquatic habitat and creek banks from the instream channel stabilization work to a less than significant level.

Mitigation Measure 4a. Channel Repair and Stabilization. The instream channel restoration work will focus on repair and stabilization of three existing drops in the channel bed which are currently supported by a mixture of logs, roots, and debris (including car tires, pieces of outdoor furniture, and other trash). If left unchecked, the upstream migration of these features could further incise the channel and produce additional bank stability concerns. The planned channel repair will stabilize these features over the design-life of the Project (many decades), reducing the long-term potential for bank instability, in addition to increasing the habitat quality and the aesthetics of the creek corridor. The goal of the restoration and stabilization work is to mimic the existing character of healthy local ephemeral coastal drainages in the area by utilizing wood harvested on-site for grade and erosion control features rather than rock or other hard reinforcement. Wood placement for instream stabilization will be entirely deliberate while providing the appearance of a network of fallen trees. These features will resist movement and enhance ecologic function.

The three existing drop features will be reconfigured using logs and rootwads removed from the banks and adjacent terraces as part of the revegetation work. Logs and only a few local rocks will be used to construct steps or weirs that discourage runoff from eroding channel banks and prevent upstream migration of channel incision. The logs will be keyed into the adjacent channel banks and will be arranged in a loose network with other placed logs to prevent destabilization. Local logs and rootwads will also be placed longitudinally in lightly regraded areas where channel banks have become oversteepened from past slumping. These longitudinal logs will discourage bank erosion and support the growth of new and existing plantings. A small redwood crib wall will be constructed to reinforce an oversteepened bank at the upstream end of the stream restoration envelope, where decaying rootwads of non-native eucalyptus will be removed.

Mitigation Measure 4b. Best Management Practices. Mitigation measures for impacts to aquatic habitat will include those described above under Mitigation Measures for Impacts to Water Quality. In summary, these include performing monitoring by a Project biologist during construction, construction work during the dry season, use of BMPS, and implementation of erosion control measures during construction.

Mitigation Measure 4c. Revegetation of Channel Slopes. This impact footprint from the channel stabilization work will be fully restored/mitigated at a ratio of 1:1. The non-native trees which will be removed as part of this work will be mitigated at a ratio of 2:1. Mitigation measures to restore the impact footprint will include revegetation of the channel slopes with native vegetation which is characteristic of coast live oak riparian forests. The revegetation is designed to stabilize the channel slopes, increase channel stability, and enhance the riparian and aquatic habitat. Native vegetation will consist of species designed to provide multi-level canopy structure as described above in the Overview and Assumptions section of this report.



# **Habitat Restoration Summary**

Table 5 summarizes impacts and mitigation for the sensitive habitat areas occurring on the Project. Mitigation will occur within the habitat restoration areas as shown on the Project's schematic design drawings (MIG Design Team 2009). The areas chosen for mitigation are contiguous with existing riparian habitat and will be maintained and protected from future disturbance to promote the development of high quality habitat along the creek corridor. The primary location of mitigation is within the footprint of grading and construction access for the instream restoration and eucalyptus removal areas, as well adjacent to the proposed development features within the pedestrian bridge and coast live oak impact areas. Also the project will utilize the 10-20 foot riparian buffers and 10 foot building setbacks along the edge of the existing riparian corridor on both sides of the channel for mitigation as required.

The mitigation will comprise restoration of high quality coast live oak riparian habitat via planting a multilayer canopy of native trees and shrubs. The specific plant species list will be defined with the development of the Mitigation and Monitoring Plan. However, the restoration tree and shrub plantings will comprise species typically found in a coast live oak riparian forest such as coast live oak, blue elderberry, California buckeye, California hazelnut, California rose, sticky monkeyflower, and California blackberry. Such species will develop into a multi-storied canopy that will provide an increase in native riparian habitat along this section of the unnamed creek corridor. The channel stabilization features will also add to the structure of the creek and stabilize and halt the potential for future erosion and incision of the channel in this portion of the channel.

Table 5. Summary of Impacts and Mitigation for Sensitive Habitat /Coast Live Oak Trees

HABITAT TYPE	IMPACT	IMPACT AREA (ACRES)	MITIGATION RATIO (IMPACT:MITIGATION)	MITIGATION AREA (ACRES)
Coast live oak riparian forest/eucalyptus	Coast live oak tree trimming at pedestrian bridge impact area	0.04	3:1	0.12
California annual grassland, developed/ornamental, coast live oak	Loss of individual coast live oak trees	n/a	See Table 4	0.25
Coast live oak riparian forest/eucalyptus	Eucalyptus removal	0.17	2:1	0.34
Coast live oak riparian forest/eucalyptus, ephemeral aquatic	Instream channel stabilization	0.09	1:1	0.09
	Total Mitigation	0.30		0.8

To ensure the success of the mitigation measures outlined in this report, a Riparian Habitat Mitigation and Monitoring Plan will be prepared by a qualified restoration ecologist during the regulatory agency permitting phase and will provide the following information:

• Brief summary of the proposed project

ATTACHMENT

This measure is not mandatory, as an additional pre-construction survey and other measures will be performed as described below. However, implementing this measure will allow for bat exclusion prior to the breeding season, thus minimizing the potential bat-related constraints to the timing of construction.

Mitigation Measure 5b. Because the aforementioned survey will be conducted prior to the breeding season, several months may pass between that survey and the initiation of construction or demolition in a given area. Therefore, another pre-construction/pre-demolition survey for roosting bats, following the methods described above, will be conducted within 15 days prior to the commencement of these activities in a given area to determine whether bats have occupied a roost in or near the Project's impact areas. This survey, which would be conducted using the methods described for Measure 5a, would be facilitated considerably by information (e.g., on potential roosts) gathered during the previous survey.

Mitigation Measure 5c. If a maternity roost of any bat species is present, the bat biologist will determine the extent of a construction-free buffer around the active roost that will be maintained. This buffer would be maintained from 1 April until the young are flying, typically after 31 August.

Mitigation Measure 5d. If a roost of any kind is found in a tree or structure that will not be disturbed by construction, or that can be avoided, the roost structure will not be impacted if feasible.

Mitigation Measure 5e. If a day roost is found in a tree or structure that is to be removed, individual bats will be safely evicted under the direction of a qualified bat biologist. Eviction of bats will occur at night, so that bats will have less potential for predation compared to daytime roost abandonment. Eviction will occur between 1 September and 15 October and/or between 15 February and 15 March but will not occur during long periods of inclement or cold weather (as determined by the bat biologist) when prey are not available or bats are in torpor. If feasible, one-way doors will be used to evict bats from roosts. If use of a one-way door is not feasible, or the exact location of the roost entrance is not known, the roosts that need to be removed should first be disturbed by removal of some of the trees' limbs or portions of the structure (e.g. wooden water tanks) not containing the bats. Such disturbance will occur at dusk to allow bats to escape during the darker hours. These trees or structures would then be removed the following day. All of these activities will be performed under the supervision of the bat biologist.

Mitigation Measure 5f. Although Project activities that require removal of or work near a pallid bat maternity roost site would occur during the nonbreeding season, such activities may result in the removal or abandonment of such a roost site. If a roost site that is used as a maternity roost by pallid bats is removed or abandoned as a result of Project activities, an alternative roost will be constructed. The design and placement of this structure will be determined by a qualified bat biologist based on the location of the original roost and the habitat conditions in the vicinity. This bat structure will be erected at least one month prior to removal of the original roost structure, or as soon as possible after a roost site is determined to have been abandoned as a result of Project activities.

Mitigation Measure 5g. In some circumstances, it may be beneficial to allow roosting bats to continue using a roost while construction is occurring on or near the roost site. For example, if a tree found to contain a day roost is located near the construction area but will not be removed, a qualified bat biologist (in consultation with the CDFG) will determine whether the bats should be evicted or whether they should remain in place. If it is determined that the risks to bats from eviction (e.g., increased predation or exposure, or competition for roost sites) are greater than the risk of colony abandonment, then the bats will not be evicted.



# THE FARM NEIGHBORHOOD PARK AND COMMUNITY CENTER MITIGATION AND MONITORING PLAN

Prepared by:

H. T. Harvey & Associates

Prepared for:

MIG 800 Hearst Avenue Berkeley, California 94710

4 December 2009

Project # 2853-01



#### **MITIGATION SUMMARY**

The project will be conducting 4 types of restoration in different areas:

- 1. Oak Riparian Mitigation- The primary focus of this document is the oak riparian mitigation area (Figure 3) which is mitigation for impacts to sensitive and regulated habitats. The instream restoration area is included within this mitigation area. This mitigation element is for project impacts to the jurisdiction of CDFG, RWQCB, and the County (the County requires mitigation for impacts at the bridge and other infrastructure improvements but not for the impacts relating to instream restoration work)
- 2. Oak Tree Replacement Mitigation- There will be oak replanting outside the mitigation area to compensate for oak trees removed from areas outside sensitive and regulated habitats. This mitigation is for impacts to trees only regulated under CEQA.
- 3. County of Santa Cruz Riparian Exception Buffer Plantings- The project will be restoring native plants in within the riparian buffer areas shown on Figure 3.
- 4. Additional Park Restoration Plantings- The Park project will be installing native plants extensively throughout the site to enhance habitat values.

The oak riparian mitigation areas are contiguous with existing riparian habitat and will be maintained and protected from future disturbance to promote the development of high quality habitat along the creek corridor. This mitigation area was also specifically expanded to include full restoration in the area where the grove of non-native eucalyptus trees and a large pine tree will be removed.

The mitigation will comprise restoration of high quality coast live oak riparian habitat via planting a multilayer canopy of native trees and shrubs. The mitigation plantings will comprise species typically found in a coast live oak riparian forest such as coast live oak, blue elderberry (Sambucus mexicana), California buckeye (Aesculus californica), California hazelnut (Corylus cornuta), California rose (Rosa californica), sticky monkeyflower (Mimulus aurantiacus), and California blackberry (Rubus ursinus). Such species will develop into a multi-storied canopy that will provide an increase in native riparian habitat along this section of the creek corridor. Integral to the riparian mitigation area is the creek stabilization work, which will reduce current and future physical instability in the creek channel and banks, reduce sedimentation related water quality impacts, and reduce vegetation loss due to creek erosion.

15



# THE FARM NEIGHBORHOOD PARK AND COMMUNITY CENTER ARBORIST REPORT

Prepared by:

H. T. Harvey & Associates

Prepared for:

MIG 800 Hearst Avenue Berkeley, CA 94710

## RECOMMENDATIONS

## TREE PRESERVATION AND IMPACT MINIMIZATION

Approximate tree preservation zones were identified for each tree on the Project site and depicted on Figure 1 in Appendix B. Areas were divided into those along the unnamed creek restoration area (with the assumption these areas will largely be undeveloped), areas in proximity to proposed development that have potential for preservation, and areas in close proximity to proposed development that will likely result in tree removals. These zones represent a rough, general estimation of the critical root zones for each tree if the tree were a candidate for preservation. The preservation zones were determined by establishing a radius around each individual tree of one foot of protection for every inch of trunk diameter (a 10 inch diameter tree would have a tree preservation radius of 10 feet). The tree protection zones described in this report have been determined on a tree by tree basis differently and separately from protection buffers associated with the overall Riparian Corridor as defined by County of Santa Cruz code and/or by the California Department of Fish and Game. Those protection buffers will be separately addressed in the Riparian Exception permit application.

Once the Project plans have moved past the schematic design phase, we recommend that trees identified for preservation be evaluated more closely and an optimum tree protection area be determined for each tree by factoring tree species, age, tolerance to disturbance, and trunk diameter (British Standards Institute, 1991 in Harris, Clark, and Matheny, 1999). In contrast, the method used in this report was to produce a quick and general estimate of potential areas required for preservation and was based solely on trunk diameter. The sensitivity or tolerance to construction and construction related disturbance will vary depending on the factors outlined above and a certified arborist should review the construction documents for this project to ensure that any necessary tree preservation measures are included in the development of the plans and specifications for this Project.

Root removal and soil compaction are the most important factors to consider for construction in the vicinity of existing trees. Grading cut and fill within the rooting zone of a tree can cause root loss and wounding, in addition to altering the soil structure, aeration, and moisture holding capacity of the soil. Grading alterations adjacent to existing trees can also alter the hydrologic conditions affecting the tree. The amount of soil excavation and compaction vary greatly with the design of footings and foundations. Custom footings, cantilever structures, and discontinuous footings (piers) should be considered near trees that will be preserved. Trenching can cause serious root injury and should be avoided within the rooting zone of trees, or tunneling or other more sensitive methods (i.e., hydraulic or pneumatic trenching) should be considered where activities cannot be avoided near trees. Trenching, grading, and placement of impervious surfaces should be avoided within the tree preservation zones to the greatest extent feasible. Activities adjacent to the tree preservation zone (including but not limited to clearing, grading, trenching, and pruning) should be monitored by a certified arborist.

ATTACHMENT

We recommend that Project alternatives be considered that avoid construction disturbance within the tree preservation zones or explore sensitive/alternative construction methods and potential relocation, where feasible and where avoidance is not a viable alternative.

Trees to be preserved should be prominently marked to avoid injury or accidental removal during construction and tree removal activities. Any trees that require pruning should be trimmed prior to construction to avoid additional damage to the tree. Care should be taken to avoid damaging adjacent trees during any tree removals or construction. They should be cut near the ground and their stumps ground in place rather than pulled to avoid injuring roots of trees to be preserved. Vehicles and equipment should be kept away from the soil and sensitive rooting zones within the tree preservation zones. Protective fencing should be installed along the limit of the tree preservation zones to protect the integrity of the trees and to ensure that soils, low branches, and trunks are not damaged from materials and equipment moving around the site. There are a handful of locations where construction activity will be required within, or limited access will be required through, the tree preservation zones. In these locations protective fencing may be temporally relocated under the direction of a qualified biologist or arborist. Per the biologists or arborists opinion such work may need to be monitored by the Project biologist or arborist to help protect the health of the tree(s). Protective fencing should be a minimum of 4 feet in height consisting of a sturdy but open material. Fencing should be installed prior to the onset of construction, and inspections of fencing by the Project arborist may be required. No construction materials, debris, solvents, or other toxic liquids should be stored or allowed within the protective fencing. Fencing is to remain in place until all construction has been completed.

During Project construction, future planting or replanting/restoration of areas that are outside of the temporary protective fencing should have mulch applied to a depth of 4-6 inches to protect the soils from construction traffic, material storage, and equipment parking. New landscaping/restoration plantings installed within the tree preservation zone of any existing tree should be designed to replicate the environment to that which existed prior to construction. Irrigation frequency and quantity should not be significantly altered (as determined by the Project biologist or arborist) around existing trees to be preserved.

In addition to tree protection measures, attempts will be made to preserve any trees suitable for transplant into the proposed restoration area. Based on the current schematic design (MIG 2009), approximately 8-12 healthy coast live oak trees, each with a diameter of 6 in or less may be transplanted into areas of the site slated for habitat restoration.

# EVALUATION OF TREE HAZARDS AND RECOMMENDATIONS FOR TREE REMOVALS

Trees 1 and 27 are both coast live oaks that appear to have had the grade raised around their trunks. A closer inspection (root crown excavation) should be conducted to determine the preservation suitability of Tree 27. Tree 1 is less suitable for preservation and will need to be removed due to its poor condition and location in the building construction area as projected on the schematic design plan.

Trees 48 and 53 are both coast live oaks with signs of bacterial infection (bleeding cracks and cankers noted on trunk and large lateral branches). Since they are along the creek restoration

**EXECUTACION** 

- Summary of habitat impacts and proposed mitigation ratios
- Brief description of the functions and values of the regulated habitats and biological resources in the impact areas
- Quantification of regulated habitat impacts
- Map showing the habitat impact locations
- Basis for proposed mitigation ratios
- Description of the primary goals of the mitigation
- Location of mitigation and description of existing physical and biotic site conditions
- Mitigation design
  - o Existing and proposed hydrology of the site
  - o Site preparation elements
  - o Conceptual planting, irrigation, and maintenance plans
- Monitoring Plan (including monitoring schedule, final and performance criteria, monitoring methods, data analysis, and reporting requirements)
- Remedial measures/adaptive management plan for mitigation elements that do not meet performance or final success criteria.

# **Potential Impacts to Roosting Bats**

Several large oaks along the creek have numerous cavities and exfoliating bark and could provide suitable roosting habitat for the pallid bat, a California species of special concern, as well as for other non-special-status bat species. These large oaks will be left intact. The cavities in the roofs of the two large tanks remaining on the property could provide roosting habitat. The eucalyptus trees provide potential habitat for western red bats and California myotis. Even if trees being used as roosts remain intact, bat colonies could be disturbed by the noise and vibrations associated with construction, potentially resulting in roost abandonment. Abandonment of a pallid bat roost, particularly a maternity roost, could result in the mortality of adult and/or young bats. Bats disturbed during the daytime could be subject to increased predation as they attempt to find new roosts. Removal of an active pallid bat maternity roost, disturbance of an active non-breeding pallid bat roost during the daytime, or loss of a large roost of non-special-status bats would result in a significant impact under CEQA. In order to reduce potential impacts to less than significant levels, the following mitigation measures will be undertaken:

Mitigation Measure 5a (recommended but optional). If feasible, a survey for roosting bats will be conducted prior to the beginning of the breeding season (i.e., prior to 1 March) in the year in which Project activities are scheduled to occur so that adequate measures can be implemented to evict the bats during the nonbreeding season. This survey will include an assessment of all trees and structures (e.g. the 2 large wooden water tanks) on and in the vicinity of the Project for their potential use by roosting bats. Any such trees that are identified by a qualified bat biologist as being high-potential roost sites will be surveyed more intensively. The survey should be conducted by a qualified bat biologist (i.e., a biologist holding a CDFG collection permit allowing the biologist to handle and collect bats). If suitable roost sites are found but a visual survey is not adequate to determine presence or absence of bats (which would be particularly likely in the case of potential roost trees), acoustical equipment will be used to determine occupancy.

area, away from proposed high use areas indicated on the schematic design, they pose a minimal safety risk. If earthwork or other disturbing activities take place within the indicated preservation zones, the safety of these tress should be reevaluated. These trees should continue to be inspected periodically to ensure their status does not decline to a state of higher safety risk.

Trees 33 and 41 are both coast live oaks and have multiple trunks with the potential for branch failure if the trunks split apart, but both are located along the creek restoration area and not expected to pose a greater than normal hazard based on the current schematic design. While such structural flaws in tress are normal, these trees should continue to be checked periodically to ensure their structural status does not decline to a state of higher safety risk.

Trees 37, 41, and 52 are all coast live oaks with notable trunk leans. They are all located along the outward edges of the creek restoration area. Trees 37 and 41 are leaning in the direction of the proposed community garden. Tree 53 is adjacent to the location of the proposed pedestrian bridge. If preserved, these trees should be inspected periodically to ensure their structural status does not decline to a state of higher safety risk. However, under the current schematic design structural pruning or removal of Trees 31, 32, 47, and 52 may be required. The necessity to trim or remove these trees will be dependent on the placement of the bridge per the final schematic design specifications. Tree 45 is a Monterey pine with a notable lean along the creek restoration area. We recommend removal of this tree to ensure public safety.

On the current schematic design, Tree 202 is a magnolia (Magnolia grandiflora), and is located adjacent to the proposed community center building and associated pedestrian use areas. Based on the current schematic design, the grading footprint for these structures will require removal of this tree.

Trees 203 through 211, 220, and 223 are located in the area of the proposed community center building, associated parking areas, proposed play areas, and other infrastructure as shown on the current schematic design and these trees will likely be removed.

In the report by Belton (2007), he recommended the removal of numerous large eucalyptus trees on the project site, reasoning that these larger trees are competitive with the oak understory for resources such as light, water, and nutrients. He recommends the removal of large eucalyptus trees based on the premise that this removal would enhance the health survivability and reestablishment of the oak woodland. His recommendation particularly applies to Tree group 42. In addition, he states that trees 200, 201, and group 220 include eucalyptus which have weak wood and present the potential for high rates of failure. Tree 200 overhangs Soquel Drive and the gas station parking lot and building abutting the Project site. This tree is currently surrounded by paved surfaces on three sides and has a limited rooting zone. Any new changes in grade within the limited rooting zone could become hazardous. Per Belton, both trees (200 and 201) are located near high use areas and should be removed due to their potential for failure and potential risk to humans or property. These 2 trees are along the property line and may be partially located on adjacent lots. Prior to proceeding with the removal of trees 200 and 201 it is recommended that the County have the property line staked by a surveyor in this area and coordinate as needed with adjacent property owners. Tree groups 42 and 216 consist of eucalyptus trees growing in limited access areas and do not pose as great a hazard to public


ATTACHMENT


safety as the eucalyptus in higher use areas. The trees in Group 42 are currently under consideration for removal to achieve the goals of the park to restore oak woodland habitat. A large coast live oak (Tree 26) has a heavy, leaning structure and fruiting bodies of a Ganoderma heart rot fungus present at the base of the trunk near grade (Belton 2007). This tree has partially fallen over and is now supported by an adjacent blue gum eucalyptus tree in the southern end of tree group 46. At the minimum, the eucalyptus stems above the area of contact with the oak should be removed because they are vulnerable to failure as they get larger over time. The safety and practicality of retaining both this eucalyptus and this oak should be addressed as the final schematic design is developed to ensure that neither tree contributes to the potential for damage to humans or property.

Trees in groups 219-221, 223, 224, 57 and 58 are within the proposed project development footprint. Based on the current design of the Project, significant grade and surfacing changes will likely occur within the critical rooting zone of these trees and their removal will be necessary. Tree 215 (coast live oak) is in fairly good condition but has some dead wood.

Trees in group 213 have been reported to have fire blight, as well these trees may be in conflict with planned site improvements and therefore are likely to be removed. These street trees are located in the County Right of Way therefore additional coordination will be needed prior to proceeding with any removal.

As mentioned above, native oak and other desirable tree species can benefit by the careful removal of non-native vegetation that is growing in close proximity to their root collars and trunks. Of particular concern are blue gum eucalyptus stump sprouts, root suckers, and seedlings. In addition, vines growing in the canopies should also be removed.





# THE FARM PARK AND COMMUNITY CENTER NOISE STUDY REPORT SANTA CRUZ COUNTY, CALIFORNIA

October 31, 2008 Revised July 27, 2009

Prepared for:

Julie Mier David J. Powers and Associates, Inc. 1885 The Alameda, Suite 204 San Jose, CA 95126

Prepared by:

Richard B. Rodkin, PE

ILLINGWORTH & RODKIN, INC. Acoustics · Air Quality 505 Petaluma Boulevard South Petaluma, CA 94952 (707) 766-7700

Job No.: 08-140

conditions by 15 to 20 dBA. The hourly average noise level (Leq) depends upon the amplitude of the noise and the duration of time the noise persists. In a smaller dog park, there would typically be fewer dogs present resulting in less time dogs would be barking. It was assumed that 5 to 6 dogs continuously present at the park for an hour would represent a credible worst case. At the nearest adjacent residence, worst-case hourly average noise levels are calculated to range from 50 to 55 dBA Leq. Average noise levels generated by the dog park would exceed existing average noise levels by up to 8 dBA Leq.


Distant Receivers. Residents in the Fairway Drive neighborhood located about 4800 feet north of the project site expressed concern regarding sound propagation from the park into their neighborhood. A sensitivity analysis was conducted to determine whether or not noise levels from the park activities could affect these residences. To complete this analysis, noise from all the activities were summed together and set to a reference distance of 50 feet. In the Fairway Drive neighborhood to the north, the noise level resulting exclusively from park activities is calculated to be 17 dBA Leq, more than 20 dBA below existing ambient noise levels. The highest intermittent noise levels generated at the park would result from groups of children. Maximum intermittent noise levels are calculated to be less than 25 dBA Lmax, more than 10 dBA below existing background noise levels. These sources would be inaudible, causing no impact upon the residents.

# Mitigation:

The following mitigation measures shall be incorporated into the design of the project to reduce potential noise impacts to less than significant levels:

Construct six- to eight-foot solid wood fences at the residential property lines west and north of the park site. A six-foot wood fence would be sufficient along the west property line of the park south of Tee Street. An eight-foot fence would be necessary along the west property line north of Tee Street and along the north property line of the park to reduce maximum noise levels generated in the neighborhood play area. The neighbor has requested a portion of this barrier be reduced to three to four feet and entered an agreement with the County stipulating that noise from the park would not disturb them.

To be an effective noise barrier, the proposed fences must be constructed solidly over the face and at the base of the barrier. Openings or gaps between barrier materials or the ground substantially decrease the effectiveness of a noise barrier. Suitable materials for barrier construction should have a minimum surface weight of 3 lbs./ft.2 (such as oneinch thick wood). The proposed barriers should be located as shown on Figure 4. With the proposed barriers, sounds would occasionally be heard at the nearest residential land uses, but noise levels would not substantially exceed existing levels.



Impact 3: Off-Site Traffic Noise Increases. Project traffic would not substantially increase traffic noise levels along area roadways. This is a less-than-significant impact.

Traffic generated by the project would not cause noise levels to substantially increase on the roadways serving the site. Future traffic noise level projections indicate that traffic noise levels in the project vicinity would increase by 0 dBA L<sub>dn</sub> (less than 0.5 dBA L<sub>dn</sub>) along Soquel Drive and Cunnison Lane. Noise levels along local roadways may increase slightly as a result of occasional intermittent project traffic. The relatively low traffic volumes associated with the project would result in a less-than-significant noise impact.

Impact 4: Construction Noise. The project site is bordered by existing residential land uses to the west, east, and north, and across Soquel Drive to the south. Noise generated by construction activities at the site would not be expected to adversely affect adjacent land uses provided standard construction noise controls are implemented at the site and the cumulative duration of significant noise-producing activities is limited to one year or less. This is a less-than-significant impact with the incorporation of standard construction noise controls.

Construction activities generate considerable amounts of noise. Construction-related noise levels are normally highest during the demolition phase and during the construction of project infrastructure. These phases of construction require heavy equipment that normally generates the highest noise levels over extended periods of time. Typical hourly average construction generated noise levels are about 81 to 88 dBA L<sub>eq</sub> measured at a distance of 50 feet from the center of the site during busy construction periods (e.g., earth moving equipment, impact tools, etc.). Construction-related noise levels are normally less during building erection, finishing, and landscaping phases. There would be variations in construction noise levels on a day-to-day basis depending on the actual activities occurring at the site. Construction generated noise levels drop off at a rate of about 6 dBA per doubling of distance between the source and receptor.

Noise impacts resulting from construction depend on the noise generated by various pieces of construction equipment, the timing and duration of noise generating activities, and the distance between construction noise sources and noise sensitive receptors. Construction noise impacts primarily occur when construction activities occur during noise-sensitive times of the day (early morning, evening, or nighttime hours), the construction occurs in areas immediately adjoining noise sensitive land uses, or when construction durations last over extended periods of time. Where noise from construction activities exceeds 60 dBA L<sub>eq</sub> and exceeds the ambient noise environment by at least 5 dBA L<sub>eq</sub> at noise-sensitive uses in the project vicinity for a period greater than one year, the impact would be considered significant.

Exterior noise levels at the nearest residential receivers would be approximately 73 to 81 dBA  $L_{eq(hr)}$  when construction occurs at the play/ sports area. Grading, roadway improvements and construction of project infrastructure would likely be completed first. The total construction duration would not last for more than 12 months. Noise generated by grading, infrastructure improvements and the construction of the project nearest the perimeter of the project site would not exceed ambient noise levels at receivers to the northeast by more than 5 dBA  $L_{eq}$  for a period of greater than one year.

Significant noise impacts do not normally occur when standard construction noise control measures are enforced at the project site and when the duration of the noise generating construction period at a particular receiver or group of receivers is limited to one construction season (typically one year) or less. Construction noises associated with projects of this type are disturbances that are necessary for the construction or repair of buildings and structures in urban areas. Reasonable regulation of the hours of construction, as well as regulation of the arrival and operation of heavy equipment and the delivery of construction material, are necessary to protect the health and safety of persons, promote the general welfare of the community, and maintain the quality of life.


The following standard controls are assumed to be included in the project:

- Noise-generating activities at the construction site or in areas adjacent to the construction site associated with the project in any way should be restricted to the hours of 8:00 a.m. to 6:00 p.m., Monday through Friday. No construction activities should occur on weekends or holidays.
- Equip all internal combustion engine driven equipment with intake and exhaust mufflers that are in good condition and appropriate for the equipment.
- Locate stationary noise generating equipment as far as possible from sensitive receptors when sensitive receptors adjoin or are near a construction project area.
- Utilize "quiet" air compressors and other stationary noise sources where technology exists.
- The contractor shall prepare a detailed construction plan identifying the schedule for major noise-generating construction activities. The construction plan shall identify a procedure for coordination with the adjacent noise sensitive facilities so that construction activities can be scheduled to minimize noise disturbances.
- Designate a "disturbance coordinator" who would be responsible for responding to any local complaints about construction noise. The disturbance coordinator will determine the cause of the noise complaint (e.g., starting to early, bad muffler, etc.) and will require that reasonable measures warranted to correct the problem be implemented. Conspicuously post a telephone number for the disturbance coordinator at the construction site and include it in the notice sent to neighbors regarding the construction schedule.

With the incorporation of these standard measures, the noise impact resulting from project construction would be considered less-than-significant. No additional measures are required.

Draft Transportation Impact Analysis

# The Farm: Park and Community Center





160 W. Santa Clara St., Ste. 675 San Jose, CA 95113

SJ08-1045

February 12, 2010

# **EXECUTIVE SUMMARY**

This report presents the results of the transportation impact analysis (TIA) for the proposed Farm Park and Community Center located in Soquel, Santa Cruz County, California. The project includes 2.7-acres of active parklands and a community center building with two classrooms and meeting room. About 2.8 acres of the site is a protected riparian corridor that is not actively used and would not generate any additional traffic.

The purpose of the TIA is to identify potential significant adverse impacts of the proposed project on the surrounding transportation system and to recommend mitigation measures, if needed. Project impacts were evaluated following the guidelines of the Santa Cruz County.

#### PROJECT TRIP ESTIMATES

Trip generation estimates for the community center and park were estimated based on a preliminary building space program and trip generation observations at local parks. The proposed park and community center is estimated to generate 94 new PM peak-hour trips on a typical day – when the community center is occupied and the outdoor areas are in use. Project trip generation was estimated for the evening (PM) peak hour since this is expected to be the busiest period at the park, based on the preliminary activity schedule. Substantially fewer trips are expected during the AM peak; therefore, the AM peak hour was not analyzed. The park may generate more trips on weekends; however, roadway volumes during the weekend are typically lower than weekday commute conditions, so the evening peak period analysis represents peak travel conditions.

#### INTERSECTION IMPACTS

Based on impact criteria defined by Santa Cruz County, the project is expected to have a *less-than-significant* project-level and cumulative-level impact at the three study intersections – Soquel Drive/Porter Street, Soquel Drive/Cunnison Lane, and Soquel Drive/Park Avenue – during the PM peak hour.

## **BICYCLE, PEDESTRIAN, AND TRANSIT IMPACTS**

The park and community center is anticipated to increase bike, pedestrian, and transit usage; however, the project will not impact existing or planned facilities or transit service. The site is served by bicycle lanes on Soquel Drive and sidewalks on Soquel Drive and Cunnison Lane. The bicycle lanes and the sidewalks near the project site can reasonably accommodate additional demand. The existing transit service can reasonably accommodate the anticipated demand. Thus, the proposed park and community center will have a *less-than-significant* impact on the existing pedestrian, bicycle, and transit network.

#### **PARKING**

Adequate project parking will be provided for outdoor recreation areas on the site. The Parks Department will monitor scheduling of the community center with the CLASS site reservation system to ensure that the demands of the community center rooms do not exceed the total parking supply on the site. The CLASS system has the ability to cap the number of people that can reserve and use particular rooms in the community center. Parking demand is related to the number of visitors to the site, so this type of reservation system and monitoring will be effective in managing parking demand. Therefore, based on the Parks' Department's programming of the building uses, and use of the CLASS system, described in the Parks Department's Programming Statement (Appendix D), the proposed park and community center will be able to provide sufficient parking for all of its on-site uses. **Table E-1** summarizes projected parking demand at the site under different scenarios that the Parks Department has proposed for the site.

ATTACHMENT



# TABLE E-1 FARM PARK AND COMMUNITY CENTER PARKING DEMAND ESTIMATES

	Number of Vehicle Parking Spaces					
\ <u> </u>	Weekday Scenarios			Weekend Scenarios		
Site Use	А	В	С	D	Ε	
Outdoor Recreation	13	13	13	21	21	
Classroom 1 (18 students + 1 instructor)	14	14	-	14	<u>-</u>	
Classroom 2 (12 students + 1 instructor)	9	9	-	9	9	
Assembly Room (18 per. Meeting) <sup>2</sup>	<u>-</u>	-	- -	14	-	
Assembly Room (26 per. Reception) <sup>2</sup>	20	-	-	-	20	
Assembly Room (31 per. Class)	<del>-</del>	22	-	-		
Assembly Room (56 per. Reception)			39	-	-	
Total Demand	56	58	52	58	48	
Total Supply	58	58	58	58	58	

## Notes:

- 1 Based on information developed in Tables 15 and 16.
- 2 Parking demand estimates developed using the mode split presented in Table 15.

Fehr & Peers; October, 2008.

# COUNTY OF SANTA CRUZ DISCRETIONARY APPLICATION COMMENTS

Project Planner: Sheila Mcdaniel

Application No.: 09-0407

**APN:** 037-101-58

Date: November 15, 2010

Time: 09:48:00

Page: 1

## Environmental Planning Completeness Comments

====== REVIEW ON JANUARY 8, 2010 BY CAROLYN I BANTI =======

++ Completeness ++ Soils and Grading ++ First Review ++

- 1. The soils report references the "Farm Community Park Entire Stream Evaluation and Analysis", by H.T. Harvey and Balance Hydrologics, which has not been submitted for review. The soils report cannot be reviewed until all technical reports have been submitted for review. Please submit the missing report.
- 2. Project grading volumes are in excess of 2000 cubic yards. Per County Code Section 16.20.060, the project will require grading plans prepared and signed by a civil engineer. Please prepare and submit these for review.
- 3. It was noted during preliminary review of the submitted plans that creek restoration plans include re-grading of the slope above the channel, the extent and grade of which are labeled to be determined on Sheet L-6.2. This grading must be determined and shown on the grading plans in order to complete preliminary grading review.
- 4. After plans have been prepared that are acceptable to all reviewing agencies, please submit a geotechnical plan review letter from the soils engineer that states the project plans are in conformance with the recommendations of the soils report. The plan review letter must reference the grading, drainage and erosion control plan sheets in addition to all other pertinent plan sheets.

Please note: Additional items may follow, pending review of the materials submitted in response to first review comments. ======= UPDATED ON JANUARY 8, 2010 BY ROBERT S LOVELAND =========

1. The grading plan (Sheet L-1.0) shows grading activity being completed within the "Building Setback" (Tee Street Area). Please revise to locate all grading activity outside this area. ======== UPDATED ON OCTOBER 27, 2010 BY ROBERT S LOVELAND

Comment below by: Carolyn Banti

As requested in first review comments, please submit the Farm Community Park Entire Stream Evaluation and Analysis, by H.T. Harvey and Balance Hydrologics for review. As previously noted, the soils report cannot be formally reviewed until all technical reports have been submitted for review.

Comment below by: Bob Loveland

Comment 1 above: Has been addressed.

# **Environmental Planning Miscellaneous Comments**

====== REVIEW ON JANUARY 8, 2010 BY CAROLYN I BANTI =======

Project Planner: Sheila Mcdaniel

Application No.: 09-0407

**APN**: 037-101-58

Date: November 15, 2010

Time: 09:48:00

Page: 2

++ Compliance Comments ++ Soils and Grading ++ First Review ++

1. It appears that project grading volumes and site disturbance may be minimized by utilizing alternate site design approaches that would not require major grading, as required by County Code Section 16.20.010, General Plan Objectives and GP Policy Sections 6.3.9 and 8.2.2. Please contact Carolyn Banti at (831) 454-5121 to arrange a meeting to discuss the current design methodology and possible alternatives to minimize grading.

Please note: Additional items may follow, pending review of the materials submitted in response to first review comments.

- ++ Conditions of Approval ++ Soils and Grading ++ First Review ++
- 1. A preconstruction meeting will be held prior to the commencement of grading operations, and another before to the commencement of in-stream work. Required attendees will be determined prior to the meeting. Please contact Carolyn Banti at (831) 454-5121 to schedule the meeting.
- 2. Please submit two copies of the soils report at the time of building permit application. The soils report must be updated since it is more than 3 years old, and must include updated seismic design parameters to reflect those required by the most current version of the building code.
- 3. Erosion control plans to be submitted for this project must be approved by a Certified Professional in Erosion and Sediment Control (CPESC), and must include the following: (a) construction schedule detailing construction/earthwork tasks and durations, (b) phased erosion control plan showing the location and types of erosion control measures to be implemented during each phase of construction/earthwork operations, (c) temporary drainage plans for each phase of construction/earthwork operations including detailed plans of all surface and subsurface drainage devices, runoff calculations and other calculations demonstrating the adequacy of drainage structures, (d) CPESC inspection schedule for certification of proper installation and maintenance of erosion control measures.
- 4. Winter grading will not be approved for this project. Grading must commence by June 1 or delayed until the following year such that grading operations will cease by October 15.
- 5. Submit civil engineered grading/drainage plans with the building permit application.

Please Note: The conditions of approval are preliminary and may be modified when above completeness and compliance comments have been addressed. ======= UPDATED ON NOVEMBER 5, 2010 BY CAROLYN I BANTI ========

6. The hydrology report by Mesiti Miller has been received by environmental planning, but has not been formally accepted. To our knowledge, no other hydrology report exists for the project area. The Mesiti Miller report did not include an analysis of scour in the vicinity of the bridge abutments, which must be included in the updated soils report submitted with the building and grading permit application.

Project Planner: Sheila Mcdaniel

Application No.: 09-0407

**APN:** 037 - 101 - 58

Date: November 15, 2010

Time: 09:48:00

Page: 3

## Dpw Drainage Completeness Comments

LATEST COMMENTS HAVE NOT YET BEEN SENT TO PLANNER FOR THIS AGENCY

====== REVIEW ON JANUARY 11, 2010 BY ALYSON B TOM ===== Application with plans dated 10/31/09, on site analysis dated 8/4/09 and off site analysis dated 7/11/09 has been received. The following items should be addressed in a complete application.

Please contact Alyson Tom of the Stormwater Management Division to set up a meeting to review stormwater design solutions potential for this project. ===== UPDATED ON OCTOBER 19, 2010 BY ALYSON B TOM ====== Application with civil plans dated 9/15/10 has been received. Please see previous miscellaneous comments for issues to be addressed prior to building permit approval.

# Dpw Drainage Miscellaneous Comments

LATEST COMMENTS HAVE NOT YET BEEN SENT TO PLANNER FOR THIS AGENCY

====== REVIEW ON JANUARY 11, 2010 BY ALYSON B TOM ====== Please address the following prior to map recordation/building permit issuance:

- 1) Provide final details and analysis for the retention and detention systems. The evaluation of the detention and retention systems orifice and bypass design should be consistent with the areas, impervious and pervious, that are proposed to drain to the facilities.
- 2) The drainage report includes a recommendation for perforated pipes with gravel trench. This concept should be included in the final design for the main pipe and/or bypass pipe sections to include open bottomed or perforated pipes. Low flows will bypass the detention pipe sections and so a perforated detention pipe will be of little benefit.
- 3) Provide final details and analysis for the proposed bio swales. Include specifications for soil and vegetative design.
- 4) The drainage report indicates that the Tee Street stormwater mitigations will be met with a landscape solution including a rain garden with underground gravel storage however the plans show a buried detention pipe. Please update the plans to correspond with the landscape solution described in the report. This report also indicates specific maintenance requirements for the system. These requirements should be included in both the final plans and recorded maintenance agreement. Can the outlet location for the system be moved to the flat area near the riparian buffer/corridor limits? This would provide for additional filtering prior to discharge to the channel.
- 5) While the December 2008 Geotechnical Report indicates areas of low permeability soils on the project site the report also suggests that permeable pavement is acceptable with the inclusion of a rock underdrain and geotextile. Permeable pavements should be considered for the final design.

**Project Planner:** Sheila Mcdaniel

Application No.: 09-0407

**APN:** 037-101-58

Date: November 15, 2010

Time: 09:48:00

Page: 4

6) The off site analysis provided was for the pre and post development 25 year storm scenarios. Please provide an analysis for the post development 10 year storm as well as many of the CDC requirements are for the 10 year storm. Please also include a gutter analysis for the sections where there is overflow out of the pipe system demonstrating a safe traffic situation.

- 7) The designer should consider future maintenance requirements, as well as safe overflow conditions when designing stormwater mitigations and should include these on the final project plans and recorded maintenance agreements.
- 8) Please submit a review letter from the Geotechnical engineer approving of the stormwater management/drainage plan. The letter should refer to dated plans.
- 9) Please provide permanent markings at each inlet that read: "NO DUMPING DRAINS TO BAY. NO TIRE DESECHO AL MAR", or equivalent. The property owner is responsible for maintaining these markings.
- 10) If structural water quality treatment, detention, or retention is proposed, recorded maintenance agreement(s) are required. A sample agreement which can be updated for use on this project is provided in the County Design Criteria. This agreement should be signed, notorized, and recorded, and a copy of the recorded agreement should be submitted to the County Department of Public Works prior to building permit submittal.
- 11) Submit detailed plans and supporting calculations demonstrating that the on-site storm water system meets design criteria requirements (capacity, safe overflow, freeboard, velocity, etc.). Include analysis for gutter spread for the required design and safe overflow storm events where applicable. Describe how runoff will be controlled at the top of slopes, particularly at the slope above Soquel Drive. Provide a drainage detail for proposed pathways - runoff should sheet flow off so it is not directly connected off site.
- 12) Coordinate drainage plans with other site plans including grading and landscaping (ex: should trees be planted above the proposed detention pipe?).
- 13) This project will be inspected by DPW staff. Once all other reviewing agencies have approved the project provide a copy of the reproducible civil plan sheets with the DPW signature block along with an engineer-s estimate for the drainage related items and a 2% (\$610 minimum) deposit for inspection fees. Allow approximately 1-2 weeks for review and signature of the reproducible plans.
- 14) Please submit a review letter from the Geotechnical engineer approving of the final stormwater management/drainage plan. The letter should refer to dated plans.
- 15) Construction activity resulting in a land disturbance of one acre or more, or less than one acre but part of a larger common plan of development or sale must obtain the Construction Activities Storm Water General NPDES Permit from the State Water Resources Control Board. Construction activity includes clearing, grading, excavation, stockpiling, and reconstruction of existing facilities involving removal and replacement. For more information see: http://www.waterboards.ca.gov/waterissues/programs/stormwater/constructionml

Project Planner: Sheila Mcdaniel

Application No.: 09-0407

**APN:** 037-101-58

Date: November 15, 2010

Time: 09:48:00

Page: 5

# Dpw Driveway/Encroachment Completeness Comments

# Dpw Driveway/Encroachment Miscellaneous Comments

======= REVIEW ON DECEMBER 22, 2009 BY DAVID GARIBOTTI ======= Driveways to conform to County Design Criteria Standards. Encroachment permit required for all offsite work in the County road right-of-way. Civil engineered plans required for curb, gutter and sidewalk. ======== UPDATED ON OCTOBER 21, 2010 BY DAVID GARIBOTTI ======== Please bubble any future revisions.

# Dpw Road Engineering Completeness Comments

====== REVIEW ON JANUARY 12. 2010 BY RODOLFO N RIVAS ======= Applicant will need to address the following comments:

Transportation Impact Analysis prepared by Fehr & Peers dated September 30, 2009:

1) Include traffic signal warrant analysis for Cunnison Lane/Soquel Drive intersection. 2) Include calculations regarding project effect on v/c ratio (critical) at intersections. 3) Synchro traffic volumes used for LOS calculations; have discrepancies with traffic volumes from figures showing peak-hour volumes.

# Improvements Plan:

====== UPDATED ON OCTOBER 18, 2010 BY RODOLFO N RIVAS =======

Project Planner: Sheila Mcdaniel

Application No.: 09-0407

**APN:** 037-101-58

Date: November 15, 2010

Time: 09:48:00

Page: 6

====== UPDATED ON OCTOBER 18, 2010 BY RODOLFO N RIVAS =======

# Dpw Road Engineering Miscellaneous Comments

# **Dpw Sanitation Completeness Comments**

Environmental Compliance Unit Review Comments Farm Neighborhood Park and Community Center Application No. 09-0407 1st Review Summary Statement: The County of Santa Cruz Environmental Compliance Unit can not approve plan this time. Please see completeness, policy compliance, and information it listed below. Completeness Items: Plans received illustrate a ceramics studio. Due to the sediment load from ceramics process, the District is requiring the facility to install pretre nt on the sinks used to drain wastewater generated from washing/molding of clay. Plans must indicate the size of the sediment trap prior to approval he Sanitation District. Please submit plans with the trap specifications an lustrate the plumbing lines and fixtures connected to the sediment trap. Policy Compliance Items: All plans for the ceramics studio must illustrate fixtures, trap size and d n before they can be approved by the Sanitation District. Information Items: Ceramics Studio: 1. Due to the sediment load from the ceramics process, the District is requiri he facility to install pretreatment on the sinks used to drain wastewater f washing/molding of the clay. 2. Glazes cannot be discharged to the sewer. 3. Oil based paints cannot be discharged to the sewer. Working water containing clay should be collected in a bucket and the clay 1d be allowed to settle out. Decant the water and dispose of solids in the h. Equipment should also be rinsed in this bucket before rinsing in the sin 4. Screens must be used in each sink to remove solids. Any questions regarding these criteria or to schedule an inspection should irected to the Santa Cruz County Sanitation District Environmental Complian nit at (831) 477-3907 All re-submittals shall be made through the Planning Department. Materials t with Public Works will not be processed or returned. See Miscellaneous comments. Engineering Division Review Comments No. 1 Review Summary Statement; Appl. No. 09-040 ; APN: 37-101-58 & -59: Sewer service is available for this project provided that the following com eness issues are addressed. The Proposal is out of compliance with Distric County sanitation policies and the County Design Criteria (CDC) Part 4, Sa ry Sewer Design, June 2006 edition. and also lacks sufficient information f omplete evaluation. The District/County Sanitation Engineering and Environ al Compliance sections cannot recommend approval of the project as proposed This review notice is effective for one year from the issuance date to allo e applicant the time to receive tentative map, development or other discret ry permit approval. If after this time frame this project has not received roval from the Planning Department, a new availability letter must be obtain by the applicant. Once a tentative map is approved this letter shall apply il the tentative map approval expires. Reference for County Design Criteria: http://www.dpw.co.santa-cruz.ca.us/DESIGNCRITERIA.PDF Completeness Items: A complete engineered sewer plan, addressing all issues required by Distric aff and meeting County -Design Criteria- standards (unless a variance is al lowed), is required. District approval of the proposed discretionary perm s withheld until the plan meets all requirements. The following items need be shown on the plans: Show proposed

Project Planner: Sheila Mcdaniel

Application No.: 09-0407

**APN:** 037-101-58

Date: November 15, 2010

Time: 09:48:00

Page: 7

sewer lateral length, pipe material, and slope noted (minimum . Drinking fountains and trash container floor drain shall be located under c or shall not be connected to sewer. Floor drain area shall be sloped or b d so that surface water does not enter sewer system. Provide elevations for top and bottom of pipes where utilities and sewer ma ateral crossings occur. Where less than 1 feet of vertical separation occu a concrete/rebar saddle shall be included in details. Include District-s -General Notes- on plans. Contact staff for electronic . The laterals serving the bathrooms and community center shall have a sewer flow or backflow prevention device installed on them per Fig. SS-14 of the gn Criteria. The proposed buildings (bathroom and community center) shall include the in lation of a water sub-meter per District policy to determine quantity of do ic and interior water for the purpose of calculating annual sewer service c harges. The use of the sub-meter shall be a requirement and condition of a val for this permit application and shall be included with the Planning Dep ent-s permit conditions. A note to this effect shall be included on plans. Sheet C-2.0 indicates sewer lateral for park is connected to adjacent prope s lateral. Contact District staff for copy of inspection record (lateral f ark site enters directly into manhole). Any questions regarding the above criteria should be directed to Diane Rome the Sanitation Engineering division at (831) 454-2160. There are no Sanitation engineering miscellaneous comments. ====== UPDATED ON FEBRUARY 2, 2010 BY DĬANE ROMĚO ====== Please add note to plan sheet that "New lateral shall be allowed only in the event that the existing manhole is not currently connected to the manhole and shall be verified in the field prior to modifiying manhole for new connection. The new lateral connection shall be made per SS-7 of Design Criteria and in- side and outside shall be water proofed by application of "Thoroseal" or approved equal if inflow or infiltration is anticipated. Existing connection at hamhole that is to be abandoned shall be completely repaired on inside and outside of manhole." Please show manhole and lateral elevations reflecting matching fop of pipe requirement.
----- UPDATED ON OCTOBER 15, 2010 BY DIANE ROMEO ----- Engineering Division Review Comments No. 2 Review Summary Statement; Appl. No. 09-040; APN: 37-101-58 & -59: Sewer service is available for this project provided that the following completeness issues are addressed. The Proposal is out of compliance with District or County sanitation policies and the County Design Criteria (CDC) Part 4, Sanitary Sewer Design, June 2006 edition, and also lacks sufficient information for complete evaluation. The District/County Sanitation Engineering and Environmental Compliance sections cannot recommend approval of the project as proposed. This review notice is effective for one year from the issuance date to allow the applicant the time to receive tentative map, development or other discretionary permit approval. If after this time frame this project has not received approval from the Planning Department, a new availability letter must be obtained by the applicant. Once a tentative map is approved this letter shall apply until the tentative map approval expires. Reference for County Design Criteria: http://www.dpw.co.santa-cruz.ca.us/DESIGNCRITERIA.PDF Completeness Items: A complete engineered sewer plan, addressing all issues required by District staff and meeting County -Design Criteria- standards (unless a variance is allowed), is required. District approval of the proposed discretionary permit is withheld until the plan meets all requirements. The plans will be approved by the District when the following items are shown on the plans: Sheet C-2.0 shall be revised to have 4- lateral connection removed from sewer manhole and relocated to sewer main. The 4- lateral from the trash enclosure shall be connected on-site to the lateral for the community building. The Sanitation District Environmental Review

division must be allowed to review plans for the sediment trap(s) prior to issuance

Project Planner: Sheila Mcdaniel

Application No.: 09-0407

**APN:** 037-101-58

Date: November 15, 2010

Time: 09:48:00

Page: 8

of a permit and to inspect the installation. Any questions regarding the above criteria should be directed to Diane Romeo of the Sanitation Engineering division at (831) 454-2160. There are no Sanitation engineering miscellaneous comments.

# Dpw Sanitation Miscellaneous Comments

The Sanitation District Environmental Review division must be allowed to re plans for the sediment trap(s) prior to issuance of a permit and to inspec e installation. There are no Sanitation Engineering miscellaneous comments.



**Board of Directors** 

Dr. Thomas R. LaHue, *President*Bruce Daniels, *Vice President*Dr. Don Hoernschemeyer
Dr. Bruce Jaffe
Daniel F. Kriege

Laura D. Brown, General Manager

September 28, 2010

Ms. Sheryl Bailey County of Santa Cruz Redevelopment Agency 701 Ocean Street, Room 510 Santa Cruz, CA 95060

SUBJECT: Renewal of Conditional Water Service Application for The Farm, Soquel APNs 037-101-58 & 59

Dear Ms. Bailey:

In response to the subject application, the Board of Directors of the Soquel Creek Water District at their regular meeting of September 7, 2010 voted to grant you a Renewal of a Conditional Will Serve Letter for The Farm Neighborhood Park and Community Center project in Soquel so that you may proceed through the appropriate planning entity. An Unconditional Will Serve Letter cannot be granted until such time as you are granted a Final Discretionary Permit on your project. At that time, an Unconditional Will Serve Letter will be granted subject to your meeting the requirements of the District's Water Demand Offset Program and any additional conservation requirements of the District prior to obtaining the actual connection to the District facilities subject to the provisions set forth below.

Possible Infrastructure Check List	yes	no
1. LAFCO Annexation required		$\times$
2. Water Main Extension required off-site		X
3. On-site water system required		×
4. New water storage tank required		×
5. Booster Pump Station required		×
6. Adequate pressure	×	
7. Adequate flow	X	
8. Frontage on a water main	×	
9. Other requirements that may be added as a result of policy changes.	×	

RECEIVED

OCT 0 1 2010

REDEVELOPMENT
AGENCY

This present indication to serve is valid for a two-year period from the date of this letter; however, it should not be taken as a guarantee that service will be available to the project in the future or that additional conditions, not otherwise listed in this letter, will not be imposed by the District prior to granting water service. Instead, this present indication to serve is intended to acknowledge the

conditions, water service would be available on condition that the developer agrees to provide the following items without cost to the District:

- 1) Destroys any wells on the property in accordance with State Bulletin No. 74;
- 2) Satisfies all conditions imposed by the District to assure necessary water pressure, flow and quality;
- 3) Satisfies all conditions of Resolution No. 03-31 Establishing a Water Demand Offset Policy for New Development, which states that all applicants for new water service shall be required to offset expected water use of their respective development by a 1.2 to 1 ratio by retrofitting existing developed property within the Soquel Creek Water District service area so that any new development has a "zero impact" on the District's groundwater supply. The required offset amount shall be as determined by the District, and credits may be purchased from the District when the project has received approval from the land use agency;
- 4) Satisfies all conditions for water conservation required by the District under the current water use efficiency ordinances as set forth in the enclosures to this letter;
- 5) Completes LAFCO annexation requirements, if applicable;
- 6) All units shall be individually metered with a minimum size of 5/8-inch by ¾-inch standard domestic water meters;
- 7) A memorandum of the terms of this letter shall be recorded with the County Recorder of the County of Santa Cruz to insure that any future property owners are notified of the conditions set forth herein.

Future conditions which negatively affect the District's ability to serve the proposed development include, but are not limited to, a determination by the District that existing and anticipated water supplies are insufficient to continue adequate and reliable service to existing customers while extending new service to your development. In that case, service may be denied.

You are hereby put on notice that the Board of Directors of the Soquel Creek Water District may adopt additional policies to mitigate the impact of new development on the local groundwater basins, which are currently the District's only source of supply. Such actions are being considered because of concerns about existing conditions that threaten the groundwater basins and the lack of a supplemental supply source that would restore and maintain healthy aquifers. The Board may adopt additional mandatory mitigation measures to further address the impact of development on existing water supplies, such as the impact of impervious construction on groundwater recharge. Possible new conditions of service that may be considered include designing and installing facilities or fixtures on-site or at a specified location as prescribed and approved by the District which would restore

Conditional Water Service Application – APNs 037-101-58 & 59 Page 3 of 3

groundwater recharge potential as determined by the District. The proposed project would be subject to this and any other conditions of service that the District may adopt prior to granting water service. As policies are developed, the information will be made available at the District Office.

Sincerely,

SOQUEL CREEK WATER DISTRICT

Michael Wilson, P.E.

Acting Engineering Manager

# **Enclosures**:

- 1. Overview of the Soquel Creek Water District's Water Use Efficiency Requirements for Public Development
- 2. Indoor Water Use Efficiency Checklist
- 3. Landscape Project Application Submittal Requirements Package for Public Development

# SANTA CRUZ COUNTY SANITATION DISTRICT

INTER-OFFICE CORRESPONDENCE

DATE:

August 16, 2010

TO:

Santa Cruz County Redevelopment Agency, ATTENTION: SHERYL BAILEY

FROM:

Santa Cruz County Sanitation District

SUBJECT:

SEWER AVAILABILITY AND DISTRICT'S CONDITIONS OF SERVICE

FOR THE FOLLOWING PROPOSED DEVELOPMENT

APN:

37-101-58 & -59

APPLICATION NO.:

Pre-application

PARCEL ADDRESS:

Northwest Corner Cunnison Lane & Soquel Drive

PROJECT DESCRIPTION:

Construct Community Center and Neighborhood Park

This review notice is effective for one year from the issuance date to allow the applicant the time to receive tentative map, development or other discretionary permit approval. If after this time frame this project has not received approval from the Planning Department, a new availability letter must be obtained by the applicant. Once a tentative map is approved this letter shall apply until the tentative map approval expires.

•Item 1) A complete engineered sewer plan, addressing all issues required by District staff and meeting County "Design Criteria" standards (unless a variance is allowed), is required. District approval of the proposed discretionary permit is withheld until the plan meets all requirements. The following items need to be shown on the plans:

Show proposed sewer laterals (including length of pipe, pipe material, cleanouts located maximum of 100-feet apart along with ground and invert elevations) and slope noted (minimum 2%) and connection to the existing public sewer.

Water use data (actual or projected), and other information as may be required for this project, must be submitted to the District for review and use in capacity and waste pretreatment requirements <u>before</u> this discretionary permit application can be approved.

The proposed buildings shall include the installation of a water sub-meter per District policy to determine quantity of domestic and interior water for the purpose of calculating annual sewer service charges. The use of the sub-meter shall be a requirement and condition of approval for this permit application and shall be included with the Planning Department's permit conditions.

Attach an approved (signed by the Sanitation and Drainage District) copy of the sewer system plan to the building permit submittal. A condition of the development permit shall be that Public Works has approved and signed the civil drawings for the land division improvement prior to submission for building permits. Failure to get approvals for improvement plans will delay issuance of building permit.

Any questions regarding the above criteria should be directed to Diane Romeo of the Sanitation Engineering division at (831) 454-2160.

•Item 2) Santa Cruz County Sanitation District Environmental Compliance Division Requirements for parks/community recreation centers include:

If a recreation room is intended with a kitchen, then you must submit a set of plans to be reviewed by the Environmental Compliance Division.

- A minimum of a 70-pound interior grease trap is required if a community kitchen is intended. Prior to approval of plans, the District must be allowed to review any proposed plans for grease interceptors. Plans must illustrate the size and location of the grease interceptor prior to approval.
- A dishwasher is not permitted unless an exterior 350-lb. minimum exterior grease interceptor is installed.
- All sinks and floor drains must be routed through a grease interceptor with the exception of hand washing sinks and bathroom drains.
- Floor drains must be installed with screens that prevent solids from blocking the facility's pipes and from entering the sanitary sewer.
- Garbage grinders are strictly prohibited in commercial/industrial kitchens.
- All grease interceptors will meet the Santa Cruz County Design Criteria
- If connecting to an existing interceptor, the District must be allowed to inspect and verify
  that it is in proper working condition and is properly sized for the facility. Upon approval
  by the District, the new facility will be allowed to connect to the existing interceptor.

# Requirements for vehicle washing and/or carwash fundraising events:

All car washing activities are strictly prohibited unless there is proper pretreatment of the wastewater.

If the community center plans to wash fleet vehicles or hold carwash fundraisers on their
property then, the wastewater generated by car wash activities must be collected and
treated before being discharged to the sanitary sewer. All car washing activities must be
conducted in a District-approved wash pad area. The wash pad area must be sloped and

## RDA PAGE 3

bermed to prevent discharge to the storm drain and to prevent excess storm water from running to the pad area drain.

• The wastewater must be treated through a minimum 1500-gallon clarifier as specified in the Santa Cruz County design Criteria. In addition, the clarifier must be completely pumped out at least once a year or as often as deemed necessary by the District.

The Sanitation District must be allowed to review plans for the grease interceptor(s) and clarifier and to inspect the installation. Any questions regarding these criteria should be directed to the Santa Cruz County Sanitation District Environmental Compliance Unit (831) 477-3907.

- Prachel Yather

Rachél Lather Sanitation Engineer

DR/dls:135

c: Engineer:

Rodney Cahill

Misiti Miller Engineers 224 Walnut Street, Suite B Santa Cruz, CA 95060

(REV. 3-01)

## PROGRAM STATEMENT - FARM PARK

#### Introduction

The Mission Statement of the Santa Cruz County Department of Parks, Open Space & Cultural Services is to provide safe, well-designed and maintained parks and a wide variety of recreational and cultural opportunities for our diverse community.

Background

Currently, the department provides a variety of active and passive outdoor recreational opportunities including hiking trails, open space, beach access points, basketball and tennis courts, swimming and other aquatic programs (e.g. water polo), skate parks, rentable sports fields, community garden spaces, picnic sites, and dog parks. The County has a total of 57 parks, five of which have a Community Center. All five of these Community Centers are utilized on weekdays for meeting space and on most weekends (May-October) for weddings and receptions; there is little opportunity for programming community classes and workshops at these five centers.

**Programming Goals** 

The Farm Park will provide a variety of recreational and educational opportunities for both nearby residents and the community at large, all in one location. While many local residents will likely walk, bike or skate to the park, others will arrive in vehicles or via public transit. The total number of spaces allotted for park users is 58 parking spaces. A matrix (attached) shows the parking available for various park uses with maximum capacity on weekends, days, and evenings, for both outdoor activities and community center programs and rentals. This matrix was developed based on the preliminary parking study prepared by Fehr and Peers in October of 2008. Parks staff will use this matrix to "program" the community center (i.e. schedule classroom use and book reservations for the assembly room) in order to maintain adequate on-site parking commensurate with the parking needs for both the outdoor park features and the community center.

Outdoor Park Features: The Farm Park will be open everyday, from dawn to dusk. The entire exterior of the Farm will be fenced. The skate feature will also be fenced, and will have a locking gate. Pedestrian access to the skate feature, the pedestrian bridge and the pedestrian gates on the Tee Street side of the park will be limited, from approximately 8:00 a.m. to dusk. Should a community building class begin earlier than 8:00 a.m., the instructor will open the driveway gate so attendees can access the park via car. The driveway gates will be locked at dusk or when the community building closes. Use of the various park features will vary based upon the seasonal conditions and also will decrease during the school year (Sept.-May), during early mornings (7-10 a.m.) and at nighttime (7-10 p.m.). The use of the outdoor park features will be dependent upon the natural lighting available and this varies with the seasons. Parking used for the outdoor features is expected to be a maximum of 13 cars on weekdays and 21 cars on weekends (preliminary Fehr & Peers transportation analysis, Oct. 2008)

#### Skate Element

The skate element is designed for skaters with beginning-level skills. It will appeal to young and pre-teen children within walking distance to the park. Older teens and adults who typically drive or skate to a "destination" skate park (e.g. the 15,000-square-foot skate park at Mike Fox Park in Santa Cruz) would find the skate element at the Farm Park too tame for their interest and skill level, and would not likely frequent the site. Expected hours of use will be M-F from school-release (appox. 3:00 p.m.) to between 6:00-9:00 p.m., depending on the season. Sa-Su use expected to be from

ATTACHMENT 12

10:00 a.m. to between 6:00-9:00 p.m., depending on the season. M-F daytime use will be similar to weekend use hours during summer months and school break periods.

#### 1/2 Basketball Court

The ½ basketball court will offer an opportunity for the neighborhood community practice their game and shoot some hoops. The ½ court will not draw the size and type group that full-courts do. . Expected hours of use will be M-F from school-release (appox. 3:00 p.m.) to between 6:00-9:00 p.m., depending on the season. Sa-Su use expected to be from 10:00 a.m. to between 6:00-9:00 p.m., depending on the season. M-F daytime use time will be similar to weekend use hours during summer months and school break periods.

#### **Bocci Ball Court**

The bocci ball court will be used primarily by those visiting the park for other reasons (e.g. picnics, assembly room rentals). Expected hours of use will be M-F from school-release (appox. 3:00 p.m.) to between 6:00-9:00 p.m., depending on the season. Sa-Su use expected to be from 10:00 a.m. to between 6:00-9:00 p.m., depending on the season. M-F daytime use time will be similar to weekend use hours during summer months and school break periods.

### Play Area

Neighborhood families with toddlers, as well as local school-age children of up to 12 years in age, will walk to the park to enjoy the play area. The play area will be comprised of three sections, one of which will be for tots, and two for school-age children. Adjacent tables and benches will give parents a place to sit and watch their children, or for the whole family to enjoy a picnic. Expected hours of use will be mornings (parents with small children), and afternoons and weekend days by school-age children who live near the park.

## **Community Gardens**

A lottery system will determine the lucky gardeners who will enjoy planting flowers and vegetables in one of the spacious (approx. 6'x8') garden beds; at least two of the garden beds will be accessible to park visitors who use a wheelchair. One of the beds will be used as a demonstration garden, for classes and interpretive programs. A picnic table, information kiosk, and garden shed round out the amenities. Open every day, dawn to dusk. Anticipate early morning and early evening use M-F, and all day on weekends. Use of the community gardens decrease during winter months.

#### Picnic Areas

Several small picnic areas, scattered throughout the park, will be used primarily by neighboring families for weekend picnics and small gatherings, and as a lunch spot on weekdays by those working nearby. The picnic areas will not be rented out; they will be available on a first-come, first-served basis.

Community Center: The Community Center is comprised of a small office and three multi-purpose main rooms: An Assembly Room (Rm. 100) and two multi-purpose classrooms, Rooms 200 and 300. The Community Center will serve a variety of purposes: from meeting space for community groups, to an assembly room for individuals to host small receptions or hold workshops, to appropriately outfitted 2-D and 3-D art classrooms for visual arts or other types of classes for all ages. Walls in the lobby area will be outfitted with a hanging system so the walls may be used as a gallery space. Soquel history will be featured in a wall kiosk in the lobby entryway.

145/163 · ATTACHMENT - 1;

The Farm Park Community Center will be open everyday (except selected holidays), from 8 a.m.-10 p.m., though classes in the Center may be scheduled as early as 7:00 a.m. Use of the various park features will decrease during the school year (Sept.-May), during early mornings (7-10 a.m.) and at nighttime (7-10 p.m.) and also during the winter when there is less natural light. Parking used for the Community Center varies based on which of the three rooms are used, and at what occupancy, at any given time. The maximum allowable parking for the Community Center is 45 cars on weekdays and 37 cars on weekends (preliminary Fehr & Peers transportation analysis, Oct. 2008). Parking for the site has been carefully developed in order for the on-site parking to be commensurate with the parking needs of both the outdoor park features and Community Center programming. The park site-plan provides 58 onsite parking spaces (fifty four on the Cunnison Lane side and four on the Tee Street side), with the appropriate number of accessible parking spaces.

The priority in programming the Community Center's three rooms is: first priority, County Parks organized programs and classes; second priority, community groups (girl scouts, AA, local non-profits, etc.); and third priority, individuals (for wedding receptions, parties, etc.). The maximum group size allowed for any given class, workshop or rental will vary based other scheduled Community Center activities and expected outdoor park use, and whether the assembly room activity is proposed for a weekday or weekend; details are shown in the attached matrix. The uses proposed for the community center will not exceed the available number of parking spaces. The number of available parking spaces has been determined based on a preliminary parking study by Fehr and Peers, Oct. 2008, which determined the required number of parking spaces for the outdoor park uses: The parking matrix, attached, was developed based on the information provided by Fehr and Peers in October 2008.

The Community Center at the Farm Park will be utilized as other Parks Department facilities are, but it will not accommodate large wedding and reception gatherings. The maximum capacity for an 800 SF room, using the same fire-code regulations as at the other county parks (1:15 SF), is 56 people. The adjacent outdoor patio may be used by groups renting the assembly room, but the maximum allowable persons will not increase.

Assembly Room - Room 100

The approximately 800 SF Assembly Room will be used both for Parks Department programs and as a rental space for individuals and community groups. Rental of the Assembly Room includes a small kitchen space, outdoor patio area with barbeque, tables and chairs, and AV equipment.

The Assembly Room will be reservable up to one year in advance using the Parks registration / reservations program, called "CLASS." The maximum number of participants for a given time of day will be entered into the CLASS system so customers know in advance how many people may attend their event or meeting. The maximum Assembly Room occupancy will be determined based upon the parking needs of the outdoor park features and classroom use (preliminary Fehr & Peers transportation analysis, Oct. 2008). Some examples of Assembly Room uses:

Parks Department organized classes:

Exercise classes (yoga, senior stretching) Parent & Me classes (Music Together) Language class

Community use examples: Scouting meeting AA meeting

## Cultural Council Associates meeting

Reservations taken from individuals for: Wedding reception Local business retreat or training session Family reunion

Classrooms (Rooms 200 and 300)

The Farm Park Community Center will offer county residents of all ages the opportunity to participate in high-quality visual art classes and workshops, as well as other types of classes and workshops, at a reasonable cost. The closest facility providing classes for the public, Cabrillo College, serves primarily recent high-school graduates; the classes at the Farm Park would serve primarily older adults and seniors (age 30+), as well as school-age (5-17 years) and pre-school children (ages 3-5). These appropriatelyequipped classrooms will draw top-notch instructors and a steady stream of students, providing a muchneeded revenue source for the Parks Department, while performing a valuable community service.

Classroom 1 (Rm. 200)

This classroom will be programmed with a variety classes for all ages and abilities. There will be adequate storage for on-going art projects (5-6 concurrent classes taught during the same calendar period but at different times of the day) and for supplies (cabinets, closet, AV equipment). A vented spray box will allow for application of fixatives (and other fume-producing sprays) inside the classroom. The building design includes an outdoor patio area where students can look to the riparian corridor for inspiration or to set up an easel and paint. Max.group size in approximately 900 SF of space, at 50 SF/student, is 19. (18 students and 1 teacher). Class offerings will vary depending on the season and age group served. Types of classes include:

Visual Arts: aqueous-medium painting, drawing and mixed-media, collage/assemblage, printmaking, fiber arts, digital media, etc. Crafts: mosaic, jewelry making, mask-making, scrapbooking, camp crafts, etc. Language Classes Tax-prep Workshops Parent & Child Classes (e.g. music together) Interpretive Workshops

Classroom 2 (Rm. 300)

This classroom will be programmed with a variety of sculpture and ceramics classes for all ages and abilities. The class offerings will vary depending on the season and age group served. There will be at least six wheels and one kiln. Storage space will be provided for on-going work and classroom supplies, such as clay, glazes, firing tools/equipment. Max.group size in approximately 600 SF of space, at 50 SF/student, is 13. (12 students and 1 teacher).

#### Office

When the Assembly Room is rented to a group for a party or reception, an attendant will staff the office. The attached parking matrix includes one teacher or facility attendant for all Assembly Room uses. If a class is scheduled in the Assembly Room, then the parking space will be used by a teacher; a facility attendant will not required as teachers will be issued a key to open the room.

#### Farm Park - Parking Matrix - Weekdays

Non-Holidays Fall/Winter/Spring	Weekday	Morning	7 AM - 10 AM	Estimated Parking
Room Description	Activity Decription	Number of Participants	Mode Split (1)	Demand
Assembly	Exercise Class (e.g. yoga, pilates)	30	22	22
Outdoor Park Use (2)				13
			To	otal 35

		At the Africants	Mode Split (1)	Estimated Parl Demand
Room Description	Activity Decription	Number of Participants	моие эрт	Domana
Assembly Rm 100	Meeting, Class or Assembly	30	22	22
Classroom Rm 300	Pottery or Sculpture Class - Adults	12	9	9
Classroom Rm 200	Workshop or Class - Adults	18	14	14
Outdoor Park Use <sup>(2)</sup>				13

Fall/Winter/Spring  Room Description	Activity Decription	Number of Participants	Mode Split (1)	Estimated Parl Demand
Assembly	Meeting, Class or Small Assembly	30	22	22
Classroom Rm 300	Pottery or Sculpture Class - children	12	9	9
Classroom Rm 200	Workshop or Class - teens	18	14	14
Outdoor Park Use (2)				13

	A divita Deportion	Number of Participants	Mode Split (1)	Estimated Parki Demand
Room Description	Activity Decription	Number of Fatticipants	wood opin	
Assembly	Meeting, Class or Assembly	30	22	22
Classroom Rm 300	Pottery or Sculpture Class - Adults	12	9	9
Classroom Rm 200	Workshop or Class - Adults	18	14	14
Outdoor Park Use (2)				13
			То	tal 58

<sup>(1)</sup> reference table 14 F&P traffic report - includes one teacher

<sup>(2)</sup> reference F&P traffic report - outdoor park uses 13 spaces weekdays; 21 weekends

Summer & School Breaks	Weekday	Morning	7 AM - 10 AM	Estimated Parking
Room Description	Activity Decription	Number of Participants	Mode Split (1)	Demand
Assembly	Exercise Class (e.g. yoga, pilates)	30	22	22
Outdoor Park Use (2)				13
			To	tal 35

Room Description	Activity Decription	Number of Participants	Mode Split (1)	Estimated Park Demand
Assembly Rm 100	Parent & Me Class (e.g Music Together)	. 28	21	21
Classroom Rm 200	Workshop or Class	18	14	14
Classroom Rm 300	Pottery or Sculpture Class - all ages	12	9	9
Outdoor Park Use (2)	,			13

g, Class or Smal Assembly ery or Sculpture	26	19	19
on Sculpture			
ass - all ages	12	9	9
hop or Class - al ages	l 18	14	14
			13
	hop or Class - al	hop or Class - all	hop or Class - all

Room Description	Activity Decription	Number of Participants	Mode Split <sup>(1)</sup>	Estimated Part Demand
Assembly	Meeting, Class or Assembly	30	22	22
Classroom Rm 300	Pottery or Sculpture Class - Adults	12	9	9
Classroom Rm 200	Workshop or Class - adults	18	14	14
Outdoor Park Use (2)				13
Outdoor Park Use (2)			Tota	

<sup>(1)</sup> reference table 14 F&P traffic report - includes one teacher

<sup>(2)</sup> reference F&P traffic report - outdoor park uses 13 spaces weekdays; 21 weekends

## Farm Park - Parking Matrix - Weekends

Non-Holidays Fall/Winter/Spring	Weekends	Morning Number of	7 AM - 10 AM	Estimated Parking
Room Description	Activity Decription	Participants	Mode Split (1)	Demand
Assembly Rm 100	Exercise Class (e.g. yoga, pilates)	30	22	22
Outdoor Park Use <sup>(2)</sup>				21
			Total	43

Non≟Holidaya FalliWiliterSpring	Waakandaks	Daytime Number of	OAM SIPM	Estimated Parking
Room Description	Activity Decription	Participants	Mode Split (1)	Demand
Assembly Rm 100	Meeting, Class	18	14	14
Classroom Rm 200	Workshop or Class - all ages	18	14	14
Classroom Rm 300	Pottery or Sculpture Class - all ages	12	9	9
Outdoor Park Use (2)				21
		•	Total	58

all/Winter/Spring	Weekends  Activity Decription	Evening  Number of  Participants	Mode Split (*)	Estimated Parking Demand
Assembly Rm 100	Meeting, Class	18	14	14
Classroom Rm 200	Workshop or Class - all ages	18	14	14
Classroom Rm 300	Pottery or Sculpture Class - all ages	12	9	9
Outdoor Park Use <sup>(2)</sup>				21
			Total	58

Room Description	Activity Decription	Number of Participants	Mode Split (1)	Estimated Parking Demand
Assembly Rm 100	Assembly	20	14	14
Classroom Rm 200	Workshop or Class - adults	18	14	14
Classroom Rm 300	Pottery or Sculpture Class - adults	12	9	9
Outdoor Park Use (2)				21
			Total	58

<sup>(1)</sup> reference table 14 F&P traffic report - includes one teacher

<sup>(2)</sup> reference F&P traffic report - outdoor park uses 13 spaces weekdays; 21 weekends

Summer & School Breaks	Weekends	Morning Number of	7-AM - 10 AM	Estimated Parking
Room Description	Activity Decription	Participants	Mode Split (1)	Demand
Assembly Rm 100	Exercise Class (e.g. yoga, pilates)	30	22	22
Outdoor Park Use <sup>(2)</sup>		·		21
			Total	43

Summer & School		a Dayline:	(10/AMI-3.PM	
		Number of		Estimated Parking
Room Description	Activity Decription	Participants	Mode Split (1)	Demand
Assembly Rm 100	Meeting, Class or Small Assembly	18	14	14
Classroom Rm 200	Workshop or Class - all ages	18	14	14
Classroom Rm 300	Pottery or Sculpture Class - all ages	12	9	9
Outdoor Park Use <sup>(2)</sup>			·	21
			Total	58

Room Description	Weekends  Activity Decription	Number of Participants	Mode Split (1)	Estimated Parking Demand
Assembly Rm 100	Meeting, Class or Small Assembly	18	14	14
Classroom Rm 200	Workshop or Class - all ages	18	14	14
Classroom Rm 300	Pottery or Sculpture Class - all ages	12	. 9	9
Outdoor Park Use (2)				21
			Total	58

Room Description	Activity Decription	Number of Participants	Mode Split (1)	Estimated Parking Demand
Assembly Rm 100	Meeting, Class or Assembly	52	37	37
Outdoor Park Use <sup>(2)</sup>				21

<sup>(1)</sup> reference table 14 F&P traffic report - includes one teacher

<sup>(2)</sup> reference F&P traffic report - outdoor park uses 13 spaces weekdays; 21 weekends



## Civil and Structural Engineering

## STREAM HYDROLOGY AND HYDRAULICS FINAL REPORT TASK 10.10

For

# FARM NEIGHBORHOOD PARK AND COMMUNITY CENTER SCHEMATIC DESIGN

SANTA CRUZ COUNTY CALIFORNIA

Prepared for:
Moore Iacofano Goltsman, Inc.
800 Hearst Avenue
Berkeley, CA 94710
Ph: 510-845-7549

Prepared by:
Mesiti-Miller Engineering, Inc.
224 Walnut Avenue, Suite B
Santa Cruz, CA 95060
Ph: 831-426-3186

Project No. 7141 July 29, 2009

Designer's Attest:

The following report has been prepared under the supervision of the undersigned, who hereby certifies that he is a Registered Civil Engineer in the State of California.

Prepared by:

Rodney T. Cahill, RCE No. 67728

67728 F

Expires 6 · 30 · 1/

(L)ate)

7.29.09

ATTACHMENT - 1



# Task 10.10 - Stream Hydrology and Hydraulics Final Report

#### 1. Introduction

#### a. Purpose

Mesiti-Miller Engineering, Inc. prepared this report at the request of Moore Iacofano Goltsman Inc. (MIG) for submittal to the Planning Department as part of the Development Permit Application for the Farm Neighborhood Park and Community Center Project Schematic Design.

The purpose of this report is to evaluate the hydrology and hydraulics of the creek that bisects the Farm Neighborhood Park site, determine the design water surface elevation for the proposed pedestrian bridge, recommend a minimum freeboard, and report the findings and recommendations. The study involved a hydrologic analysis to quantify the runoff rate and the development of a hydraulic computer model to determine the water surface elevation at the proposed bridge site.

## b. Project Description

The proposed project is a neighborhood park and community center on the north side of Soquel Drive, approximately midway between Porter Street and Park Avenue in Santa Cruz, California (Figure 1). The unnamed creek that bisects the site is a tributary to Nobel Creek and Soquel Creek. The proposed pedestrian bridge will span approximately 80-100 feet and connect the two sides of the park together.

The project site is located outside the limits of study to determine the Special Flood Hazard Area: the area subject to flooding by the 1% annual chance flood according to the Federal Emergency Management Agency (FEMA (b), 2006). Site-specific hydrologic calculations and a hydraulic model were prepared to develop design water surface elevations.

## 2. Hydrology and Hydraulics

#### a. Hydrology

Hydrologic calculations were prepared using the Rational Method in accordance with the County Design Criteria (Santa Cruz County, 2006). The watershed area above the Soquel Drive culvert is about 121.54 acres (Figure 2). The creek is an intermittent stream extending 4,631 feet upstream from the Soquel Creek culvert to the most remote point in the watershed near Fairway Drive. The elevation of the most remote point in the watershed is about 286 feet above the entrance to the Soquel Drive culvert. The resulting time of concentration is 16 minutes (Fig SWM-4). We estimated the 100-year runoff rate using a spreadsheet with precipitation data and runoff coefficients obtained from the County Design Criteria (Table 1).



The estimated 100-year peak runoff rate is 178 cfs.

## b. Hydraulic Analysis

We modeled two hydraulic scenarios to determine the design water surface elevation; the first case based on unobstructed flow through the Soquel Drive culvert, the second case considered the culvert clogged with debris so that water would build up and flow across Soquel Drive.

We generated cross sections of the creek at 100-foot intervals based on site-specific topographic survey information (Gary Ifland and Associates, 2008) in AutoCAD Civil 3D (Autodesk, 2008). We input approximate section properties such as invert elevation, top of bank elevation (left and right), and base width into HEC-RAS 4.0.0 water surface profile computer program (USACE, 2008). We prepared a map with cross section locations (Figure 3).

The Soquel Drive culvert is a compound structure made up of concrete pipes, concrete arches, and junction structures. We simplified the culvert for modelling purposes into an equivalent 287 feet long, 48 inch diameter culvert.

In the clogged design case we reduced the culvert diameter to 4 inches. We input the approximate land surface geometry above the culvert so that we could investigate the effects of flow passing over the roadway on the water surface elevation at the proposed bridge. We obstructed the fenced area around the gas station and reduced the weir coefficient to 2.0 to account for complex flow paths around fences and across the roadway. This is less than the typical range (2.5-3.1) recommended for a broad crested spillway, and results in a slower the rate of flow than the typical coefficient.

For an 80 foot span bridge, the proposed deck elevation is about 144 on the western side and 142 on the eastern side (Sheet S-1.0). We added the proposed bridge to the model at Station 10+00 with a thickness of 10 feet to account for the truss height.

A channel roughness value (Manning's n) was chosen based on field observations and comparison with the range of channel roughness values used in the Flood Insurance Study for adjacent watersheds; 0.015 to 0.050 (FEMA (a), 2006). The selected roughness value used in the model was 0.035. The downstream boundary condition was set to normal depth based on the mean slope of the Soquel Drive culvert, 3%. The upstream boundary condition was set to normal depth based on the mean slope of the upper reach of channel, 7%. We extended the model a sufficient distance each side of the proposed bridge site to normalize the effects of these assumptions.

We kept the expansion/contraction coefficients for most cross sections at the default values, 0.1/0.3. We increased the coefficients to 0.3/0.5 to account for energy losses each side of the culvert. We kept the default channel coefficients at the proposed bridge location since the bridge will be elevated above the water surface.



### c. Estimated water surface elevation

Water surface elevation profiles and a cross section view were presented in Figures 4 and 5. This table is a summary of the results of our analysis:

Table 2 - Design Water Surface Elevation

Design Case #	Design Case	100-year Design Water Surface Elevation at Proposed Bridge Site
1	Unobstructed Flow	124.1
2	Clogged Culvert	126.3

We recommend using the clogged culvert design case in the bridge design since there is a chance that debris from the watershed could clog the trash rack located on the entrance to the Soquel Drive culvert.

## 3. Design Recommendations

## a. Minimum freeboard recommendation

We recommend three feet of freeboard be provided between the design water surface elevation and the lower chord of the bridge superstructure to allow for unaccounted factors. These might include unusual hydrologic events, future development in the watershed, unforeseen bank failure, the accumulation of silt or debris, simplifications made in the study, and variations of coefficients used in the analysis (USACE, 1991).

Table 3 - Design Water Surface Elevation

Design Case #	Design Case	100-year Design Water Surface Elevation at Proposed Bridge Site + 3 feet of Freeboard
2	Clogged Culvert	129.3

#### 4. Conclusion

#### a. Bridge Design

The lower chord elevation of the proposed bridge (138 feet) is approximately 12 feet above the 100-year design water surface elevation (126.3 feet). The proposed bridge elevation provides approximately 9 feet of additional clearance on top of the minimum recommended freeboard.



# **ON-SITE STORM DRAINAGE** FINAL REPORT

**TASK 10.8** 

For

# FARM NEIGHBORHOOD PARK AND COMMUNITY CENTER **SCHEMATIC DESIGN**

SANTA CRUZ COUNTY **CALIFORNIA** 

Prepared for: Moore Iacofano Goltsman, Inc. 800 Hearst Avenue Berkeley, CA 94710 Ph: 510-845-7549

Prepared by: Mesiti-Miller Engineering, Inc. 224 Walnut Avenue, Suite B Santa Cruz, CA 95060 Ph: 831-426-3186

> Project No. 7141 August 4th, 2009

Designer's Attest:

The following report has been prepared under the supervision of the undersigned, who hereby certifies that he is a Registered Civil Engineer in the State of California.

Prepared by:

Rodney T. Cahill, RCE No. 67728

67728



## Task 10.8 – On-site Storm Drainage Final Report

#### 1. Introduction

#### A. Purpose

Mesiti-Miller Engineering, Inc. (MME) prepared this drainage report at the request of Moore Iacofano Goltsman, Inc. (MIG) for the Farm Neighborhood Park and Community Center project. The purpose of this drainage report is to summarize existing and proposed on-site drainage conditions for Development Permit Application in conjunction with the Schematic Design Plans. Recommendations for detention and/or retention are included in accordance with County of Santa Cruz Department of Public Works (DPW) Drainage Section Standards.

### **B.** Project Description

The project site is approximately 5.5 acres and consists of two adjoining parcels located on the north side of Soquel Drive, approximately midway between Porter Street and Park Avenue in Santa Cruz County, California. A 3.75-acre parcel is located on the corner of Soquel Drive and Cunnison Lane at 5555 Soquel Drive (APN 37-101-58). A 1.77-acre parcel is located at 5540 Tee Street (APN 37-101-59).

The proposed project is a neighborhood park that features a community building, a restroom building, parking, a community garden, walking trails, a pedestrian bridge, play equipment, and sporting elements.

## 2. Pre-development Drainage Conditions

#### A. Hydrology

About 70 percent of the project site or about 3.7 acres drains toward an unnamed creek that bi-sects the site. Runoff flows through a culvert under Soquel Drive and continues down an open channel and into Noble Gulch, then into Soquel Creek, and outlets into Monterey Bay at Capitola Village. The remaining 1.7 acres or 30 percent of the south-eastern part of the site drains to a street storm drainage network in Soquel Drive and Cunnison Lane. This network discharges through a junction box below the sidewalk in front of the gas station/convenience store into the afore-mentioned culvert below Soquel Drive. In this way, 100% of the site drains into the culvert under Soquel Drive (Figure 1).

ATTACHMENT 14



We prepared on-site hydrologic calculations using the rational method for the 10-year storm event, per DPW standards. We divided the site into six sub-watersheds to determine the amount of runoff flowing to six different inlets, or points of concentration (Figure 1). A weighted coefficient of runoff was determined for each sub-watershed by considering the watershed drainage characteristics and the relative effect of any existing impervious areas. We used runoff coefficients and antecedent moisture condition factors given in the County Design Criteria (CDC).

We accounted for only the impervious areas with recorded permits or that were areas constructed prior to Zone 5 incorporation in 1969, per DPW standards. To do this we reviewed the archived building permits for the parcels, the available assessor's records, and the pre-existing maps prepared by Gary Ifland and Associates<sup>1</sup> and determined which structures, parking areas, gravel areas, and paved walkways would count toward the existing impervious area.

Rainfall intensity was determined using the equation given in Figure SWM-3 of the CDC. Since a stormwater detention system is required to mitigate the post-development increase in impervious area we selected a minimum time of concentration of 15 minutes in accordance with the CDC for detention system sizing.

We summarized pre-development flow calculations and coefficients for each subwatershed in Table 1 and prepared a diagram of pre-development on-site drainage boundaries in Figure 1. Detailed hydrologic calculations were included in Appendix A.

## **B.** Hydraulics

We investigated existing conditions on-site hydraulic conditions on a qualitative basis by visiting the site, inspecting the site topographic survey and regional aerial survey, and reviewing our hydrology calculations.

With the notable exception of the flow in the creek, on-site runoff is low-volume, low-flow, shallow, and well-distributed or sheet flow. For a separate analysis of the creek traversing the site, refer to the Stream Hydrology and Hydraulics Report<sup>2</sup>.

We observed a small drainage swale originating from an existing drainage inlet in the south-east corner of Tee Street that traverses the site in a south-easterly direction. Neighbors informed us that during some storms, stormwater will overflow on to the site and sheet slowly across the meadow and down into the creek. We analyzed the catch basin inlet capacity, inflow pipe capacity, and outflow pipe capacity to assess the existing storm drainage system in Tee Street. The results showed the existing drainage pipes and inlet are large enough to carry the design flows. We investigated the land condition downstream of the drainage swale and did not find any evidence of soil or bank erosion. As a result, we estimate stormwater run-on occurs infrequently, possibly due to obstruction of the inlet, and does not pose any significant risk of erosion to the project.



#### **Post-development Drainage Conditions** 3.

## A. Hydrology

A post-development weighted coefficient of runoff was determined for each sub watershed by considering the watershed drainage characteristics and the relative effect of impervious areas (Appendix A). This enabled us to calculate the post-development peak flow for each watershed and compare to pre-development conditions. Pre- and post-development hydrologic and hydraulic calculations were summarized in Table 1. Post-development drainage area boundaries were drawn in Figure 2.

We measured post-development impervious areas to determine the increase in impervious area in each watershed (Table 4). We slightly overestimated the postdevelopment impervious areas shown in the Schematic Design Site Plan<sup>3</sup> to provide design flexibility in the final design phase (Figure 2). These areas should be refined before building permit submittal.

Table 4 - Impervious Areas

Fable 4 – Impervio Sub-Watershed	Pre-development Impervious Area (square feet)	Post-development Impervious Area (square feet)	Net New Impervious Area (square feet)
1	49,002	66,260	17,259
2	5,731	3,463	-2,268
3	2,313	160	-2,153
4	3,487	23,083	19,596
5	505	20,259	19,754
6	4,327	12,639	8,313
Total	65,365	125,864	60,501

Our preliminary measurements show that the proposed impervious areas exceed the existing impervious areas by approximately 60,501 square feet. As a result, detention facilities are required to mitigate hydrologic changes and maintain post-development runoff at pre-development rates.

## B. Hydraulics

We prepared the Schematic Design On-Site Drainage Plan (Figure C-1.0) to demonstrate recommended post-development drainage conditions. Key objectives of the drainage plan were to slow down, infiltrate, and filter stormwater. To do this we diverted drainage from parking and hardscape areas into vegetated areas, bioswales, rain gardens, or lawn areas prior to collection and routing through the proposed subsurface drainage system. There are two different drainage systems developed for the project to suit the opportunities and constraints of the two parcels. The higher development density on the Cunnison Lane parcel required a traditional drainage design approach whereas the availability of open space on the Tee Street parcel allowed for a lower intensity drainage design technique.

The Cunnison Lane drainage system conveys stormwater from all impervious areas to a sub-surface detention/retention pipe via a treatment train consisting of bioswales and



a hydrodynamic separator to meet DPW and LEED design criteria. The proposed detention/retention facility is a large diameter pipe and outlet control structure designed to meter release rates. We recommend retaining some runoff on-site by providing perforations in the detention pipe that will allow some runoff to infiltrate into a surrounding gravel trench. Retention is required to to satisfy LEED stormwater quantity control credit criteria although DPW does not require retention facilities since the site is outside of County-identified groundwater recharge watersheds. We recommend consulting with the Geotechnical Engineer during the Design Development phase to finalize retention details. We worked with grading designers to slope parking areas toward landscaped bioswales adjacent to the parking lots where possible before routing to the hydrodynamic separation unit and sub-surface detention/retention facility. The hydrodynamic separator unit will require annual vacuum cleaning and a signed maintenance agreement per DPW guidelines.

The Tee Street drainage system features a detention/retention rain garden system to allow stormwater to percolate through the lower portion of the recreational turf into the groundwater. Pre-treatment will occur by filtration across the grassy slope and through a loamy sand layer. Detention volume will be provided within the voids of a crushed rock layer below the loamy sand layer. Perforated sub-drains below the rain garden and a surface spillway will provide safe overflow for when very heavy storm events exceed the infiltration capacity of the soil. This system will be invisible from the surface, except for a slight depression in the turf surface, and will be dry within 48 hours after a 10-year rain storm. The garden will be walk-able during rain events since the loamy sand and crushed rock substrate will have low clay content. Good maintenance will keep the watershed free of loose soil and maintain minimal sediment supply to the percolation area. The upslope turf area will naturally filter runoff sheet flowing into the rain garden so that the system will tolerate some unexpected sediment. Schematic Design On-site Drainage Plans show a swale to pick up potential off-site run-on from Tee Street and safely convey stormwater around the on-site retention/detention facility and toward the creek.

Since site grading and drainage design is currently in schematic form a precise hydraulic study of pipes and drainage structures is premature at this point. We did however calculate the approximate size of detention and retention facilities based on currently planned impervious surfaces in order to gain an appreciation of how they will fit into the landscape. We calculated detention volume requirements for the 10-year storm with a 15 minute time of concentration based on net new impervious area per DPW Standards (Table 2). We considered existing gravel driveways to be 50% impervious, per Drainage Section Standards. We provided detailed detention and retention calculations in Appendix B. For preliminary purposes we calculated retention volumes using the DPW-recommended modified rational method for a 2-year, 2-hour storm (Appendix B). We summarized retention volumes in Table 3. In final calculations we will examine the 1-year and 2-year, 24-hour storms in accordance with LEED requirements using TR-55 methodology that is more suited to detention and retention facility sizing. We do not expect LEED requirements to result in larger or more costly detention or retention facilities. These Best Management Practices (BMPs) will release stormwater downstream at a rate less than the pre-development rate for the 1-year 24 hour, 2-year 24 hour, and 10-year peak storms. In addition BMPs will filter and remove 80% of Total Suspended Solids from 90% of the average annual rainfall in accordance with LEED standards. Since the rain water harvesting



tank could possibly be full during the peak design storm, rainwater harvesting did not affect the sizing of the detention system per DPW criteria. Refer to the Irrigation Water Supply Report<sup>4</sup> for further discussion on rainwater harvesting.

#### C. LEED Credits

The following drainage-related Leadership in Environmental and Energy Design (LEED) Credits are available for the project<sup>5</sup>:

1. LEED Sustainable Sites Credit 6.1 Stormwater Design, Quantity Control – 1 point: Implement a stormwater management plan that prevents the post-development peak discharge rate and quantity from exceeding the pre-development peak discharge rate and quantity for the one- and two-year, 24-hour design storms.

Groundwater conditions over the winter season are unknown at the site. Since the volume control part of this requirement will require mid-sized on-site infiltration measures, a seasonal groundwater investigation is required to determine the feasibility of achieving this credit. Infiltration design is controlled by the 2-year, 24-hour design storm for Santa Cruz, or 3.5 inches<sup>6</sup>. For reference, this is less stringent and results in smaller facilities than the DPW standard for projects in water supply watersheds (not applicable to this project). The rate control/detention part of this requirement is more easily satisfied and less stringent than the DPW Standards for 10-year, 10-minute storms. To achieve this credit a mid-sized infiltration/retention system is required. These systems commonly include perforated pipes, gravel trenches, ponds, or drainage structures.

 LEED Sustainable Sites Credit 6.2 Stormwater Design, Quality Control – 1 point: Implement a stormwater management plan that reduces impervious cover, promotes infiltration, and captures and treats the stormwater runoff from 90% of the average annual rainfall using acceptable best management practices (BMPs). BMPs used to treat runoff must be capable of removing 80% of the average annual post development total suspended solids (TSS) load based on existing monitoring reports.

We can design bio-filtration and hydrodynamic separation systems to comply with this credit. 90% of the average annual rainfall for semi-arid watersheds is about 1 inch.

i:\7141 farm park\reports\task 10 - reports\task 10.8 on-site sd\final report\text parts\7141 farmpark t108 on-site sd rpt.doc

Gary Ifland and Associates, Pre-1991 Plan for The Farm Park, 2008


<sup>&</sup>lt;sup>2</sup> MME, Stream Hydrology and Hydraulics Final Report, 29 July 2009

<sup>&</sup>lt;sup>3</sup> MIG, Schematic Design, Site Plan, 19 June 2009

<sup>&</sup>lt;sup>4</sup> MME, Irrigation Water Supply Draft Report, 29 July 2009

<sup>&</sup>lt;sup>5</sup> U.S Green Building Council, <u>LEED for New Construction and Major Renovations</u>, Version 2.2, October 2005

<sup>&</sup>lt;sup>6</sup> National Oceans and Atmosphere Administration, <u>NOAA Atlas 2, Volume XI Precipitation Frequency</u> <u>Atlas of the Western United States</u>, 1973





# OFF-SITE STORM DRAINAGE FINAL REPORT TASK 10.9

For

# FARM NEIGHBORHOOD PARK AND COMMUNITY CENTER SCHEMATIC DESIGN

SANTA CRUZ COUNTY CALIFORNIA

Prepared for:
Moore lacofano Goltsman, Inc.
800 Hearst Avenue
Berkeley, CA 94710
Ph: 510-845-7549

Prepared by:
Mesiti-Miller Engineering, Inc.
224 Walnut Avenue, Suite B
Santa Cruz, CA 95060
Ph: 831-426-3186

Project No. 7141 July 11th, 2009

Designer's Attest:

The following report has been prepared under the supervision of the undersigned, who hereby certifies that he is a Registered Civil Engineer in the State of California.

Prepared by:

Rodney T. Cahill, RCE No. 67728

67720 Expires 6/30///

7/11/2009 (Date)

ATTACHMENT

14



## 4. Summary of Off-Site Upgrade Recommendations

Soquel Drive East and Soquel Junction

We recommend the following upgrades to the off-site drainage system in Soquel Drive downstream of the Project site in connection with the Farm Park Project. The schematic design for off-site drainage improvement is included (Sheet C-1.1).

- 1. Replace 62 linear feet of 18" diameter pipe with 24" diameter pipe at a deeper elevation and steeper slope (P-9)
- 2. Replace 328 linear feet of 18" diameter pipes with 36" diameter pipes at deeper elevations and steeper slopes (P-10, P-11, P-12)
- 3. Replace two 7 feet sections of 18" diameter pipe with a 36" diameter pipe (P-13).
- 4. Replace three existing inlets with Caltrans Type GOL-10 combination inlets (1-5, 1-6, 1-7).
- 5. Replace one existing junction structure (J-5) with a Caltrans Type GOL-10 combination inlet (I-17).
- 6. Replace one existing manhole (J-6) to suit new pipe elevations and diameters.
- 7. Adjust/replace one existing junction structure (J-1) to suit new pipe elevation and diameter.

## Soquel Drive West and Hardin Way

To prevent overflow across Soquel Drive we recommend upgrades to the Hardin Way and West Soquel Drive drainage systems. This work would be separate from the Farm Park Project in that the Project site is separate and does not contribute runoff to the Hardin Way and West Soquel Drive drainage systems.

i:\7141 farm park\reports\task 10 - reports\task 10.9 off-site sd\final report\text parts\7141 farmpark t109 off-site sd rpt.doc

Santa Cruz County, Design Criteria Containing Standards for the Construction of Streets, Stormwater Systems, Sanitary Systems, Water Systems, Driveways within the Unincorporated Portion of Santa Cruz County, June 2006

<sup>&</sup>quot;Santa Cruz County Public Works Department, Volume 1 Zone 5 Master Drainage Plan, 20 October 1998

iii Santa Cruz County Planning Department, Application # 06-0595, letter to Santa Cruz Redevelopment Agency, 12 February, 2007

<sup>&</sup>lt;sup>iv</sup> California Department of Transportation, Highway Design Manual, Chapter 830 Roadway Drainage, September 1 2006

<sup>&#</sup>x27;Gary Ifland and Associates, Topographic Survey for Farm Park, May 20 2008

vi Sheryl Bailey, Santa Cruz County Redevelopment Agency, Email to Rodney Cahill, dated June 30, 2009 12:13 PM

vii Dolan v. City of Tigard, 512 U.S 374, 129 L. Ed 2d 304, 114 S. Ct. 2309 (1994)

viii Dolan v. City of Tigard, 512 U.S 374, 129 L. Ed 2d 304, 114 S. Ct. 2309 (1994)

<sup>&</sup>lt;sup>ix</sup> California Department of Transportation, <u>Highway Design Manual</u>, Chapter 830 Roadway Drainage, September 1 2006

Mesiti-Miller Engineering Inc., Notes from Meeting with DPW Drainage, May 15 2008