

COUNTY OF SANTA CRUZ
PLANNING DEPARTMENT
701 Ocean Street, 4th Floor
Santa Cruz, CA 95060
(831) 454-2580

**NOTICE OF ADMINISTRATIVE AGRICULTURAL BUFFER
SETBACK REDUCTION**

Pursuant to Santa Cruz County Code 16.50.095, this notice has been provided to the project applicant, to all members of APAC, to the Agricultural Commissioner, to owners of commercial agricultural land within 500 feet of the project location, and to members of the Board of Supervisors. The identified planner may be contacted for specific information on this application.

APPLICATON NUMBER: 251056

SITUS: 107 Browns Valley Road, Watsonville, CA 95076

Proposal to recognize the construction of an ADU built on the west side of a commercial agricultural (CA) zoned property, approximately 285 feet west of the existing single-family dwelling. Project requires an Administrative Agricultural Buffer Setback Reduction to reduce the 200-foot setback to 143 feet to the north.

Project site is located at the northwest corner of the Browns Valley Road and Amesti Road intersection (107 Brown's Valley Road).

APN: 107-211-09

OWNER: JORDAN JAMES T

APPLICANT: JORDAN JAMES T

SUPERVISORIAL DISTRICT: 2

PLANNER: Evan Ditmars, (831) 454-3227

EMAIL: Evan.Ditmars@santacruzcountycalifornia.gov

Questions or comments must be received by 5:00 p.m. August 29, 2025.

A decision will be made on, or shortly after, September 1, 2025.

ABBREVIATIONS			
Ø	DIAMETER	MAX	MAXIMUM
AB	AGGREGATE BASE	MEP	MECHANICAL/ELECTRICAL/PLUMBING
ABDN	ABANDONED	MH	MANHOLE
AC	ACRE, ASPHALT CONCRETE	MIN	MINIMUM
ACP	ASBESTOS CEMENT PIPE	MIPT	MALE IRON PIPE THREAD
ACM	ASBESTOS CONTAINING MATERIAL	MJ	MECHANICAL JOINT
AD	AREA DRAIN	MPVC	MIDPOINT OF VERTICAL CURVE
AGG	AGGREGATE	MON	MONUMENT
ALGN	ALIGNMENT	N	NORTHING COORDINATE
ARV	AIR RELEASE VALVE	(N)	NEW
ASB	AGGREGATE SUBBASE	NC	NORMALLY CLOSED
ASPH	ASPHALT	NIC	NOT IN CONTRACT
		NO	NUMBER
		NTS	NOT TO SCALE
BC	BEGIN CURVE		
BEG	BEGIN		
BFP	BACK FLOW PREVENTER		
BLDC	BUILDING CORNER	OHE	OVERHEAD ELECTRIC
BLDG	BUILDING	O.R.	OFFICIAL RECORDS
BMP	BEST MANAGEMENT PRACTICES		
BOD	BOTTOM OF DOCK	(P)	PROPOSED
BOL	BOLLARD	P	PAVEMENT ELEVATION
BSW	BACK OF SIDEWALK	PA	PLANTER AREA
BVC	BEGIN VERTICAL CURVE	PB	PULL BOX
BW	FINISHED GRADE AT BOTTOM OF WALL	PCC	POINT OF COMPOUND CURVATURE
			PORTLAND CEMENT CONCRETE
C	CONCRETE OR CIVIL	PE	PLAIN END
CB	CATCH BASIN	PED	PEDESTRIAN
C&S/W	CURB, GUTTER & SIDEWALK	PERF	PERFORATED
CI	CAST IRON OR CURB INLET	PH	POTHOLE
CIP	CAST IRON PIPE	PID	POINT ID
CL	CENTERLINE	PIV	POST INDICATOR VALVE
CLR	CLEAR	PL	PROPERTY LINE
CLSM	CONTROLLED LOW-STRENGTH MATERIAL	PM	PARKING METER
CMN	COMMUNICATION	PMH	POWER MANHOLE
CMP	CORRUGATED METAL PIPE	PO	PUSH-ON
CO	CLEAN OUT	POC	POINT ON CURVE
CONC	CONCRETE	POI	POINT OF INTERSECTION
CONST	CONSTRUCTION OR CONSTRUCT	PP	POWER POLE
CONF	CONFORM TO EXISTING	PRC	POINT OF REVERSE CURVATURE
CSC	CITY OF SANTA CLARA	PRV	PRESSURE REDUCING VALVE
CU	CUBIC	PRUE	PRIVATE UTILITY EASEMENT
CY	CUBIC YARD	PT	POINT OF TANGENCY
		PUE	PUBLIC UTILITY EASEMENT
		PVC	POLYVINYL CHLORIDE PIPE
D=	DELTA (CURVE)	R	RIGHT
DCDA	DOUBLE CHECK DETECTOR ASSEMBLY	R=	RADIUS (CURVE)
DEMO	DEMOLISH	RC	RELATIVE COMPACTION
DEPT	DEPARTMENT	RCF	REINFORCED CONCRETE PIPE
DET	DETAIL	RJ	RESTRAINED JOINT
DI	DROP INLET, DUCTILE IRON	RP	RADIUS POINT
DIA	DIAMETER	RPBFP	REDUCED PRESSURE BACKFLOW PREVENTER
DIP	DUCTILE IRON PIPE	RPPA R	REDUCED PRESSURE PRINCIPLE ASSEMBLY
DOM	DOMESTIC	RSC	RECEIVING AND SUPPORT CENTER
DW	DOMESTIC WATER	RW	RECYCLED WATER
DWG	DRAWING	R/W, ROW	RIGHT OF WAY
		S	SOUTH, SLOPE
E	EASTING COORDINATE, ELECTRIC	S.A.D.	SEE ARCHITECTURAL DRAWINGS
EC	END CURVE	SD	STORM DRAIN
EG	EXISTING GRADE	SDCB	STORM DRAIN CATCH BASIN
EL, ELEV	ELEVATION	SDI	STORM DRAIN INLET
ELEC	ELECTRICAL	SDMH	STORM DRAIN MANHOLE
EP	EDGE OF PAVEMENT	SDCO	STORM DRAIN CLEANOUT
EVA	EMERGENCY VEHICLE ACCESS	S.E.D.	SEE ELECTRICAL DRAWINGS
EX,EXIST, (E)	EXISTING	SF	SILT FENCE
(F)	FUTURE	SG	SUBGRADE
FA	FIRE ALARM	SHLDR	SHOULDER
F/C,FC	FACE OF CURB	SHT	SHEET
FD	FOUND	SL	STREETLIGHT
FDC	FIRE DEPARTMENT CONNECTION	S.L.D.	SEE LANDSCAPE DRAWINGS
FF,FFE	FINISHED FLOOR ELEVATION	SMH	SIGNAL MANHOLE
FG	FINISH GRADE	S.M.D	SEE MECHANICAL DRAWINGS
FH	FIRE HYDRANT	S.P.D	SEE PLUMBING DRAWINGS
FIPT	FEMALE IRON PIPE THREAD	SS	SANITARY SEWER
FL	FLOW LINE, FLANGE	S.S.D.	SEE STRUCTURAL DRAWINGS
FG	FLANGE	SSD	SUBSURFACE DRIP
FM	FLOWMETER/FORCE MAIN	SSCO	SANITARY SEWER CLEANOUT
FOUND	FOUNDATION	SSFM	SANITARY SEWER FORCE MAIN
FS	FINISHED SURFACE	SSMH	SANITARY SEWER MANHOLE
FT	FOOT, FEET	SSPS	SANITARY SEWER PUMP STATION
FW	FIRE WATER	STA	STATION
		STD	STANDARD
G	GAS, GROUND ELEVATION	STL	STEEL
GB	GRADE BREAK	SW	SIDEWALK
GI	GALVANIZED IRON	SVP	SILICON VALLEY POWER
GRD, G	GROUND		
GV	GATE VALVE	T	TELEPHONE
		TC	TOP OF CURB
HMA	HOT MIX ASPHALT	TD	TRENCH DRAIN
HORIZ	HORIZONTAL	TEL	TELEPHONE
HT	HEIGHT	TEMP	TEMPORARY
HP	HIGH POINT	TFC	TOP FACE OF CURB
		THK	THICK
INV	INVERT	TOD	TOP OF DOCK
INST	INSTALL	TOE	TOE OF SLOPE
IRR	IRRIGATION	TW,TOW	TOP OF WALL
		TS	TOP OF SLAB
JP	JOINT POLE	TYP	TYPICAL
JT	JOINT TRENCH		
		UON	UNLESS OTHERWISE NOTED
L	LEFT	U/G	UNDERGROUND
L=	LENGTH (CURVE)	VC	VERTICAL CURVE
L _F	LINEAR FEET		
LAT	LATERAL		
LIP	LIP OF GUTTER	W	WEST, WATER
LP	LIGHT POLE, LOW POINT	WM	WATER METER
LPFH	FIRE HYDRANT	WV	WATER VALVE
LS	LANDSCAPE	WWF	WELDED WIRE FABRIC
LSA	LANDSCAPE ARCHITECT	W/	WITH
MA	MEDICAL AIR	YDS	YARDS

CIVIL SYMBOLS LEGEND			
SURVEY TOPO AND SITE IMPROVEMENTS		ANNOTATION	
6" CURB & GUTTER	SDLO	KEYNOTE	
EDGE OF AC PAVEMENT	E	DEMOLITION NOTE	
6" VERTICAL CURB	PB		
DOMESTIC WATER MAIN	HVE		
ELECTRIC LINE	T		
FLUSH LINE	Ø		
FORCE MAIN	GUY		
GAS LINE	JP		
IRRIGATION LINE	STREET LIGHT		
OVERHEAD WIRES	ELECTROLIER		
OVERHEAD ELECTRIC	TRAFFIC SIGNAL		
OVERHEAD TELEPHONE	TRAFFIC SIGNAL		
RECYCLED WATER	PEDESTRIAN LIGHT		
SANITARY SEWER LINE	PEDESTRIAN PUSH BUTTON		
STORM DRAIN LINE	CROSSWALK DETECTOR		
STREET LIGHT CONDUIT	STREET LIGHT PULLBOX		
TELECOMMUNICATIONS	SIGN (AS NOTED)		
TELEPHONE LINE	THRUST BLOCK		
TELEVISION LINE	CAP		
WATER LINE	GATE VALVE		
UNDERGROUND ELECTRIC	BUTTERFLY VALVE		
TRENCH DRAIN	DEMO		
METAL BEAM GUARD RAIL	WELL		
SILT FENCE	PUMP		
CHAIN LINK FENCE	BALL VALVE		
FLOW LINE	ACTUATED BALL VALVE		
CONTOUR ELEVATION LINE	SOLENOID VALVE		
CENTER LINE	AIR/VACUUM BREAKER		
PROPERTY LINE	PRESSURE REGULATOR		
MONUMENT LINE	SSD FILTER		
EASEMENT LINE	ISOLATION VALVE		
FINISH GRADE	CHECK VALVE		
SURFACE DRAINAGE SLOPE	FLOW METER		
SPOT ELEVATION	PRESSURE GAUGE		
GRADE BREAK	PRESSURE SWITCH		
LIMIT OF WORK/GRADING	FLOAT VALVE		
IRRIGATION BOX			
GAS METER			
GAS VALVE			
WATER METER			
WATER VALVE			
WATER METER OR BFP			
FIRE HYDRANT			
FIRE DEPARTMENT CONNECTION			
WATER TAPPING SADDLE			
SEWER MANHOLE			
SEWER CLEANOUT			
SEWER LAMP HOLE			
SEWER VENT			
STORM DRAIN MANHOLE			
CATCH BASIN			
CURB INLET			
DRAINAGE INLET			

SITE VICINITY

SITE LOCATION

APN MAP

PROJECT DESCRIPTION

GENERAL: NEW SEPTIC SYSTEM

BASIS: LEGALIZE ADU

GENERAL SHEET NOTES																							
<p>1. ABBREVIATIONS AND SYMBOLS ON THIS SHEET APPLY ONLY TO THE CIVIL DRAWINGS, REFER TO OTHER DISCIPLINES FOR APPLICABLE ABBREVIATIONS AND SYMBOLS NOT PROVIDED HERE.</p> <p>2. THIS IS A STANDARD ABBREVIATION AND LEGEND SHEET, THEREFORE, SOME ABBREVIATIONS AND LEGEND SYMBOLS MAY APPEAR ON THIS SHEET AND MAY NOT BE UTILIZED ON THIS PROJECT.</p> <p>3. DO NOT SCALE DRAWINGS.</p> <p>4. ALL WORK AND MATERIALS SHALL BE IN FULL ACCORDANCE WITH THE CURRENTLY REQUIRED VERSION OF THE FOLLOWING CODE:</p> <p>4.1. CALIFORNIA BUILDING CODE</p> <p>4.2. CALIFORNIA PLUMBING CODE</p> <p>4.3. CALIFORNIA MECHANICAL CODE</p> <p>4.4. CALIFORNIA ELECTRICAL CODE</p> <p>4.5. ALL APPLICABLE LOCAL, STATE, AND FEDERAL CODES AND ORDINANCES</p> <p>5. NOTHING ON THE ENCLOSED DRAWINGS IS TO BE CONSTRUED AS REQUIRING OR PERMITTING WORK THAT IS CONTRARY TO THE CODES, ORDINANCES, OR REGULATIONS DESCRIBED ABOVE.</p> <p>6. ANY DEVIATIONS FROM THE PROPOSED PLANS SHALL BE DISCUSSED WITH THE PROJECT ENGINEER PRIOR TO MAKING CHANGES IN THE FIELD.</p>																							
INDEX																							
<table><thead><tr><th colspan="3">WASTEWATER SHEETS</th></tr><tr><th>NO.</th><th>SHEET</th><th>TITLE</th></tr></thead><tbody><tr><td>1</td><td>WW 1</td><td>COVER SHEET</td></tr><tr><td>2</td><td>WW 2</td><td>EXISTING SITE LAYOUT</td></tr><tr><td>3</td><td>WW 3</td><td>WASTEWATER SYSTEM PLAN</td></tr><tr><td>4</td><td>WW 4</td><td>WASTEWATER SYSTEM SCHEMATIC AND DETAILS</td></tr><tr><td>5</td><td>WW 5</td><td>WASTEWATER SYSTEM SPECIFICATIONS (AND EROSION CONTROL NOTES)</td></tr></tbody></table>			WASTEWATER SHEETS			NO.	SHEET	TITLE	1	WW 1	COVER SHEET	2	WW 2	EXISTING SITE LAYOUT	3	WW 3	WASTEWATER SYSTEM PLAN	4	WW 4	WASTEWATER SYSTEM SCHEMATIC AND DETAILS	5	WW 5	WASTEWATER SYSTEM SPECIFICATIONS (AND EROSION CONTROL NOTES)
WASTEWATER SHEETS																							
NO.	SHEET	TITLE																					
1	WW 1	COVER SHEET																					
2	WW 2	EXISTING SITE LAYOUT																					
3	WW 3	WASTEWATER SYSTEM PLAN																					
4	WW 4	WASTEWATER SYSTEM SCHEMATIC AND DETAILS																					
5	WW 5	WASTEWATER SYSTEM SPECIFICATIONS (AND EROSION CONTROL NOTES)																					
PROJECT DESIGN AND OPERATION NOTES																							
<p>DESIGN FLOWS, VOLUMES, AND TREATMENT</p> <p>FACILITY TYPE: RESIDENTIAL UNIT FLOW BASIS: # OF BEDROOMS # OF UNITS: LEGALIZE 1 BEDROOM ADU DESIGN FLOWS: 375 GPD TREATMENT CATEGORY: CONVENTIONAL NEW SEPTIC TANK VOLUME: 1,500 GALLONS WASTEWATER STRENGTH: DOMESTIC RESIDENTIAL STRENGTH DOMESTIC STRENGTH DEFINITION: <220 MG/L BOD, <60 MG/L TSS, <60 MG/L TN</p> <p>SOIL TESTING RESULTS AND DISPOSAL DESIGN</p> <p>SITE TEST PIT: MYER ENGINEERING OBSERVED THE SOIL CHARACTERISTICS OF A TEST PIT EXCAVATED TO A DEPTH OF 24' BELOW GROUND LEVEL (BGL). THE LOCATION OF THE TEST PIT IS PROVIDED ON THE PROJECT DESIGN PLANS. THE FOLLOWING SOIL PROFILE WAS OBSERVED:</p> <p>0'- 20' BGL: DARK BROWN LOAM 20'- 10' BGL: BROWN SANDY LOAM 10'- 13.5' BGL: LITE BROWN FINE GRAINED SAND (SWITCH TO 18" AUGER DRILL BIT) 13.5'- 20' BGL: TAN BROWN SAND 20'- 24' BGL: TAN MEDIUM GRAINED SAND GROUNDWATER WAS NOT ENCOUNTERED, AND GROUNDWATER INDICATORS WERE NOT PRESENT.</p> <p>SITE PERCOLATION TEST: TEST HOLE #1 (P-1): DEPTH = 7.0', RATE = 16.76 MPI TEST HOLE #2 (P-2): DEPTH = 4.0', RATE = 25.77 MPI TEST HOLE #3 (P-3): DEPTH = 3.0', RATE = 7.66 MPI TEST HOLE #4 (P-4): DEPTH = 7.0', RATE = 18.53 MPI TEST HOLE #5 (P-5): DEPTH = 3.0', RATE = 11.24 MPI TEST HOLE #6 (P-6): DEPTH = 4.0', RATE = 13.85 MPI OVERALL AVERAGE STABILIZED RATE = 14.6 MPI</p> <p>DESIGN AREA APPLICATION RATE: 0.73 GPD/SF REQUIRED EFFECTIVE LEACHING AREA: 514 SF DESIGN PRIMARY EFFECTIVE LEACHING AREA: 520 SF 100%+ DESIGN FUTURE EXPANSION EFFECTIVE AREA: 520 SF DESIGN PRIMARY TRENCH GEOMETRY: 2 X 1.5'W X 4'D (2.5' EFFECTIVE) X 65'L</p> <p>MAX EFFECTIVE AREA/LF: 45F/LF</p> <p>WATER SUPPLY: PRIVATE WELL</p> <p>OWNER IS RESPONSIBLE FOR GENERAL OPERATION AND MAINTENANCE OF THE WASTEWATER SYSTEM</p> <p>THE SEPTIC/WASTEWATER SYSTEM SHALL BE INSTALLED BY A QUALIFIED PROFESSIONAL.</p>																							

COVER SHEET

Jordan Site Improvement Project

107 Browns Valley Road
Watsonville CA 95076
APN: 107-211-09

CLIENT

JIM JORDAN
wesmattnike@hotmail.com
831-818-8403

MYER ENGINEERING, INC.

Civil Engineering Consulting Services

PAUL MYER, MS, PE
1796 LAUREL GLEN RD.
SOQUEL, CA 95073
(831) 800-2244
paul@myerengineering.com

REGISTERED PROFESSIONAL ENGINEER
PAUL MYER
C 80522
EXP 03/31/25
CIVIL
STATE OF CALIFORNIA

Drawn By
PEM

Checked By
PEM

Project No.
202250

Scale
AS SHOWN



Date
FEB 2023

Sheet No.

WW1

1 OF 5

No.	Revision/Issue	Date
-----	----------------	------



1 EXISTING SITE LAYOUT

SCALE: 1" = 40'

No.	Revision/Issue	Date

Drawn By PEM	Checked By PEM
Project No. 202250	Scale AS SHOWN
Date FEB 2023	
Sheet No.	



WW2
2 OF 5

MYER ENGINEERING, INC.
Civil Engineering Consulting Services
PAUL MYER, MS, PE
1796 LAUREL GLEN RD.
SOQUEL, CA 95073
(831) 800-2244
paul@myerengineering.com

CLIENT
JIM JORDAN
wesmatthike@hotmail.com
831-818-8403

Jordan Site Improvement Project
107 Browns Valley Road
Watsonville CA 95076
APN: 107-211-09

EXISTING SITE LAYOUT



No.	Revision/Issue	Date

WASTEWATER SYSTEM
PLAN

Jordan Site Improvement Project
107 Browns Valley Road
Watsonville CA 95076
APN: 107-211-09


CLIENT
JIM JORDAN
wesmatthike@hotmail.com
831-818-8403

MYER ENGINEERING, INC.
Civil Engineering Consulting Services
PAUL MYER, MS, PE
1796 LAUREL GLEN RD.
SOQUEL, CA 95073
(831) 800-2244
paul@myerengineering.com




REGISTERED PROFESSIONAL ENGINEER
PAUL MYER
C 80522
EXP 03/31/25
CIVIL
STATE OF CALIFORNIA
RENEWAL

Drawn By PEM	Checked By PEM
Project No. 202250	Scale AS SHOWN
Date FEB 2023	
Sheet No.	

WW3
3 OF 5



1 1,500 GALLON SEPTIC TANK
SCALE: AS DIMENSIONED



4 CONVENTIONAL LEACHFIELD
SCALE: AS DIMENSIONED

No.	Revision/Issue	Date

WASTEWATER SYSTEM
SCHEMATIC AND DETAILS

Jordan Site Improvement Project
107 Browns Valley Road
Watsonville CA 95076
APN: 107-211-09

CLIENT
JIM JORDAN
wesmattnike@hotmail.com
831-818-8403

MYER ENGINEERING, INC.
Civil Engineering Consulting Services
PAUL MYER, MS, PE
1796 LAUREL GLEN RD.
SOQUEL, CA 95073
(831) 800-2244
paul@myerengineering.com

REGISTERED PROFESSIONAL ENGINEER
PAUL MYER
C 80522
EXP 03/31/25
CIVIL
STATE OF CALIFORNIA

Drawn By
PEM
Project No.
202250
Date
FEB 2023
Sheet No.

Checked By
PEM
Scale
AS SHOWN

WW4
4 OF 5

GENERAL SPECIFICATIONS

THE FOLLOWING SPECIFICATIONS ARE FOR THE INSTALLATION OF THE ENHANCED WASTEWATER TREATMENT SYSTEM AT THE LOCATION SPECIFIED IN THE BORDER OF THESE DESIGN PLANS. THE ACCOMPANIED PLANS PRESENT THE GENERAL LAYOUT, PLUMBING CONFIGURATION, AND CONSTRUCTION DETAILS.

MATERIAL SPECIFICATIONS

THE FOLLOWING ARE MATERIAL SPECIFICATIONS FOR THE WASTEWATER SYSTEM COMPONENTS. ALL MATERIALS USED FOR THE CONSTRUCTION OF THIS PROJECT SHALL CONFORM TO THE FOLLOWING SPECIFICATIONS AND AS DESCRIBED IN THE ACCOMPANIED PLANS OR AN ENGINEER APPROVED EQUIVALENT.

1. SUBSURFACE TANKS

THE SUBSURFACE TANKS INCLUDE THE 1,500 GALLON WATER-TIGHT SEPTIC TANK.

1.1. 1,500 GALLON WATER-TIGHT SEPTIC TANK. THE SYSTEM SHALL BE CAPABLE OF TREATING DESIGN FLOW OF AT LEAST 600 GPD. DIMENSIONS, FITTING SIZES AND LOCATIONS, AND OPTIONAL ACCESSORIES SHALL BE INCLUDED AS SHOWN ON TANK DRAWINGS. THE TANK SHALL BE WATERTIGHT AND TESTED IN THE FIELD AFTER INSTALLATION.

1.2. PRODUCT STORAGE. THE SUBSURFACE TANKS SHALL BE CAPABLE OF STORING SEPTAGE LIMITED TO THE COLLECTION AND STORAGE OF HUMAN SOLID OR LIQUID ORGANIC WASTE.

1.3. PIPING. SDR35 PVC PIPE, SCHEDULE 40 PVC PIPE, OR ABS PIPE SHALL BE USED FOR INLET AND OUTLET PIPING AS SHOWN ON DRAWINGS. ALL PIPING SHALL BE FACTORY SEALED TO ENABLE FIELD TIGHTNESS TESTING WITH AT LEAST ONE PIPE OPENING PROVIDED WITH A THREADED FITTING FOR CONNECTING A PRESSURE TEST MANIFOLD.

1.4. ACCESS OPENINGS. ALL ACCESS OPENINGS SHALL BE 30 INCHES IN DIAMETER OR LARGER AS SHOWN ON THE PLANS. SHALL BE MANUFACTURED OF FIBERGLASS, CONCRETE OR CAST IRON WITH RESPECT TO SPECIFIED TRAFFIC RATING. LOCATIONS SHALL BE AS SHOWN ON TANK DRAWINGS. EACH MANHOLE SHALL HAVE A WATERTIGHT RISER TO FINISH GRADE.

1.5. RISERS. RISERS SHALL BE REQUIRED FOR ACCESS TO INTERNAL VAULTS AND ACCESS INTO THE TANKS FOR SEPTAGE PUMPING. ALL RISERS SHALL BE CONSTRUCTED WITH WATERTIGHT SEALS PROVIDED. RISERS SHALL BE A MINIMUM OF 30" IN NOMINAL DIAMETER WHEN THE DEPTH OF BURY IS 36" OR GREATER. TO ENSURE PRODUCT COMPATIBILITY, RISERS, LIDS, AND ATTACHMENT COMPONENTS SHALL BE SUPPLIED BY A SINGLE MANUFACTURER AND, WHERE APPLICABLE, SHALL BE FACTORY EQUIPPED WITH THE FOLLOWING:

1.5.1. ADHESIVE. WHEN BONDING TO THE RISER RINGS, AN EPOXY PROVIDED BY THE MANUFACTURER SHALL BE USED. ADHESIVES AND SEALANTS SHALL BE WATERPROOF, CORROSION RESISTANT, AND APPROVED FOR THE INTENDED APPLICATION. THE RISER-TO-TANK CONNECTION SHALL BE WATERTIGHT AND STRUCTURALLY SOUND. THE RISER-TO-TANK CONNECTION SHALL BE CAPABLE OF WITHSTANDING A VERTICAL UPLIFT OF 5,000 POUNDS TO PREVENT RISER SEPARATION DUE TO TANK SETTLEMENT, FROST HEAVE, AND VEHICLE TRAFFIC OVER THE TANK.

1.5.2. LIDS. ONE LID SHALL BE FURNISHED WITH EACH ACCESS RISER. LIDS SHALL BE WATERPROOF, CORROSION RESISTANT, AND UV RESISTANT. LIDS SHALL BE FLAT, WITH NO NOTICEABLE UPWARD DOME. LIDS SHALL NOT ALLOW WATER TO POND ON THEM. LIDS SHALL FORM A WATERTIGHT SEAL WITH THE TOP OF RISER. TRAFFIC-RATED LIDS SHALL BE CAPABLE OF WITHSTANDING A TRUCK WHEEL LOAD (36 SQUARE INCHES) OF 2500 POUNDS FOR 60 MINUTES WITH A MAXIMUM VERTICAL DEFLECTION OF 1-1/2". LIDS SHALL BE PROVIDED WITH TAMPER-RESISTANT STAINLESS STEEL FASTENERS AND A TOOL FOR FASTENER REMOVAL. TAMPER-RESISTANT FASTENERS INCLUDE RECESSED DRIVES, SUCH AS HEX, TORX, AND SQUARE. FASTENERS THAT CAN BE REMOVED WITH COMMON SCREWDRIVERS, SUCH AS SLOTTED AND PHILLIPS, OR FASTENERS THAT CAN BE REMOVED WITH STANDARD TOOLS, SUCH AS PLIERS OR CRESCENT WRENCHES, ARE NOT CONSIDERED TAMPER-RESISTANT. TO PREVENT A TRIPPING HAZARD, FASTENERS SHALL NOT EXTEND ABOVE THE SURFACE OF THE LID.

1.5.3. RISER INSTALLATION. RISER INSTALLATION SHALL BE IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS.

2. PIPING AND FITTINGS

THE TYPE OF PIPE MATERIALS AND FITTINGS SHALL BE AS DESIGNATED ON THE PLANS AND SHALL COMPLY WITH THE FOLLOWING:

2.1. FITTINGS AND COUPLINGS
THE FITTINGS AND COUPLINGS FOR PVC PIPES SHALL BE THREADED OR SLIP-FITTED TAPERED SOCKET SOLVENT WELD. THREADED ADAPTERS SHALL BE PROVIDED WITH SOCKET PIPE FOR CONNECTIONS TO THREADED PIPE.

3. VALVES

3.1. GENERAL
VALVES SHALL BE OF THE SIZE, TYPE, AND CAPACITY DESIGNATED ON THE PLANS OR IN THE SPECIFICATIONS AND SHALL COMPLY WITH THE REQUIREMENTS SPECIFIED HEREIN. ALL VALVES ON PRESSURIZED PORTIONS OF THE SYSTEM SHALL BE CAPABLE OF SATISFACTORY PERFORMANCE AT WORKING PRESSURE OF 150 PSI. ALL VALVES ON GRAVITY PORTIONS OF THE SYSTEM SHALL BE RATED FOR AT LEAST TWICE THE ESTIMATED STATIC HEAD ABOVE THE VALVE. VALVES SHALL BE DESIGNED TO PERMIT DISASSEMBLY TO REPLACE SEALING COMPONENTS WITHOUT REMOVAL OF THE VALVE BODY FROM THE PIPELINE, SUCH AS TRUE UNION BALL VALVES AND CHECK VALVES.

4. PUMP SYSTEMS

ALL PUMP SYSTEMS SHALL BE INSTALLED PER MANUFACTURER RECOMMENDATIONS. IF THERE IS A CONFLICT BETWEEN MANUFACTURER RECOMMENDATIONS, AND THE DESIGN PLANS, THE PROJECT ENGINEER SHALL BE CONTACTED FOR APPROVAL OF INSTALLATION CONFIGURATION.

5. ADDITIONAL COMPONENTS

ALL COMPONENTS SHALL BE INSTALLED PER MANUFACTURER RECOMMENDATIONS. IF THERE IS A CONFLICT BETWEEN MANUFACTURER RECOMMENDATIONS, AND THE DESIGN PLANS, THE PROJECT ENGINEER SHALL BE CONTACTED FOR APPROVAL OF INSTALLATION CONFIGURATION.

6. LEACHFIELDS

THE LEACHFIELD SYSTEM SHALL PROVIDE ADDITIONAL TREATMENT AND DISPOSAL OF THE WASTEWATER. THE SYSTEM SHALL BE CONSTRUCTED AS SHOWN ON PLANS.

6.1. CLEAN DRAIN ROCK
THE DRAIN ROCK SHALL BE LOCATED AS SHOWN IN THE ACCOMPANYING PLANS. THE ROCK SHALL BE CLEAN, DOUBLE WASHED GRAVEL RANGING FROM 3/4"Ø TO 1-1/2"Ø WITH FINES LESS THAN 1%.

6.2. FILTER FABRIC
THE FILTER FABRIC SHALL BE PLACED ON TOP OF THE GRAVEL ROCK BED. THE FABRIC SHALL BE A GEOTEXTILE SYNTHETIC FILTER FABRIC SUCH AS MIRAFI 1100N, DUPONT TYPAF 4 OR 6 OZ/50 YO, OR APPROVED EQUIVALENT. THE FABRIC SHALL COVER AN AREA SUCH THAT IT EXTENDS 1 FOOT BEYOND THE TRENCH IN EACH DIRECTION.

6.3. SOIL COVER
THE SOIL COVER SHALL BE PLACED OVER THE LEACHFIELDS TO REDUCE EROSION AND SLOPE INSTABILITY. THE SOIL SHALL BE A SANDY LOAM TO INCREASE THE POTENTIAL FOR AIR THROUGH THE DEPTH OF THE SOIL. THE SOIL SHALL BE COMPACTED TO A MINIMUM OF 90% RELATIVE COMPACTION IN LANDSCAPE AREAS AND 95% RELATIVE COMPACTION IN DRIVEWAYS AND ROADWAYS.

CONSTRUCTION SPECIFICATIONS

THE CONSTRUCTION OF THE PROJECT SHALL CONFORM TO THE PLANS AND FOLLOWING SPECIFICATIONS. ALL NECESSARY CONSTRUCTION PERMITS SHALL BE OBTAINED PRIOR TO COMMENCEMENT OF ALL SITE WORK.

1. PRECONSTRUCTION CONFERENCE

THE CONTRACTOR SHALL HAVE A PRECONSTRUCTION MEETING WITH THE ENGINEER AND OWNER AT LEAST ONE WEEK PRIOR TO COMMENCEMENT OF SITE WORK. THE ENGINEER SHALL BE CONTACTED 48 HOURS PRIOR TO THE MEETING CONFERENCE. THE MEETING SHOULD BE CONDUCTED TO REVIEW THE DESIGN,

MATERIAL, AND CONSTRUCTION SPECIFICATIONS. ALL CONTRACTOR PROPOSED REVISIONS IN THE DESIGN SHALL BE APPROVED BY THE ENGINEER. THE INSTALLATION MUST BE INSPECTED BY THE ENGINEER FOR CONFORMANCE TO THE DESIGN.

2. STAKING

THE CONTRACTOR WILL PROVIDE SUFFICIENT HORIZONTAL AND VERTICAL CONTROL FOR INSTALLATION OF THE WORK AT DATUM POINTS NECESSARY TO ESTABLISH ALIGNMENT AND GRADE. THE PROTECTION AND CARE OF THE STAKES ONCE SET, SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.

3. EXCAVATION

ALL EXCAVATION WORK SHALL BE MADE TO THE LINES, GRADES AND DIMENSIONS SHOWN IN THE ACCOMPANIED PLANS. EXCAVATIONS SHALL BE PERFORMED IN THE DAY AND IN A MANNER THAT MINIMIZES EROSION, FLOODING AND SEDIMENTATION. EXCAVATED SOILS THAT ARE TO BE STOCKPILED ON-SITE SHALL BE PLACED IN A LOCATION AND MANNER THAT MINIMIZES EROSION AND CONTROLS SEDIMENTATION.

THE CONTRACTOR SHALL TAKE EXTRA PRECAUTION WHERE EXCAVATION EQUIPMENT MAY ENCOUNTER EXISTING UNDERGROUND UTILITIES AND OTHER FACILITIES OF ANY NATURE. CONTRACTOR SHALL PERSON HIS OPERATION IN SUCH A MANNER AND SHALL EXERCISE THE GREATEST OF CARE SO AS NOT TO INJURE IN ANY MANNER EXISTING UNDERGROUND UTILITIES, MAINS OR FACILITIES OF ANY NATURE. SHOULD THE CONTRACTOR INJURE, BREAK OR DAMAGE EXISTING UNDERGROUND UTILITIES, MAINS, OR FACILITIES OF ANY NATURE IN ANY MANNER, THEY SHALL REPAIR THE SAME AT THEIR OWN EXPENSE. IF IT DOES NOT APPEAR FEASIBLE THAT THE CONTRACTOR CAN MAKE NEEDED REPAIRS, THEN SUCH REPAIRS SHALL BE MADE BY THE OWNER AND THE CONTRACTOR SHALL BE CHARGED FOR SUCH REPAIRS.

4. POLLUTION CONTROL

4.1. WATER POLLUTION
THE CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THAT ALL PERMITTING REQUIREMENTS RELEVANT TO THE CONSTRUCTION OF THE PROJECT ARE MET AT ALL TIMES. ACTIONS BY THE CONTRACTOR, THE SUBCONTRACTORS OR EMPLOYEES THEREOF RESULTING IN NONCOMPLIANCE OF PERMITTING REQUIREMENTS MAY BE GROUNDS FOR TERMINATION OF THIS CONTRACT.

4.2. NOISE POLLUTION
IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO KEEP NOISE POLLUTION, DUE TO THESE CONSTRUCTION ACTIVITIES, AS LOW AS POSSIBLE.

4.3. SOIL CONTAMINATION
THE CONTRACTOR SHALL NOT ALLOW REGULATED MATERIALS TO SPILL ON THE PROJECT SITE. ANY SPILLAGE OR REGULATED MATERIALS RESULTING FROM THE CONTRACTOR'S OPERATION SHALL BE REMOVED IMMEDIATELY BY THE CONTRACTOR AT THE CONTRACTOR'S EXPENSE.

4.4. STORAGE OF REGULATED MATERIALS
THE STORAGE AND USE OF ANY REGULATED MATERIALS SHALL MEET ALL REQUIREMENTS OF LOCAL, STATE, AND FEDERAL REGULATORY AGENCIES. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO SATISFY THE REQUIREMENTS OF ANY REGULATORY AGENCY FOR THE STORAGE, MONITORING, USAGE, TRANSPORTATION, SAFETY, REPORTING AND ANY OTHER REQUIREMENTS REGARDING THE MANAGEMENT OF REGULATED MATERIALS ON AND OFF THE PROJECT SITE.

5. SITE WORK

5.1. MOBILIZATION
THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL PREPARATORY WORK AND PLACEMENT OF MATERIALS IN A STAGING AREA REQUIRED FOR CONSTRUCTION OPERATIONS INCLUDING, BUT NOT LIMITED TO, THOSE NECESSARY FOR THE MOVEMENT OF PERSONNEL, EQUIPMENT, SUPPLIES, AND INCIDENTALS TO THE PROJECT SITE; FOR THE ESTABLISHMENT OF FACILITIES NECESSARY FOR WORK ON THE PROJECT; PROVIDING POLLUTION CONTROL MEASURES; AND FOR ALL OTHER WORK AND OPERATIONS WHICH MUST BE PERFORMED.

THE CONTRACTOR SHALL PROVIDE MATERIALS, NOT SPECIFICALLY DESCRIBED BUT REQUIRED FOR PROPER COMPLETION OF THE WORK OF THIS SECTION, AS SELECTED BY THE CONTRACTOR SUBJECT TO THE APPROVAL OF THE COUNTY.

5.2. CLEARING AND GRUBBING
CLEAR THE SITE AS SHOWN ON THE DRAWINGS AND AS SPECIFIED IN THIS SECTION. CLEARING AND GRUBBING SHALL CONSIST OF ALL WORK INCLUDING, BUT NOT LIMITED TO, SALVAGED MATERIALS REMOVAL, PROVIDING AND INSTALLING TEMPORARY EROSION CONTROL, AND PLACEMENT OF TREES, TREE BRANCHES, TREE STUMPS, BRUSH, ROOTS, BOULDERS, SHRUBS, SEDIMENT, AND ALL OBJECTIONABLE MATERIALS IN AN AGREED UPON LOCATION ADJACENT TO THE WORK SITE.

EXAMINE THE AREAS AND CONDITIONS UNDER WHICH THE WORK OF THIS SECTION WILL BE PERFORMED. CORRECT CONDITIONS DETRIMENTAL TO TIMELY AND PROPER COMPLETION OF THE WORK. DO NOT PROCEED UNTIL UNSATISFACTORY CONDITIONS ARE CORRECTED.

ALL WASTES DISPOSAL SHALL BE CONDUCTED AS FOLLOWS:

- A. REMOVE WASTE FROM CLEARING OPERATIONS.
- B. DISPOSE OF AWAY FROM THE SITE IN A LEGAL MANNER.
- C. DO NOT STORE OR PERMIT DEBRIS TO ACCUMULATE ON THE JOB SITE.
- D. DO NOT BURN DEBRIS AT THE SITE.

6. DELETERIOUS MATERIALS

MATERIALS CONTAINING AN EXCESS OF 5% (BY WEIGHT) OF VEGETATION OR OTHER DELETERIOUS MATTER MAY BE UTILIZED IN AREAS OF LANDSCAPING OR OTHER NON-STRUCTURAL FILLS. DELETERIOUS MATERIAL INCLUDES ALL VEGETATIVE AND NON-MINERAL MATTER, AND ALL NON-REDUCIBLE STONE, RUBBLE AND/OR MINERAL MATTER OF GREATER THAN 6 INCHES.

7. UTILITY TRENCHES

- A. A SELECT, NONCORROSIVE, GRANULAR, EASILY COMPACTED MATERIAL SHOULD BE USED AS BEDDING AND SHADING IMMEDIATELY AROUND UTILITY PIPES. THE SITE SOILS MAY BE USED FOR TRENCH BACKFILL ABOVE THE SELECT MATERIAL. IF OBTAINING COMPACTION IS DIFFICULT WITH THE SITE SOILS, USE OF A MORE EASILY COMPACTED SAND MAY BE DESIRABLE. THE UPPER FOOT OF BACKFILL IN LANDSCAPED OR OTHER OPEN AREAS SHOULD CONSIST OF NATIVE MATERIAL TO REDUCE THE POTENTIAL FOR SEEPAGE OF WATER INTO THE BACKFILL.
- B. TRENCH BACKFILL IN THE UPPER 12 INCHES OF SUBGRADE BENEATH AREAS TO RECEIVE PAVEMENT SHOULD BE COMPACTED TO A MINIMUM OF 95 PERCENT OF MAXIMUM DRY DENSITY. TRENCH BACKFILL IN OTHER AREAS SHOULD BE COMPACTED TO A MINIMUM OF 90 PERCENT OF MAXIMUM DRY DENSITY. JETTING OF UTILITY TRENCH BACKFILL SHOULD NOT BE ALLOWED.

8. PIPE INSTALLATION

8.1. GENERAL
PIPE SHALL BE JOINED BY SOCKET TYPE SOLVENT-WELDED FITTINGS OR THREADED FITTINGS. PLASTIC PIPE SHALL BE CUT SQUARE, EXTERNALLY CHAMFERED APPROXIMATELY 10 TO 15 DEGREES, AND ALL BURRS AND FINIS REMOVED. SOLVENT-WELDED JOINTS SHALL BE MADE IN ACCORDANCE WITH ASTM D 2855. THE SOLVENT RECOMMENDED BY THE MANUFACTURER SHALL BE USED.

CARE SHALL BE EXERCISED IN ASSEMBLING A PIPELINE WITH SOLVENT WELDED JOINTS SO THAT STRESS ON PREVIOUSLY MADE JOINTS IS AVOIDED. HANDLING OF THE PIPES FOLLOWING JOINTING, SUCH AS LOWERING THE ASSEMBLED PIPELINE INTO THE TRENCH, SHALL NOT OCCUR PRIOR TO THE SET TIMES SPECIFIED BY THE MANUFACTURER.

SOLVENTS SHALL BE APPLIED TO PIPE ENDS IN SUCH A MANNER THAT NO MATERIAL IS DEPOSITED ON THE INTERIOR SURFACE OF THE PIPE OR EXTRUDED INTO THE INTERIOR OF THE PIPE DURING JOINTING. EXCESS CEMENT ON THE EXTERIOR OF THE JOINT SHALL BE WIPED CLEAN IMMEDIATELY AFTER ASSEMBLY.

THREADED PIPE JOINTS SHALL BE MADE USING TEFLON TAPE OR OTHER APPROVED JOINTING MATERIAL. SOLVENT SHALL NOT BE USED WITH THREADED JOINTS. PLASTIC PIPE WHICH HAS BEEN NICKED, SCARRED, OR OTHERWISE DAMAGED SHALL BE REMOVED AND REPLACED. PLASTIC PIPE SHALL BE SNAKED FROM SIDE TO SIDE IN THE TRENCH TO ALLOW 1 FOOT OF EXPANSION AND CONTRACTION PER 100 FEET OF STRAIGHT RUN. THE PIPELINE SHALL NOT BE EXPOSED TO WATER FOR 24 HOURS AFTER THE LAST SOLVENT-WELDED JOINT IS MADE.

8.2 GRAVITY PIPE
GRAVITY PIPE FOR WASTEWATER SHALL PROVIDE 2 FT VERTICAL AND 10 FT HORIZONTAL CLEARANCE FROM WATER LINES, AND SHALL CROSS SUCH LINES AS NEARLY AS POSSIBLE TO 90 DEGREES, IF CROSSING CAN NOT BE AVOIDED.

PIPE SLOPES SHALL NOT BE LESS THAN 2% FOR 4"Ø PIPE. PIPES SHALL ENTER AND LEAVE CONNECTIONS AS CLOSE TO PARALLEL AS POSSIBLE, BUT IN NO WAY TO EXCEED AN ANGLE OF 45°. 90° TEE CONNECTIONS ARE NOT ALLOWED.

8.3 GENERAL TRENCHING
EXCAVATION OF PIPE TRENCHES SHALL FOLLOW NEAT AND PARALLEL LINES, WITH TRENCH WIDTH, IN GENERAL, TO BE ONE FOOT, WITH SUCH WIDENING, AS REQUIRED TO PLACE VALVES AND FITTINGS WITH A MINIMUM OF 4 INCH CLEARANCE TO TRENCH WALL. THE TRENCH SHALL BE NO LESS THAN 24 INCHES DEEP, EXCEPT WHEN IT IS NECESSARY, TO AVOID UNDERGROUND OBSTRUCTIONS OR ROCKY CONDITIONS. IN ALL CASES, THE PIPE SHALL BE PLACED ON A BEDDING OF IMPORTED OR NATIVE MATERIAL PROVIDING CONTINUOUS SUPPORT THROUGHOUT ITS LENGTH.

BACKFILL FOR THE PIPE TO THE TOP OF THE PIPE PLUS 4 INCHES SHALL BE SELECTED OR IMPORTED SANDY MATERIAL, FREE OF STONE, CLAY, LIMBS OR OTHER DELETERIOUS MATERIALS IN EXCESS OF 1/2 INCH MAXIMUM DIMENSION, PLACED AND TAMPED AND/OR PADDED ABOUT THE PIPE TO ENSURE PROPER BEDDING PRIOR TO COMPLETION OF TRENCH FILL. THE REMAINING BACKFILL SHALL BE PLACED AT 90% RELATIVE COMPACTION.

9. FLUSHING AND TESTING

AFTER COMPLETION, ALL PIPELINES SHALL BE THOROUGHLY FLUSHED TO REMOVE DIRT, SCALE, OR OTHER MATERIAL. AFTER FLUSHING, THE LINE SHALL BE PRESSURE TESTED. ALL EQUIPMENT, MATERIALS AND LABOR NECESSARY TO PERFORM THE TESTS SHALL BE FURNISHED BY THE CONTRACTOR AND ALL TESTS SHALL BE CONDUCTED IN THE PRESENCE OF THE OWNER OR ENGINEER.

THE CONTRACTOR SHALL PERFORM A TEST TO DEMONSTRATE THAT THE TANKS AND BASINS ARE WATER TIGHT. THE INLET AND OUTLET PIPES OF THE TANKS SHALL BE CAPPED AND THE TANKS SHALL BE COMPLETELY FILLED WITH WATER. THE WATER LEVEL SHALL REMAIN CONSTANT FOR MORE THAN 24 HOURS, OR DURATION BY THE REVIEWING AGENCY JURISDICTION, WHICHEVER IS GREATER, TO DETERMINE IF IT IS WATER TIGHT.

10. OPERATIONAL TEST

THE PERFORMANCE OF ALL COMPONENTS OF THE SYSTEMS SHALL BE EVALUATED BY THE CONTRACTOR.

DURING THE TEST PERIOD AND AT LEAST 15 DAYS PRIOR TO FINAL INSPECTION, THE SYSTEM SHALL OPERATE SATISFACTORILY DURING SUCH PERIOD. ALL NECESSARY REPAIRS, REPLACEMENTS, AND ADJUSTMENTS SHALL BE MADE UNTIL ALL EQUIPMENT, ELECTRICAL WORK, CONTROLS, AND INSTRUMENTATION ARE FUNCTIONING IN ACCORDANCE WITH THE CONTRACTORS DOCUMENTS OR MANUFACTURER SPECIFICATIONS.

11. AS-BUILT DRAWINGS

THE CONTRACTOR SHALL PROVIDE THE OWNER WITH A SET OF AS-BUILT DRAWINGS OF THE LAYOUT AND CONSTRUCTION OF THE SYSTEM.

12. OTHER ITEMS

ANY PROCEDURES NOT NOTED OR INCLUDED IN THE ENGINEERING PLANS OR SPECIFICATIONS SHALL BE APPROVED BY THE PROJECT ENGINEER PRIOR TO IMPLEMENTATION.

EROSION CONTROL NOTES:

GENERAL. THE CONTRACTOR SHALL INSTALL, MAINTAIN AND INSPECT EROSION CONTROL AND TEMPORARY STORMWATER CONTROL MEASURES TO CONTROL SEDIMENT AND RUNOFF IN ACCORDANCE WITH THESE PLANS AND THE LOCAL JURISDICTION.

1.1. THE CONSTRUCTION OF THIS PROJECT IS NOT EXPECTED TO OCCUR DURING THE WINTER SEASON (OCTOBER 15TH THROUGH APRIL 15TH).

1.2. THE CONTRACTOR SHALL BE RESPONSIBLE FOR EROSION AND SEDIMENT CONTROL BMP INSTALLATION AND MAINTENANCE.

1.3. ALL GRADING SHALL CONFORM TO THE LOCAL GRADING ORDINANCE, EROSION CONTROL ORDINANCES, AND CALIFORNIA BUILDING CODE.

1.4. ALL DISTURBED SURFACES SHALL BE PREPARED AND MAINTAINED TO CONTROL EROSION AND TO ESTABLISH NATIVE OR NATURALIZED VEGETATIVE GROWTH COMPATIBLE WITH THE AREA. THIS CONTROL SHALL CONSIST OF: A. EFFECT TEMPORARY PLANTING SUCH AS RYE GRASS, SOME OTHER FAST-GERMINATION SEED, AND MULCHING WITH STRAW AND/OR OTHER SLOPE STABILIZATION MATERIAL; B) PERMANENT PLANTING OF NATIVE OR NATURALIZED DROUGHT RESISTANT SPECIES OF SHRUBS, TREES, OR OTHER VEGETATION, PURSUANT TO THE COUNTY'S LANDSCAPE CRITERIA, WHEN THE PROJECT IS COMPLETED; C) MULCHING, FERTILIZING, WATERING OR OTHER METHODS MAY BE REQUIRED TO ESTABLISH NEW VEGETATION, ON SLOPES LESS THAN 20%, TOPSOIL SHOULD BE STOCKPILED AND REAPPLIED.

SEED AND MULCH. ALL AREAS ON- AND OFF-SITE EXPOSED DURING CONSTRUCTION ACTIVITIES, IF NOT PERMANENTLY LANDSCAPED PER PLAN, SHALL BE PROTECTED BY MULCHING AND/OR HAND BROADCASTING OF THE FOLLOWING STERIL, WEED FREE, SEED MIX AND INCORPORATED OVER ALL DISTURBED SLOPES:

BROMUS CARINATUS 10#/ACRE
LEYMUS TRITICOIDES 8#/AC
HORDEUM BRACHYANTHERUM 5#/AC
FESTUCA RUBRA 8#/AC
DESCHAMPSIA CESPIIOSA 8#/AC

THE MIX/APPLICATION SHALL ALSO CONTAIN:
- FERTILIZER (6-3-3) SHALL BE HAND BROADCAST AND INCORPORATED AT 30-LB/ACRE OVER ENTIRE AREA.
- MYCHORRHIZAL FUNGI SHALL BE ADDED AT 50 LB/ ACRE.
- IF HYDROSEEDING, ADD MULCH AND TACKIFIER TO ABOVE.

ALL EXCAVATED MATERIAL SHALL BE REMOVED TO AN APPROVED DISPOSAL SITE OR DISPOSED OF ON-SITE IN A MANNER THAT WILL NOT CAUSE EROSION.

CONCRETE WASHOUT. TEMPORARY CONCRETE WASHOUT FACILITIES SHALL BE LOCATED A MINIMUM OF 50 FEET FROM STORM DRAIN INLETS, OPEN DRAINAGE FACILITIES, AND WATERCOURSES. THE CONCRETE WASHOUT FACILITY SHALL BE BELOW GRADE AND CONSTRUCTED WITH A MINIMUM LENGTH AND MINIMUM WIDTH OF 10 FEET. TEMPORARY CONCRETE FACILITIES SHALL BE CONSTRUCTED AND MAINTAINED IN SUFFICIENT QUANTITY AND SIZE TO CONTAIN ALL LIQUID AND CONCRETE WASTE GENERATED BY WASHOUT OPERATIONS. THE WASHOUT SHALL HAVE A 10 ML POLYETHYLENE PLASTIC LINER. WHEN CONCRETE WASHOUT FACILITIES ARE NO LONGER REQUIRED FOR THE WORK, THE HARDENED CONCRETE AND MATERIALS FOR THE WASHOUT SHALL BE REMOVED AND DISPOSED OF. HOLES, DEPRESSIONS, OR OTHER GROUND DISTURBANCES CAUSED BY THE REMOVAL OF THE CONCRETE WASHOUT SHOULD BE BACKFILLED AND REPAIRED.

OTHER PROVISIONS. IF CONSTRUCTION OCCURS BETWEEN OCTOBER 15TH AND APRIL 15TH, EXPOSED SOIL NOT INVOLVED IN IMMEDIATE CONSTRUCTION ACTIVITY SHALL BE PROTECTED FROM EROSION AT ALL TIMES. AFTER APRIL 15TH, EROSION CONTROL MEASURES SHALL BE IN PLACE DURING INCLEMENT WEATHER.

EROSION CONTROL MEASURES SHALL BE KEPT IN PLACE BY THE CONTRACTOR UNTIL NATIVE VEGETATION HAS BEEN ESTABLISHED AND PROVIDES NECESSARY SLOPE COVER (MINIMUM 70% COVER).

WASTEWATER SYSTEM SPECIFICATIONS

Jordan Site Improvement Project

107 Browns Valley Road
Watsonville CA 95076

APN: 107-211-09

CLIENT

JIM JORDAN
wesmattnike@hotmail.com
831-818-8403

MYER ENGINEERING, INC.
Civil Engineering Consulting Services

PAUL MYER, MS, PE
1796 LAUREL GLEN RD.
SOQUEL, CA 95073
(831) 800-2244
paul@myerengineering.com


REGISTERED PROFESSIONAL ENGINEER
PAUL MYER
C 80522
EXP 03/31/25
CIVIL
STATE OF CALIFORNIA

Drawn By	Checked By
PEM	PEM
Project No.	Scale
202250	AS SHOWN
Date	
FEB 2023	
Sheet No.	


WW5

5 OF 5


No.	Revision/Issue	Date




NORTH ELEVATION
SCALE: 1/4" = 1'-0"




EAST ELEVATION
SCALE: 1/4" = 1'-0"



WEST ELEVATION
SCALE: 1/4" = 1'-0"



SOUTH ELEVATION
SCALE: 1/4" = 1'-0"



FLOOR PLAN
SCALE: 1/4" = 1'-0"

HEATED AREA: 989 SF
COVERED PORCH: 354 SF

REVISIONS	BY

ROBIN ALAGA
250 Evening Hill Lane, Covellitos, CA 95076
Phone: (831) 724-4994 Cell: (831) 419-4979
e-mail: alagabn@gmail.com

JORDAN A.D.U.
James Jordan 831.818.8403 wesmattnike@hotmail.com
107 Brown's Valley Road Watsonville, CA 95076
A.P.N. 107 - 211 - 09

Robin Alaga

DRAWN ROBIN
CHECKED
DATE 1-MAY-25
SCALE 1/4" = 1'-0"
JOB NO. 25-21
SHEET 2
OF SHEETS